



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

NFPA 1901-2009

The National Fire Protection Association "Standard for Automotive Fire Apparatus", 2009 edition, is hereby adopted and made a part of these specifications, the same as if it were written out in full detail, with the exception of the section dealing with "Equipment Recommended for Various Types of Apparatus". Bidders shall provide the equipment requested herein and the buyer shall supply the rest before the apparatus is put into service. It is the intent of the purchaser to purchase an apparatus that meets 100% of the minimum standards defined and outlined in NFPA 1901-2009 edition. There are to be no exceptions to this requirement.

PREREQUISITE BIDDING REQUIREMENTS

Any manufacturer submitting a proposal or bid, to these specifications, shall meet the following conditions:

- The manufacturer of the apparatus herein specified, shall be wholly owned (100%) and managed by a Company, Corporation, and/or Parent Company that is wholly based and permanently resides in the United States of America.
- The Company, Corporation, and/or Parent Company, and all assets belonging to such, shall be wholly owned and managed (100%) by the entities specified above.
- Any proposal, bid, or response to these specifications by any foreign based, owned, or managed (in part or in whole) Company, Corporation, and/or Parent Company shall be cause for immediate rejection.
- Any proposal, bid, or response to these specifications by any Company, Corporation, and/or Parent Company, that is owned, operated, managed, or held in contract, in part or wholly by a partnership or other agreement, shall be cause for immediate rejection.

Exceptions to these conditions will not be allowed under any circumstances.

CONSTRUCTION DOCUMENTATION

The contractor shall supply, at the time of delivery, at least one (1) copy of the following documents:

1. The manufacturers record of apparatus construction details, including the following information:
 - Owners name and address
 - Apparatus manufacturer, model, and serial number
 - Chassis make, model, and serial number



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

- GAWR of front and rear axles
- Front tire size and total rated capacity in pounds or kilograms
- Rear tire size and total rated capacity in pounds or kilograms
- Chassis weight distribution in pounds with water and manufacturer mounted equipment (front and rear)
- Engine make, model, serial number, rated horsepower and related speed, and governed speed
- Type of fuel and fuel tank capacity
- Electrical system voltage and alternator output in amps
- Battery make, model, and capacity in cold cranking amps (CCA)
- Chassis transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio
- If applicable, the pump make, model, rated capacity in gallons or liters per minute, and serial number
- Pump transmission make, model, serial number, and gear ratio, if unit is equipped with a pump
- If applicable, the auxiliary pump make, model, rated capacity in gallons or liters per minute, and serial number
- Water tank certified capacity in gallons or liters
- On aerial apparatus, the device type, rated vertical height in feet or meters, rated horizontal reach in feet or meters, and rated capacity in pounds or kilograms
- Paint manufacturer and paint number(s)
- Company name and signature of responsible company representative

2. Certification of slip resistance of all stepping, standing, and walking surfaces

3. If the apparatus has a fire pump, a copy of the following shall be provided: pump manufacturers certification of suction capability, apparatus manufacturers approval for stationary pumping applications, engine manufacturers certified brake horsepower curve showing the maximum governed speed, pump manufacturers certification of the hydrostatic test, and the certification of inspection and test for the fire pump



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

4. If the apparatus has an aerial device, the certification of inspection and test for the aerial device, and all the technical information required for inspections to comply with NFPA 1914, Standard for Testing Fire Department Aerial Devices
5. If the apparatus has a fixed line voltage power source, the certification of the test for the fixed power source
6. If the apparatus is equipped with an air system, test results of the air quality, the SCBA fill station, and the air system installation
7. Weight documents from a certified scale showing actual loading on the front axle, rear axle(s), and overall fire apparatus (with the water tank full but without personnel, equipment, and hose)
8. Written load analysis and results of the electrical system performance tests
9. When the apparatus is equipped with a water tank, the certification of water tank capacity

OPERATION AND SERVICE DOCUMENTATION

The contractor shall supply, at time of delivery, at least two (2) sets of complete operation and service documentation covering the completed apparatus as delivered and accepted. The documentation shall address at least the inspection, service, and operations of the fire apparatus and all major components thereof. The contractor shall also provide documentation of the following items for the entire apparatus and each major operating system or major component of the apparatus:

1. Manufacturer's name and address
2. Country of manufacturer
3. Source of service and technical information
4. Parts and replacement information
5. Descriptions, specifications, and ratings of the chassis, pump, and aerial device
6. Wiring diagrams for low voltage and line voltage systems to include the following information: representations of circuit logic for all electrical components and wiring, circuit identification, connector pin identification, zone location of electrical components, safety interlocks, alternator-battery power distribution circuits, and input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
7. Lubrication charts
8. Operating instructions for the chassis, any major components such as a pump or aerial device, and any auxiliary systems
9. Precautions related to multiple configurations of aerial devices, if applicable
10. Instructions regarding the frequency and procedure for recommended maintenance



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

11. Overall apparatus operating instructions
12. Safety considerations
13. Limitations of use
14. Inspection procedures
15. Recommended service procedures
16. Troubleshooting guide
17. Apparatus body, chassis, and other component manufacturers warranties
18. Special data required by this standard
19. Copies of required manufacturer test data or reports, manufacturer certifications, and independent third-party certifications of test results
20. A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus

The contractor shall deliver with the apparatus all manufacturers operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

STATEMENT OF EXCEPTIONS

The proposed apparatus as described in this specification document and all related material with the bid package shall meet or exceed all applicable sections for the category of apparatus as defined by NFPA 1901, unless specifically noted within this specification or other official documents associated with this bid.

Should any area, section or portion of the apparatus not meet the intent and applicable requirements, a clearly defined listing or explanation of what and why compliance was not achieved shall be provided to the purchaser at the time of delivery.

INTENT OF SPECIFICATIONS

It is the intent of these specifications to cover the furnishing and delivery to the purchaser of a complete apparatus equipped as herein specified. With a view to obtaining the best results and the most acceptable apparatus for service in the fire department, these specifications cover the general requirements as to the type of construction, together with certain details as to finish, equipment, and appliances with which the successful bidder must conform. Minor details of construction and materials where not otherwise specified are left to the discretion of the contractor, who shall be solely responsible for the design and construction of all features.

Bids shall only be considered from companies that have an established reputation in the field of fire apparatus construction and have been in business for a minimum of 50 years.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Each bidder shall furnish satisfactory evidence of his ability to construct the apparatus specified, and shall state the location of the factory where the apparatus is to be built. The bidder shall also show that they are in a position to render prompt service and furnish replacement parts for said apparatus.

CONTRACTOR'S SPECIFICATIONS

Each bid shall be accompanied by a set of "Contractor's Specifications" consisting of a detailed description of the apparatus and equipment proposed and to which the apparatus furnished under contract must conform.

These specifications shall indicate size, type, model, and make of all component parts and equipment.

TIMELY PROPOSALS

It is the bidder's responsibility to see that their proposals arrive on time. Late proposals, facsimiles, e-mails, telegram, or telephone bids shall not be considered.

DRAWINGS

All bid drawings shall be stamped PROPOSAL.

- A total of six (6) packets of 11" x 17" drawings, each packet complete with a single view drawing for each side of the apparatus shall be supplied
- All drawings shall be drawn and printed to an appropriate scale to maximize the size of the apparatus on each 11" x 17" sheet of paper.
- Compartment door opening dimensions shall be shown in each compartment.
- Drawings shall be five (5) views. (left, right, front, rear, top) with the exception of chassis that are not always available as AutoCAD drawings
- Rear plumbing, such as 2-1/2" discharges, rear steamers, and direct tank fills, shall be shown
- Ladders shall be labeled with a letter designation referring to the table for an explanation of the ladder type
- OAL (overall length) in feet & inches -

Estimated length shall be rounded up to the nearest inch

- OAH (overall height) in feet & inches

Estimated height shall be rounded up to the nearest inch

- Body dimensions shown - pump house width & front of the body to centerline of the rear axle



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

- Wheelbase in inches
- Estimated in-service weight
- Turning clearance radius
- Front and rear overhang in inches
- No pump panel or instrument panel controls, discharges or inlets. To be blank and labeled "Pump Panel"
- Water tank outline
- Foam tank(s) fill towers
- Exterior mounted hard suction hose
- Warning lights
- D.O.T. lights
- Generator outline
- No front bumper layout
- Rollup doors will be shown in open position. Lap doors will be shown in the closed position
- Compartment depth break over measurement. The measurement where the compartment switches from full depth to shallow depth
- Angle of approach and departure
- Top view of chassis

Text Block Items

- Chassis model
- Water tank capacity
- Foam tank capacity
- Hose bed capacity in cubic feet
- Total compartment cubic feet
- Drawing box is to read "BID" and utilize the bid number



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

- Drawings shall be printed on white paper with black ink; blue line drawings shall not be acceptable.

PURCHASER'S OBLIGATIONS

The purchaser reserves the right to accept or reject any or all bids on such basis as the purchaser deems to be in its best interest. All bidders shall be advised that the purchaser is not bound in any manner to automatically accept the lowest bid. The purchaser shall only be obligated to purchase the lowest bid that meets these detailed specifications as closely as possible.

SAFETY REQUIREMENTS

It is required that the bidder shall meet all State and Federal safety standards and laws that are in effect on the date of the bid for the item(s) that are being specified and the particular use for which they are meant.

ACQUAINTANCE WITH SPECIFICATIONS

It is the responsibility of the bidder to review all of the bidding requirements. Failure of a bidder to be acquainted with this information shall not relieve them from any obligations of the bid requirements.

QUALITY AND WORKMANSHIP

The design of the apparatus shall embody the latest approved automotive engineering practices. Experimental designs and methods shall not be acceptable.

The workmanship shall be of the highest quality in its respective field. Special consideration shall be given to the following points: accessibility of the various units that require periodic maintenance, ease of operation (including both pumping and driving), and symmetrical proportions.

GENERAL CONSTRUCTION

The complete apparatus, assemblies, subassemblies, component parts, and so on, shall be designed and constructed with due consideration to the nature and distribution of the load to be sustained and to the general character of the service to which the apparatus is to be subjected when placed in service.

All parts of the apparatus shall be strong enough to withstand the general service under full load. The apparatus shall be so designed that the various parts are readily accessible for lubrication, inspection, adjustment and repair.

The apparatus shall be designed and constructed, and the equipment so mounted, with due consideration to distribution of the load between the front and rear axles, and side to side loading that all specified equipment, including a full complement of specified ground ladders, full water tank, loose equipment, and firefighters; shall be carried without overloading or damaging the apparatus as per requirements defined in NFPA 1901.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The main apparatus body structure shall have an approximate width of 100" in order to maximize the enclosed compartment space of the apparatus. The 100" wide measurement represents the main body structure measured from the bottom, outermost rear corners of the apparatus body structure. Components affixed or fastened to the apparatus will increase the body width proportionately.

LIABILITY

The bidder, if their bid is accepted, shall defend any and all suits and assume all liability for the use of any patented process, device or article forming a part of the apparatus or any appliance furnished under the contract.

WARRANTY

A copy of the warranties for the chassis, pump, body, paint, and water tank shall be furnished with each bidder's proposal.

BID FORMS / SPECIFICATIONS

All bid forms shall be submitted on the attached bid form. The bid form and/or these specifications shall be filled out by checking either the "YES" or "NO" column for each and every section/paragraph. Failure to use this form and/or these specifications shall be cause for immediate rejection of any bid.

EXCEPTION TO SPECIFICATIONS

The following chassis, pump, and body specifications shall be strictly adhered to. Exceptions shall be allowed if they are equal to or superior to that specified (as judged by the customer), and provided they are listed and fully explained on a separate page entitled "EXCEPTIONS TO SPECIFICATIONS". Exception lists shall refer to the specification page number. Each check in the "NO" column shall be listed and fully explained. Where no check is made in a particular paragraph with either "YES" or "NO", it shall be assumed the bidder is taking exception to that paragraph. If a paragraph contains an empty column, where the bidder neglected to check the proper "YES" or "NO" column, it is assumed the bidder is not conforming to the requirements of this paragraph. If no explanation is given in the "EXCEPTIONS TO SPECIFICATIONS" document, the bid is subject to immediate rejection.

PROPOSALS TAKING TOTAL EXCEPTION TO THESE SPECIFICATIONS WILL BE IMMEDIATELY REJECTED.

The buyer is aware that all bidders shall have to take some exceptions therefore; BIDDERS THAT TAKE NO EXCEPTIONS shall BE REQUIRED TO MEET EVERY PARAGRAPH TO THE FULLEST EXTENT SHOULD THEIR BID BE ACCEPTED. It is the intent of the purchaser to receive bids that do not require telephone calls or other communications to ascertain what a bidder is intending to supply.

Upon delivery, the apparatus shall be inspected against THESE specifications and not those supplied by the bidder with their proposal. Deviations shall not be acceptable unless they were



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

noted as exceptions at the time of bid and the apparatus shall be rejected until said deviations are corrected to the satisfaction of the buyer.

Decisions regarding equal to or better than, shall be the sole responsibility of the recipient of the bids rather than those companies submitting bids. All deviations, regardless of significance must be explained in the "EXCEPTIONS TO SPECIFICATIONS" section of the bid.

When exceptions are not taken but inconsistencies are noted in the submitted detailed specifications, the bid may be subject to rejection.

ROADABILITY

The apparatus, when fully equipped and loaded, shall be capable of the following performance while on dry paved roads that are in good condition:

- From a standing start, the apparatus shall be able to attain a speed of 35 mph (55 kmph) within 25 seconds on a level road.
- The apparatus shall be able to attain a minimum top speed of 50 mph (80 kmph) on a level road.
- The apparatus shall be able to maintain a speed of at least 20 mph (30 kmph) on any grade up to and including 6 percent.

The maximum top speed of the apparatus shall not exceed the tire manufacturer's maximum speed rating for the tires installed on the apparatus.

FAILURE TO MEET TESTS

In the event the apparatus fails to meet the test requirements of these specifications on the first trials, second trials may be made at the option of the bidder within 30 days of the date of the first trials.

Such trials shall be final and conclusive and failure to comply with these requirements shall be cause for rejection. Failure to comply with changes as required to conform to any clause of the specifications within 30 days after notice is given to the bidder of such changes, shall be cause for rejection of the apparatus.

Permission to keep or store the apparatus in any building owned or occupied by the Department during the specified period, with the permission of the bidder, shall not constitute acceptance. No Exceptions

PROPOSAL SEQUENCE

Bid specifications shall be submitted in the same sequence as these specifications for ease of checking compliance. There shall be no exceptions allowed to this requirement. The apparatus committee intends to be thorough during the evaluation of bids process. In order to maximize efficiency and minimize the time it takes to thoroughly evaluate all received bids this requirement must be strictly adhered to.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

AWARD OF CONTRACT

All bids submitted shall be good for a minimum of 30 days during which time bid securities submitted with the proposals shall be held by the purchaser. Criteria for the award shall include, but not be limited to, the following:

- Apparatus Performance And Safety Levels / Considerations
- Completeness of proposal
- Accuracy of accompanying data
- Past performance of bidder
- Compliance with the detailed specifications
- Compliance with purchasers request(s) for personnel qualifications or certifications
- Exceptions and clarifications
- Financial stability of bidder
- Local representation of the manufacturer
- Serviceability of the proposed apparatus
- Service capabilities of the bidder's local representative
- Compliance with NFPA 1901
- Any other factor the purchaser deems relevant

After the evaluation and award process is complete, all bidders shall be notified of the results and securities shall be returned.

OVERALL HEIGHT

The actual overall height of the vehicle shall be approximately 139" from the ground. This measurement shall be taken with the tires properly inflated with the apparatus in the unloaded condition. The actual measurement shall be taken at the highest point of the apparatus.

OVERALL LENGTH

The actual overall length of the vehicle shall be approximately 432".

WHEELBASE

The actual wheelbase of the vehicle shall be approximately 238".

ANGLE OF APPROACH



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The actual angle of approach of the vehicle shall be approximately 10 degrees.

ANGLE OF A DEPARTURE

The actual angle of departure of the vehicle shall be approximately 11 degrees.

VEHICLE TOP SPEED

The apparatus Gross Vehicle Weight Rating (GVWR) is over 26,000 lbs. The vehicle's top speed shall be 68 mph.

MISCELLANEOUS EQUIPMENT ALLOWANCE

The Gross Axle Weight Rating (GAWR) and the Gross Combined Weight Rating (GCWR) or Gross Vehicle Weight Rating (GVWR) of the chassis shall be adequate to carry the weight of the unequipped apparatus with the water tank and other tanks full, specified hose load, unequipped personnel weight, ground ladders, and miscellaneous equipment allowance of 2,000 pounds.

MISCELLANEOUS EQUIPMENT

Miscellaneous equipment, as defined by NFPA 1901, sections 5.8.2 and 5.8.3, shall be the responsibility of the customer. The apparatus shall be designed and manufactured in such a manner as to provide ample enclosed space for which to store such equipment.

PRINTED OWNER'S MANUALS

There be two (2) hard copies, printed versions, of the owner's manual provided with the apparatus as well as (1) USB drive.

INSPECTION CERTIFICATE - NFPA 1901 COMPLIANCE

A third party inspection certificate for the apparatus shall be furnished upon delivery. The purpose of this NFPA 1901 compliance inspection shall be to serve as proof to the customer that all applicable standards have been met or exceeded by the responsible manufacturer.

The following objectives shall be achieved as a result (this listing shall not be construed as being all inclusive):

- Ensure that understanding of all parties respective responsibilities have been addressed by the actual referencing of NFPA 1901 and the amendments in these specifications and the purchase contract and documentation.
- Ensure that only structural materials complying with appropriate standards and codes are used for construction.
- Ensure that applicable standards of design and manufacturing have been met or exceeded.
- Ensure that safety factors have been met or exceeded where required.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

- Ensure that applicable standards for testing and inspection have been met or exceeded by personnel with the appropriate qualifications, experience, and certifications.
- Ensure that where applicable components, equipment, and loose equipment carry the appropriate characteristics, classifications, and/or certifications.
- Ensure that in general and as a whole, all applicable requirements set forth in NFPA 1901, and those codes, standards, and specifications referenced by said parties are met, exceeded, and/or addressed.

INDEPENDENT THIRD PARTY PUMP CERTIFICATION

The fire pump shall be tested and certified by Underwriter's Laboratories, a nationally recognized independent third party testing company. Tests shall be conducted so that the pump performs as listed below:

- 100% of rated capacity at 150 pounds net pressure
- 70% of rated capacity at 200 pounds net pressure
- 50% of rated capacity at 250 pounds net pressure
- 100% of rated capacity at 165 pounds net pressure

The entire pump, both suction and discharge passages, shall be hydrostatically tested to a pressure of 600 PSI. The pump shall be fully tested at the pump manufacturer's factory to the performance spots as outlined by NFPA 1901. The pump shall be free from objectionable pulsation and vibration.

PUMP CERTIFICATION

The pump shall be certified in U.S. gallons per minute (GPM).

FOAM PROPORTIONING SYSTEM TESTING

The foam proportioning system shall be tested and certified after final installation as per NFPA 1901.

12 VOLT SYSTEMS TEST

After completion of the unit, the 12 volt electrical system shall undergo a battery of tests as listed in NFPA 1901. These tests shall include, but not be limited to:

- Reserve capacity test
- Alternator performance test at idle
- Alternator performance test at full load
- Low voltage alarm test



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Certification of the results shall be supplied with the apparatus at the time of delivery.

TILT TABLE TESTING

The apparatus shall be tested to verify the stability to 26.5 degrees in both directions. The apparatus shall be tested while loaded with fuel, fire fighting agents, hose, ladders, weight of 250 lbs. per seat, and also weight that is equivalent to the miscellaneous equipment that shall be carried. The weight added to the apparatus for testing purposes shall be distributed approximately to the in-service use, yet not to exceed the manufacturer's compartment ratings.

VEHICLE STABILITY

The apparatus shall comply with the requirements of NFPA 1901 as it applies to vehicle stability. The particular apparatus as described in the specification provided within the bid package shall be classified into one of the following categories:

- The apparatus shall go through actual tilt table testing. This shall be determined by the apparatus manufacturer.
- The apparatus shall be equipped with a rollover stability control system as defined in section 4.13.1.2 of NFPA 1901.
- The apparatus shall be deemed a similar apparatus and meeting the intent of section 4.13.1.1.2 of NFPA 1901.

TEN (10) YEAR WARRANTY BODY STRUCTURAL INTEGRITY

The body shall be free of structural or design failure or workmanship for a period of ten (10) years or 100,000 miles starting thirty (30) days after the original invoice date.

THREE (3) YEAR PAINT LIMITED WARRANTY

The apparatus body and pump house shall be free of blistering, peeling and any other adhesion defect caused by defective manufacturing methods or paint material selection for exterior surfaces for a prorated period of three (3) years starting thirty (30) days after the original invoice date.

Paint on the undercarriage, body interior (Line-X® coating included) or aerial structure related paint, if applicable, is covered only under the Standard One (1) Year Limited Warranty.

TEN (10) YEAR CORROSION LIMITED WARRANTY

The body exterior paint shall be warranted against corrosion perforation for a prorated period of ten (10) years starting thirty (30) days after the original invoice date.

TEN (10) YEAR STAINLESS STEEL PLUMBING LIMITED WARRANTY

The stainless steel plumbing and piping shall be free from corrosion perforation for a period of ten (10) years starting thirty (30) days after the original invoice date.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

PUMP WARRANTY

The fire pump shall be warranted by Waterous for a period of five (5) years from the date of delivery to the fire department or five and one-half (5-1/2) years from the shipment date by Waterous, whichever period shall be first to expire.

WATER TANK WARRANTY

The tank shall be complete with a lifetime warranty. The tank manufacturer shall mark the tank and furnish notice that indicates proof of warranty.

TWENTY (20) YEAR GALVANIZED SUBFRAME WARRANTY

The galvanized subframe shall be free of structural or design failure or workmanship for a period of twenty (20) years starting thirty (30) days after the original invoice date.

ONE (1) YEAR BASIC LIMITED PARTS & LABOR WARRANTY - OEM FABRICATED PARTS

OEM fabricated parts shall be free of defects in material and workmanship for a period of one (1) year starting thirty (30) days after the original invoice date.

SPARTAN GLADIATOR CHASSIS

The chassis shall be a Spartan Gladiator.

AIR INLET

The air inlet shall be supplied and installed by the chassis manufacturer.

MUD FLAPS

In addition to the chassis supplied front mud flaps, there shall be two (2) mud flaps provided rearward of the rear axles on the apparatus. The mud flaps shall be a minimum of 3/8" thick to prevent "sailing."

DRIVELINE WORK

The driveline work connecting the chassis and pump application shall be completed by the OEM manufacturer.

CHASSIS SUPPLIED EJECT

The charger eject shall be supplied and installed by the chassis manufacturer.

CHASSIS SUPPLIED SWITCH PANEL

The switch panel shall be supplied and installed by the chassis manufacturer.

HAZARD AND DOOR OPEN WARNING CIRCUIT



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be a hazard and "open door" warning circuits tied to the Vista Display in the chassis to alert the driver of an unsafe condition for moving the apparatus. The Vista Display shall have a specific screen to show the displayed alert. The screen shall show the apparatus in full left, right and rear views. The door, component or device that is not properly closed or stowed will be shown on the screen on the appropriate view. The displayed alerts shall be shown automatically when the parking brake is not fully engaged and any of the following conditions exist:

- Any equipment compartment door that is not closed (excluding compartments with 4 ft³ (0.1 m³) or less of volume; or have an opening of 144 in² (92,000 mm²) or less; or doors that do extend sideways beyond the mirrors or up above the top of the fire apparatus).
- Any ladder or equipment rack that is not in the stowed position.
- Any device or component that is permanently attached to the apparatus that is open, extended, or deployed in a manner that is likely to cause damage to the apparatus that has been specified as being tied to the hazard warning circuit.

CHASSIS SUPPLIED FRONT BUMPER

The front bumper shall be chassis supplied and installed.

CENTER FRONT BUMPER STORAGE WELL

There shall be a storage well in the center of the extended front bumper. The storage well shall be located between the chassis frame rails. The floor shall be covered with Dri-Dek.

STORAGE WELL COVER WITH NOTCH

There shall be an aluminum tread plate cover installed on the storage well. The cover shall be notched to allow for the stored hose to be pre-connected.

CHASSIS SUPPLIED AIR HORNS

The air horns shall be supplied and installed by the chassis manufacturer.

CHASSIS SUPPLIED SIREN

The siren shall be supplied and installed by the chassis manufacturer.

FIRE PUMP

The fire pump shall be a Waterous CRUC21-2 4000 U.S. GPM Single Stage Pump

PUMP TRANSMISSION

The pump shall have a Waterous model C21 series transmission.

SINGLE STAGE FIRE PUMP



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The pump shall be a single stage centrifugal class "A" rated fire pump, designed specifically for the fire service.

The pump shall be rated at 4000 gallons per minute.

PUMP BODY

The pump body shall be cast as two (2) horizontally split pieces. The body shall be made of high tensile, close-grained gray iron with a minimum tensile strength of 40,000 PSI.

FIRE PUMP MOUNTING

The fire pump shall be mounted within a separate body module that is not directly connected to the apparatus body.

The pump shall be frame mounted; therefore minimizing the likelihood of the pump casing cracking should the apparatus be involved in a collision.

The pump module shall be mounted to the frame in four (4) locations and shall be reinforced appropriately in order to carry the expected load for the life of the apparatus.

PUMP PRIMED BLACK BY PUMP MANUFACTURER

The pump shall be primed black by the pump manufacturer.

ZINC ANODES

There shall be four (4) Waterous zinc anodes provided with the fire pump. The anodes shall aid in preventing galvanic corrosion within the water pump and be easily replaceable. The anodes shall be installed as follows:

- Two (2) on the intake side of the pump
- Two (2) in the discharge manifold of the fire pump.

IMPELLERS

The pump impellers shall be bronze, specifically designed for the fire service and accurately balanced for vibration free running. The stripping edges shall be located on opposite sides of the impellers to reduce shaft deflection.

The impeller shaft shall be stainless steel, accurately ground to size and supported at each end by oil or grease lubricated anti-friction ball bearings for rigid, precise support. The bearings used on the impeller shaft shall be automotive type bearings, easily cross-referenced and readily available at normal parts or bearing stores.

WATEROUS IMPELLER WEAR RINGS

The pump shall be equipped with replaceable bronze wear rings for increased pump life and minimum maintenance cost. The wear rings shall be designed to fit into a groove in the face of



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

the impeller hubs forming a labyrinth that, as the clearance increases with age, directs water from the discharge side in several directions eventually exiting outward, away from the eye of the impeller hub.

MECHANICAL SEALS

The pump shall be equipped with self-adjusting, maintenance free mechanical shaft seals that shall not require manual adjustment. These seals shall be designed in a manner such that they shall remain functional enough to permit continued use of the pump in the unlikely event of a seal failure.

ELECTRIC OVER AIR PUMP SHIFT

The pump shift shall be supplied and installed by the chassis manufacturer.

The pump system shift indicator lights in the chassis cab shall be supplied and installed by the chassis manufacturer.

The pump system shift indicator lights on the operator's panel shall be incorporated with the pump pressure governor.

PRIMING PUMPS

There shall be a Two Waterous, model VPO/VPOS priming pump included with the pump. The priming pump shall be an electrically driven rotary vane pump mounted firmly within the pump area. The pump shall be controlled from the pump operator's panel. An indicator light on the pump panel shall show when the primer motor is engaged. The pump shall be capable of creating suction and discharging water from a lift of 10 feet through 20 feet of suction hose of the appropriate size, in not more than 30 seconds starting with the pump dry. It shall be capable of developing a vacuum of 22 inches at an altitude of up to 1000 feet.

WATEROUS VACUUM ACTIVATED PRIMING (VAP) VALVE

There shall be a Waterous model VAP vacuum activated priming valve supplied with the pump. The valve shall open automatically when the priming system is activated. The valve shall be installed on the pump or mounted remotely.

PRESSURE GOVERNOR

There shall be a Fire Research Pump Boss 400 pressure governor and monitoring display kit installed. The kit shall include a control module, intake pressure sensor, discharge pressure sensor, and cables. The control module case shall be waterproof and have dimensions not to exceed 6 3/4" high by 4 5/8" wide by 1 1/2" deep. The control knob shall be 2" in diameter with no mechanical stops, have a serrated grip, and a red idle push button in the center. It shall not extend more than 1 3/4" from the front of the control module. Inputs for monitored information shall be from a J1939 data bus or independent sensors. Outputs for engine control shall be on the J1939 data bus or engine specific wiring. Inputs to the control module from the pump discharge and intake pressure sensors shall be electrical.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The following continuous displays shall be provided:

- Engine RPM; shown with four daylight bright LED digits more than 1/2" high
- Check engine and stop engine warning LEDs
- Oil pressure; shown on a dual color (green/red) LED bar graph display
- Engine coolant temperature; shown on a dual color (green/red) LED bar graph display
- Transmission Temperature: shown on a dual color (green/red) LED bar graph display
- Battery voltage; shown on a dual color (green/red) LED bar graph display
- Pressure and RPM operating mode LEDs
- Pressure / RPM setting; shown on a dot matrix message display
- Throttle ready LED

The dot-matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options when selected by the operator. All LED intensity shall be automatically adjusted for day and night time operation.

The program shall store the accumulated operating hours for the pump and engine to be displayed with the push of a button. The kit shall monitor inputs and support audible and visual warning alarms for the following conditions:

- High Battery Voltage
- Low Battery Voltage (Engine Off)
- Low Battery Voltage (Engine Running)
- High Transmission Temperature
- Low Engine Oil Pressure
- High Engine Coolant Temperature
- Out of Water (visual alarm only)
- No Engine Response (visual alarm only)

The program features shall be accessed via push buttons located on the front of the control module. There shall be a USB port located at the rear of the control module to upload future firmware enhancements.

The governor shall operate in two control modes, pressure and RPM. No discharge pressure or engine RPM variation shall occur when switching between modes. A throttle ready LED shall light



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

when the interlock signal is recognized. The governor shall start in pressure mode and set the engine RPM to idle. In pressure mode the governor shall automatically regulate the discharge pressure at the level set by the operator. In RPM mode the governor shall maintain the engine RPM at the level set by the operator except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in RPM mode to a maximum of 30 psi. Other safety features shall include recognition of no water conditions with an automatic programmed response and a push button to return the engine to idle.

The pressure governor and monitoring pressure display shall be programmed to interface with a specific engine.

INTAKE RELIEF VALVES

There shall be Two (2) Elkhart Brass intake relief valve installed on the suction side of the pump. The valve shall be the preset type, adjustable from 75 to 250 PSI, and shall be designed to prevent vibration from altering the setting. The relief outlet shall be directed below the pump with the discharge terminating in a 2-1/2" male NST connection. The discharge shall be away from the pump operator and labeled "Do Not Cap".

Shop Note: Both Preset to 175PSI

MASTER DRAIN VALVE

A Trident manifold drain valve assembly shall be supplied. This drain shall provide the capability to drain the entire pump by turning a single control. The valve assembly shall consist of a stainless steel plate and shaft in a bronze body with multiple ports. The drain valve control shall be mounted on the left side pump panel and labeled "Master Drain".

WATEROUS OVERHEAT PROTECTION MANAGER WITH INDICATOR LIGHTS

There shall be a Waterous Overheat Protection Manager (OPM), installed on the pump. The relief valve shall automatically relieve water from the pump when the temperature of the pump water exceeds 140°F. In addition, a warning light on the pump panel shall be triggered by a thermal switch when the water in the pump reaches 180°F. The warning light acts as an additional protection device if the temperature inside the pump keeps rising although the valve is open. The valve shall automatically reset after activation.

WATEROUS PUMP LUBRICATION SYSTEM

An internal lubrication system shall deliver lubricant directly to the drive chain. This unique design shall eliminate the need for an external lubrication pump and auxiliary cooling. Oil shall be supplied with the lubrication system.

PUMP AND ENGINE COOLING SYSTEM

There shall be a pump and engine cooling system provided on the apparatus. The cooling system shall keep the engine cool when running for long periods of time and the pump cool during long



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

periods of pumping when water is not being discharged. The cooling system shall also be setup in a way that the cooling system lines can be easily drained through the master pump drain.

The cooling system lines shall consist of high-pressure, high-temperature 3/8" (inside diameter) abraded rubber hose. The engine cooling lines shall be installed with one (1) line going from the discharge side of the water pump through a Class 1, model 38BV, quarter turn ball valve and continuing on to the chassis heat exchanger. The return line from the heat exchanger shall then run into the suction side of the pump. The pump cooling lines shall be installed with one (1) line going from the discharge side of the water pump through a Class 1, model 38BV, quarter-turn ball valve up to the water tank. At the water tank, the pump cooling line shall be plumbed into a 3/8" check valve on the "Tank Fill" valve. The check valve shall prevent tank water from back flowing into the pump when the cooling system is not in use. A return line from the water tank shall be plumbed into the water pump.

The engine cooling system valve shall be controlled on the operators panel, and shall be clearly labeled, "Engine Cooler".

The pump cooling system valve shall be controlled on operators panel, and shall be clearly labeled, "Pump Cooler".

Class "B" foam shall be utilized.

A single foam flush system shall be installed to provide a clean water flush of the foam concentrate pump preventing foam concentrates from mixing and possible jelling. Clean water from the booster tank shall be plumbed with a 2" line.

There shall be one (1) Kochek model ALF25 Camlock Male 2 1/2" X 2 1/2" NPT.

There shall be two (2) Kochek 2 1/2" Camlock Caps with Chain supplied on the apparatus.

There shall be one (1) Kochek model K36R2525 2 1/2" Camlock Male X 2 1/2" NH Rigid Male

HARD SUCTION HOSE, KOCHEK

There shall be Hard Suction Two (2), Kochek, 3 X 10" Hard hose with 2 1/2" Female Couplings

FOAM PICK UP TUBE

Foam Picku-p Tube (stin-ger) A foam sting-er shall be provi-ded, const-ructe-d of 3" PVC pipe. The foam sting-er shall be an inver-ted "L" shape with the long end being 48" with a 45 deg. cut on one end. The short end of the "L" shall be 12" long attac-hed to the long end with a 90 deg. elbow-. The short end shall termi-nate with PVC pipe threa-d adapt-er, and a 2.5" Male cam lock fitti-ng.

FOAM CONSENTRATE/DRY FITTING

The shall be a 3" plumbing running from the pump panel to the back of deck gun to allow Dry Chemical from and off board source to be used with the Ambassador deck gun. There shall be a 2 1/2" fitting behind the deck gun for a hose to be hooked to the monitor to supply Dry Chemical.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

TFT DISCHARGE ADAPTERS

TFT adapters (2) AJ1SX-NX 6 FNH Swivel to 6" Storz with (2) A01SX Storz Cap

TFT JUMBO INTAKE VALVES WITH CAPS

There shall be (6) Six TFT 6" FNH Swivel to 6" Storz Jumbo intake Ball valves AX1SX-NX and (6) A01SX Caps

4" FOAM TANK SUCTION

There shall be a 4" FOAM TANK plumbed with a Class 1 flexible hose from the tank to the suction side of the pump.

NATIONAL FOAM 4" VALVE

There shall be 4" National Foam 4" valve supplied with the National Foam Kit.

The air actuator shall be controlled by a Williams model WM783-A control lever. The controller shall utilize a non-compensating four-way control valve with three functional positions. The valve shall be equipped with a spring loaded lockout safety device, which locks the control lever in each of the three positions to prevent unintentional movement.

There shall be a check valve between the pump suction and the booster tank valve. The check valve shall eliminate back flow into the water tank when the pump is connected to a pressurized source.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a black color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

2 1/2" FOAM TANK FILL

There shall be a 2 1/2" foam tank fill plumbed from the pump to the tank. Installation shall be completed with 2 1/2" Class 1 rubber hose and stainless steel hose couplings.

An Akron Brass model 8625 2-1/2" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall be manufactured and assembled in the United States. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The electric actuator shall be controlled by an Akron Brass model 9323 Navigator™ Pro electric valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Two (2) additional buttons shall be available to be used for preset selection, preset activation and menu navigation. The controller shall have up to three (3) preset locations that can be user set and easily recalled upon each use. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall provide position indication through a full color backlit LCD display. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. The unit shall carry a five (5) year warranty.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a black color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

(2) TWO 6" LEFT SIDE STEAMER INLET

There shall (2) Two 6" steamer inlet located on the left side of the pump module. The suction fittings shall include a removable die-cast screen to provide cathodic protection for the pump thus reducing corrosion.

A short steamer barrel shall be installed to accommodate an intake valve without exceeding the legal overall body width.

The intake shall terminate MNST thread.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a chrome color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

TWO (2)6" RIGHT SIDE STEAMER INLET

There shall be (2) Two 6" steamer inlet located on the right side of the pump module. The suction fittings shall include a removable die-cast screen to provide cathodic protection for the pump thus reducing corrosion.

A short steamer barrel shall be installed to accommodate an intake valve without exceeding the legal overall body width.

The intake shall terminate MNST thread.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a chrome color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

3" LEFT SIDE INLET

There shall be a 3" gated inlet, with 3" plumbing, provided on the left side of the pump module. The inlet shall be located towards the forward side of the pump module and shall be fully recessed behind the panel in order to keep the valve protected from the elements.

An Akron Brass model 8630 3" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall be manufactured and assembled in the United States. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9323 Navigator™ Pro electric valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Two (2) additional buttons shall be available to be used for preset selection, preset activation and menu navigation. The controller shall have up to three (3) preset locations that can be user set and easily recalled upon each use. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall provide position indication through a full color backlit LCD display. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. The unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The intake shall terminate FNST thread.

There shall be one (1) Trident model 01.022.0, 3" NST plug with chain provided. The plug shall have a chrome finish.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a black color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

3" LEFT SIDE DISCHARGE

There shall be a 3" discharge, with 3" plumbing, located on the left side of the pump module.

The discharge shall be foam capable.

An Akron Brass model 8630 3" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall be manufactured and assembled in the United States. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The discharge shall terminate MNST thread.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a red color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

6" RIGHT SIDE DISCHARGE

There shall be a 6" large diameter discharge, with 6" plumbing, located on the right side of the pump module.

The discharge shall be foam capable.

An Akron Brass model 7960 6" butterfly valve shall be provided. The valve shall be constructed with aluminum body and Pyrolite® valve adapters. The male adapter shall have a ¾" NPT bleeder port. It will have a two piece stainless steel valve stem and self-centering valve disc with no pins, screws or bolts securing the disc to the valve stem. The valve shall be designed for 250 PSI operating pressure and shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall meet NFPA 1901 standards for opening and closing speed.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products ¾" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The discharge shall terminate MNST thread.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a blue color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

3" RIGHT SIDE DISCHARGE

There shall be a 3" discharge, with 3" plumbing, located on the right side of the pump module.

The discharge shall be foam capable.

An Akron Brass model 8630 3" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall be manufactured and assembled in the United States. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The discharge shall terminate MNST thread.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a orange color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

6" LEFT SIDE DISCHARGE

There shall be a 6" large diameter discharge, with 6" plumbing, located on the Left side of the pump module.

The discharge shall be foam capable.

An Akron Brass model 7960 6" butterfly valve shall be provided. The valve shall be constructed with aluminum body and Pyrolite® valve adapters. The male adapter shall have a ¾" NPT bleeder port. It will have a two piece stainless steel valve stem and self-centering valve disc with no pins, screws or bolts securing the disc to the valve stem. The valve shall be designed for 250 PSI operating pressure and shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall meet NFPA 1901 standards for opening and closing speed.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The discharge shall terminate MNST thread.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a light green color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

1-1/2" CROSSLAY PRE-CONNECT

There shall be a 1-1/2" crosslay pre-connect with 2" plumbing.

The discharge shall be foam capable.

An Akron Brass model 8620 2" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed directly on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The discharge shall terminate MNST thread.

The discharge shall be designated as a pre-connect and no cap and chain shall be supplied.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a yellow color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

1-1/2" CROSSLAY PRE-CONNECT

There shall be a 1-1/2" crosslay pre-connect with 2" plumbing.

The discharge shall be foam capable.

An Akron Brass model 8620 2" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed directly on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The discharge shall terminate MNST thread.

The discharge shall be designated as a pre-connect and no cap and chain shall be supplied.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a white color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

2-1/2" FRONT BUMPER DISCHARGE

There shall be a 2-1/2" discharge located above the gravel shield on the right side of the front bumper. The discharge shall be plumbed with 2-1/2" plumbing and high pressure flex hose with stainless steel couplings.

The discharge shall have Class1 model 34AD automatic drains installed in the low routed areas below the 1/4 turn manual drain. The automatic drains shall open whenever pressure in the line drops below 6 psi.

The discharge shall be foam capable.

An Akron Brass model 8630 3" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall be manufactured and assembled in the United States. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The discharge shall terminate MNST thread.

The discharge shall be designated as a pre-connect and no cap and chain shall be supplied.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a black color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

2" LEFT SIDE DISCHARGE

There shall be a 2" discharge, with 2" plumbing, located on the left side of the pump module. This discharge shall be foam concentrate discharge.

The discharge shall be foam capable.

An Akron Brass model 8620 2" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed directly on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9323 Navigator™ Pro electric valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Two (2) additional buttons shall be available to be used for preset selection, preset activation and menu navigation. The controller shall have up to three (3) preset locations that can be user set and easily recalled upon each use. The unit shall be capable of being used in conjunction with at least



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

two (2) additional displays to control one (1) valve. The unit shall provide position indication through a full color backlit LCD display. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. The unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The discharge shall terminate MNST thread.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a blue color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

6" REAR DISCHARGE

There shall be a 6" large diameter discharge, with 6" plumbing, located on the rear of the apparatus.

The discharge shall be foam capable.

An Akron Brass model 7960 6" butterfly valve shall be provided. The valve shall be constructed with aluminum body and Pyrolite® valve adapters. The male adapter shall have a 3/4" NPT bleeder port. It will have a two piece stainless steel valve stem and self-centering valve disc with no pins, screws or bolts securing the disc to the valve stem. The valve shall be designed for 250 PSI operating pressure and shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall meet NFPA 1901 standards for opening and closing speed.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The discharge shall terminate MNST thread.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a burnt orange color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

3" REAR DISCHARGE

There shall be a 3" discharge located on the rear of the apparatus below the hosebed. There termination shall be 2.5" NHM Threads.

The discharge shall be foam capable.

An Akron Brass model 8630 3" Swing-Out™ valve shall be provided. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall be manufactured and assembled in the United States. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall have a 16:1 gear ratio, which actuates from fully open to fully closed in five (5) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The discharge shall terminate MNST thread.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a brown color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

6" REAR DISCHARGE

There shall be a 6" large diameter discharge, with 6" plumbing, located on the rear of the apparatus.

The discharge shall be foam capable.

An Akron Brass model 7960 6" butterfly valve shall be provided. The valve shall be constructed with aluminum body and Pyrolite® valve adapters. The male adapter shall have a 3/4" NPT bleeder port. It will have a two piece stainless steel valve stem and self-centering valve disc with no pins, screws or bolts securing the disc to the valve stem. The valve shall be designed for 250 PSI operating pressure and shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall meet NFPA 1901 standards for opening and closing speed.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

The discharge shall terminate MNST thread.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a brown color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

8" DELUGE RISER DISCHARGE

There shall be a 8" discharge for the deluge located above the pump module. The discharge shall be centered in the pump module.

The discharge shall be foam capable.

KEYSTONE 8" ELECTRIC VAVLE

There shall 8" electric valve supplied on the 8" dulge riser.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a Trident Emergency Products 3/4" quarter-turn drain valve included. There shall be a chrome plated rectangular handle provided on the drain valve to facilitate use with a gloved hand. The drain valve shall be located just above the running board and below the pump panel to reduce clutter in the pump panel area. The drain valve shall be connected to the valve with flexible hose that is routed in such a manner as to assure complete drainage to below the apparatus. A matching color coded bezel shall be included.

DECK GUN ATTACHEMENT

The Deck Gun shall have and 8" 8 bolt flange.

WILLIAMS AMBASSADOR MONITOR

The "Ambassador" Series Large Volume Deck Gun is designed for today's Industrial fire fighting and protection needs. Hazards involving flammable liquids in storage and liquids under pressure have met their match with the New Millennium Equipment from Williams Fire & Hazard Control, Inc®. This high volume delivery system is available in either wireless or hardwired hydraulic driven remote control in 12 or 24VDC with manual hand wheel & nozzle pattern adjustment overrides.

The "Ambassador" monitor/nozzle combination is capable of large volume discharge to elevations never before attained by conventional equipment to provide fire suppression, cooling, personnel protection, toxic gas dispersion and more. Discharge flow rates from 2000-6000 USGPM (7571-22700 LPM) can be water only, Hydro-Foam or Hydro-Chem for extinguishing liquids and gases under pressure

This "Hybrid" nozzle has the unique capability to perform as an automatic pressure and fixed gallonage nozzle. During automatic operation the nozzle will respond to varying flows to maintain a nearly constant tip pressure, thus maximizing effective range for a given discharge flow. Once the nozzle reaches the fixed gallonage set point (2000-6000 GPM), it performs as a conventional fixed gallonage nozzle. This is desirable for foam proportioning operations on storage tank fires or other hazards requiring specific application rates. This nozzle is capable of Hydro-Foam™ proportioning at rates up to 6000 GPM @1% / 3% (3000 GPM @ 6%) using remote jet pump technology. The extensive "Ambassador" options list allows this nozzle to be Hydro-Chem™ capable with PKW flow rates from 25 lbs/s to 100 lbs/s. The single 8" full flow stainless steel waterway construction provides minimum friction loss, maximum efficiency, and years of trouble-free service.

Shop Note: This includes Nozzle, and Hydro-Chem Choke Tubes.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a magenta color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

4" DELUGE RISER DISCHARGE

There shall be a 4" discharge for the deluge located above Left side compartments and plumbed into the 6" rear discharge.

The discharge shall be foam capable.

An Akron Brass model 8840 4" Swing-Out™ valve shall be provided. The valve shall have an all cast brass valve body with a 4" full flow waterway ideal for flows up to 2000gpm and a maximum body length of 4". The valve shall utilize a bronze flat ball design with a single urethane seat and be structurally rated to 500psi with a 250psi operating pressure. The valve shall not require the lubrication of seats or any other internal waterway parts, and shall be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall have a 25:1 gear ratio, which actuates from fully open to fully close in eight (8) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a magenta color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

4" DELUGE RISER DISCHARGE



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be a 4" discharge for the deluge located above right side compartments and plumbed into the 6" rear discharge.

The discharge shall be foam capable.

An Akron Brass model 8840 4" Swing-Out™ valve shall be provided. The valve shall have an all cast brass valve body with a 4" full flow waterway ideal for flows up to 2000gpm and a maximum body length of 4". The valve shall utilize a bronze flat ball design with a single urethane seat and be structurally rated to 500psi with a 250psi operating pressure. The valve shall not require the lubrication of seats or any other internal waterway parts, and shall be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass electric actuator installed on the valve. The electric actuator shall have a 25:1 gear ratio, which actuates from fully open to fully close in eight (8) seconds, a clutchless motor, and utilize an electric controller with current limiting design.

The electric actuator shall be controlled by an Akron Brass model 9325 Navigator™ Pro valve controller. The electric controls shall be of true position feedback design, requiring no clutches in the motor or current limiting. The unit shall be completely sealed with momentary open, close as well as an optional one (1) touch full open feature to operate the actuator. Three (3) additional buttons shall be available to be used for preset selection, preset activation, CAFS activation and menu navigation. The unit shall be capable of being connected to both Flow Sensor and Pressure Sensor, and provide an LCD display showing pressure and/or flow as well as valve position indication. Valve position indication shall be determined from true position feedback and indicate the exact position of the valve. The unit shall be capable of being used in conjunction with at least two (2) additional displays to control one (1) valve. The unit shall be able to be programmed to GPM or LPM for flow as well as Bar, PSI or kPa for pressure. The unit shall have programmed pipe sizes and be capable of custom calibration to high and low flow ranges. The unit shall also be capable of turning on and off a solenoid used in a CAFS system. The only calibration required is to set the unit to the valve during initial set up. No other calibration shall be required. The display shall be a full color LCD display with a backlight. It shall have manual adjustment of the brightness as well as an auto-dimming option. Unit shall carry a five (5) year warranty.

There shall be a two (2) piece permanent plate installed that includes a verbiage tag and a tan color coded bezel. The verbiage tag shall be etched on aluminum and have 3M-468 adhesive applied to the back for assembly into the bezel. The bezel shall be die cast aluminum construction and color coded on all visible surfaces with an automotive grade paint. 3M VHB adhesive shall be applied to the back.

DECK GUN RISER PIPE

The riser for the deck gun shall terminate with a 8-bolt flange.

TASK FORCE TIPS MONSOON RC ELECTRIC MONITOR

There shall be one (1) Task Force Tips Monsoon RC, model Y4-E21A-L, remote controlled electric monitor installed at the end of the aerial waterway. The monitor shall operate with 12 volt



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

direct current and controlled by a monitor mounted switch panel with functions that control rotation, elevation and nozzle patterns. The monitor shall be compatible with optional wired and wireless control panels.

The electrical controls for the monitor shall be waterproof and utilize current limiting and position encoders to protect the drive train at the ends of travel. Monitor will be pre-wired to a control/connection box with 4 feet of wire such that the control/connection box is mountable to the ladder at a nearby location. Control box on monitor will contain a membrane switch panel for control of unit from top of ladder. Remote control/connection box will contain one TFT communications module which will allow the connection of a remote TFT toggle switch box (supplied separately if additional controls at the ladder tip are desired) simultaneously with allowing input from discreet signals that provide a positive 12 volt signal for actuation of each movement axis or can be easily reconfigured in the field to accept ground signals. The priority of operation will be set from the factory such that the discrete inputs always have control priority. An electrical connection for a TFT remote control nozzle shall be provided. The monitor shall be equipped with small override knobs for use in the event of power failure or electrical malfunction. The knobs control stainless steel worm gears for rotation and elevation adjustment.

The monitor shall have the following capabilities:

- Control box mounted to top center of monitor for maximum clearance;
- Override control shafts shall be short in length to provide maximum clearance;
- Small override knobs installed;
- Maximum operating pressure of 200 PSI

For resistance to corrosion the monitor shall be constructed from hard coat anodized aluminum with a silver powder coat interior and exterior finish. A threaded port for an optional pressure gauge shall be provided.

The monitor shall be designed with a unique waterway that minimizes the path of travel, reduces friction loss and turbulence, and produces a far reaching water stream. The monitor shall be configured with a 4" ANSI 150 flange inlet and 3-1/2" male NH outlet.

TETHERED MONITOR CONTROL MODEL TFT Y4E-CT-30-D

A Task Force Tips monitor control model Y4E-CT-30 shall be supplied on the apparatus. The controller shall allow the electric monitor to be controlled from a handheld pendant. The control shall be supplied with a stainless steel mounting bracket to securely store the unit.

TFT WIRELESS CONTROLLER MODEL YE-RF-900

A Task Force Tips model YE-RF-900 wireless remote controller shall be provided. The controller shall allow the electric monitor to be controlled using a wireless handheld transmitter. The transmitter will operate up to 500 feet away from the truck. The transmitter shall be supplied with a stainless steel mounting bracket. The wireless handheld controller shall come with the display.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be <<qty>> (<=<qty>>) Task Force Tips, model M-ERP2000-NN, automatic master stream electric nozzle with 3-1/2" NH thread swivel base provided. The nozzle shall be equipped with an electric pattern control. The nozzle shall maintain a constant nozzle pressure regulated to 100 PSI, while being continuously variable from straight stream to wide fog. A rubber bumper incorporate TFT "power fog" teeth for fully-filled, finger-free fog pattern shall be included. The nozzle shall be lightweight hard coat anodized aluminum for maximum resistance to corrosion and wear.

DECK GUN RISER PIPE

The riser for the deck gun shall terminate with a 8-bolt flange.

TASK FORCE TIPS MONSOON RC ELECTRIC MONITOR

There shall be one (1) Task Force Tips Monsoon RC, model Y4-E21A-L, remote controlled electric monitor installed at the end of the aerial waterway. The monitor shall operate with 12 volt direct current and controlled by a monitor mounted switch panel with functions that control rotation, elevation and nozzle patterns. The monitor shall be compatible with optional wired and wireless control panels.

The electrical controls for the monitor shall be waterproof and utilize current limiting and position encoders to protect the drive train at the ends of travel. Monitor will be pre-wired to a control/connection box with 4 feet of wire such that the control/connection box is mountable to the ladder at a nearby location. Control box on monitor will contain a membrane switch panel for control of unit from top of ladder. Remote control/connection box will contain one TFT communications module which will allow the connection of a remote TFT toggle switch box (supplied separately if additional controls at the ladder tip are desired) simultaneously with allowing input from discreet signals that provide a positive 12 volt signal for actuation of each movement axis or can be easily reconfigured in the field to accept ground signals. The priority of operation will be set from the factory such that the discrete inputs always have control priority. An electrical connection for a TFT remote control nozzle shall be provided. The monitor shall be equipped with small override knobs for use in the event of power failure or electrical malfunction. The knobs control stainless steel worm gears for rotation and elevation adjustment.

The monitor shall have the following capabilities:

- Control box mounted to top center of monitor for maximum clearance;
- Override control shafts shall be short in length to provide maximum clearance;
- Small override knobs installed;
- Maximum operating pressure of 200 PSI

For resistance to corrosion the monitor shall be constructed from hard coat anodized aluminum with a silver powder coat interior and exterior finish. A threaded port for an optional pressure gauge shall be provided.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The monitor shall be designed with a unique waterway that minimizes the path of travel, reduces friction loss and turbulence, and produces a far reaching water stream. The monitor shall be configured with a 4" ANSI 150 flange inlet and 3-1/2" male NH outlet.

TETHERED MONITOR CONTROL MODEL TFT Y4E-CT-30-D

A Task Force Tips monitor control model Y4E-CT-30 shall be supplied on the apparatus. The controller shall allow the electric monitor to be controlled from a handheld pendant. The control shall be supplied with a stainless steel mounting bracket to securely store the unit.

TFT WIRELESS CONTROLLER MODEL YE-RF-900

A Task Force Tips model YE-RF-900 wireless remote controller shall be provided. The controller shall allow the electric monitor to be controlled using a wireless handheld transmitter. The transmitter will operate up to 500 feet away from the truck. The transmitter shall be supplied with a stainless steel mounting bracket. The wireless handheld controller shall come with the display.

There shall be <<qty>> (<=<qty>>) Task Force Tips, model M-ERP2000-NN, automatic master stream electric nozzle with 3-1/2" NH thread swivel base provided. The nozzle shall be equipped with an electric pattern control. The nozzle shall maintain a constant nozzle pressure regulated to 100 PSI, while being continuously variable from straight stream to wide fog. A rubber bumper incorporate TFT "power fog" teeth for fully-filled, finger-free fog pattern shall be included. The nozzle shall be lightweight hard coat anodized aluminum for maximum resistance to corrosion and wear.

WATER TANK MOUNTING

The water tank cradle shall be an integral part of the body sub-frame. Please reference the sub-frame section for complete water tank mounting information.

FOAM TANK DRAIN

There shall be a 1-1/2" drain valve provided under the sump of the Foam tank. The valve shall include a locking lever to prevent accidental draining of the Foam tank.

6" WATER TANK SLEEVES

The United Plastic Fabricating water tank shall contain the appropriate number of 6" tank sleeves for plumbing to the rear of the apparatus.

8" WATER TANK SLEEVES

The United Plastic Fabricating water tank shall contain the appropriate number of 8" tank sleeves for plumbing to the rear of the apparatus.

6" WATER TANK OVERFLOW

The tank shall be equipped with a minimum of a 6" schedule 40 polypropylene overflow/air vent pipe. The pipe shall be installed in the fill tower and extend through the tank and dump to the rear of the rear axle.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

TANK FILL/VENT FOR UNITED PLASTIC FABRICATING TANK

There shall be an auxiliary tank vent piped to the rear of the tank to void trapped air and allow filling the tank to the maximum when filling on unlevelled surfaces.

WATER TANK

The apparatus shall be equipped with a United Plastic Fabricating 1000 U.S. gallon rectangular water tank. Certification of the tank capacity shall be recorded on the manufacturer's record of construction and shall be provided to the purchaser upon delivery of the apparatus. The UPF® water tank shall be constructed of 1/2" thick PT2E™ polypropylene sheet stock. This material shall be a non-corrosive stress relieved thermoplastic, black in color, and U.V. stabilized for maximum protection.

BOOSTER TANK

The booster tank shall be of a specific configuration and shall be so designed to be completely independent of the body and compartments. All joints and seams shall be nitrogen welded and tested for maximum strength and integrity. The top of the booster tank shall be fitted with removable lifting eyes designed with a 3 to 1 safety factor to facilitate easy removal.

TANK BAFFLES

The transverse swash partitions shall be manufactured of 3/8" PT2E™ polypropylene (natural in color) and extend from approximately 4" off the floor to just under the cover. The longitudinal swash partitions shall be constructed of 3/8" PT2E polypropylene (natural in color) and extend to the floor of the tank through the cover to allow for positive welding and maximum integrity. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions shall interlock with one another and be welded to each other as well as to the walls of the tank.

TANK SUMP

There shall be one (1) sump in the bottom of the water tank. The sump shall be constructed of 1/2" polypropylene and shall be located in the left front quarter of the tank. On all tanks that require a front suction, a 4" schedule 40 polypropylene pipe shall be installed that will incorporate a dip tube from the front of the tank to the sump location. The sump shall be used as a combination clean-out and drain. All tanks shall have an anti-swirl plate located approximately 2" above the sump to pre-vent air from being entrained in the water while pumping.

TANK FILL CONNECTION

All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank, and shall be capable of withstanding sustained fill rates of up to 1,000 GPM.

TANK LID



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The tank lid shall be constructed of 1/2" thick PT2E™ polypropylene to incorporate a multi three-piece locking design that allows for individual removal and inspection if necessary. The tank lid shall be recessed 3/8" from the top of the tank and shall be welded to both sides and longitudinal partitions for maximum integrity. Each one of the lids shall have hold downs consisting of 2" polypropylene dowels spaced a maximum of 30" apart. These dowels shall extend through the covers and shall assist in keeping the covers rigid under fast filling conditions. A minimum of two lifting dowels shall be drilled and tapped 1/2" x 13" to accommodate the lifting eyes.

The foam tank shall have a manual fill tower. The fill tower shall be constructed of 1/2" PT3™ polypropylene and shall be a minimum dimension of 16" x 16" outer perimeter. Each foam fill tower shall be constructed of a black colored material indicating which tower is to receive each type of foam utilized. The capacity of the tank shall be engraved on the top of the fill tower lid. The tower shall be located in the right front corner of the tank unless otherwise specified. The tower shall have a 1/4" thick removable polypropylene screen and a stainless steel hinged-type cover. Inside the fill tower, approximately 1.5" down from the top, there shall be an anti-foam fill tube that extends down to the bottom of the tank. A pressure vacuum vent shall be provided in the lid of the fill tower. The lid shall be locking.

Class "B" foam shall be utilized.

FOAM TANK LEVEL GAUGE

There shall be one (1) Fire Research TankVision™ model WLA270-A00 class B foam tank level gauge provided. The gauge shall be located on the pump operators control panel and shall have a label that indicates it is for the foam cell that contains class B foam. The gauge shall have 9 super bright LEDs to show the tank volume. The display shall use a 2 dimensional, 2-element lens to refract the light from the LEDs to provide full 180° visibility for the level indication. The gauge shall use a pressure transducer installed near the bottom of the foam tank to determine the correct volume in the tank. The gauge shall be self-calibrating by filling the tank at a steady flow rate. Self-diagnostics capabilities shall be standard on the gauge. The gauge shall start to flash when the tank volume is at 1/4 tank or less and use down scrolling LEDs to alert the pump operator when the tank is almost empty.

2-1/2" REAR DIRECT TANK FILL

There shall be a one (1) 2-1/2" direct tank fill located on the left-rear of the apparatus.

An Akron Brass model 8825 2-1/2" Swing-Out™ valve shall be utilized for the tank fill. The valve shall have an all brass body with flow optimizing stainless steel ball and dual polymer seats. The valve shall be capable of dual directional flow while incorporating a self-locking ball feature using an automatic friction lock design and specially designed flow optimizing stainless steel ball. The valve shall not require lubrication of seats or any other internal waterway parts, and must be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valve shall carry a ten (10) year warranty by the valve manufacturer.

The valve shall be actuated by an Akron Brass model TSC manual actuator installed directly on the valve. The handle shall allow the valve to be controlled directly at the valve.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be a 3/4" Male NPT bleeder valve on the underside of the valve body to provide relief on pressurized lines.

A flange shall be mounted to the rear face of the valve body that shall extend out and down at a 30 degree angle. The flange shall terminate in a Female NST swivel and include a strainer.

There shall be one (1) Kochek model PC2552C 2-1/2" NH plug with chain provided with the tank fill. The plug shall have a chrome finish.

INDEPENDENT ALUMINUM PUMP MODULE

The pump module shall be fabricated from 3/16" smooth aluminum sheet. The module shall be fabricated as an individual unit, independent from the body. The module shall be fabricated utilizing the break and bend technique in order to form a strong, yet flexible, structure. The pump module shall be fabricated using precision holding fixtures to ensure proper dimensions and all attachment points shall be heavily reinforced.

PUMP MODULE LIGHTS

The pump module shall be equipped with two (2), 9" On-Scene Night Axe LED compartment lights. The lights shall be rated at 100,000 hours of service. The light shall be waterproof and magnesium chloride resistant. The light shall be enclosed in tough 5/8" Lexan tube. Multi-clip attachments shall allow for easy installation.

CONTROL PANEL

The forward, top section of the pump enclosure shall consist of two surfaces. The forward surface shall be on a flat, horizontal plane running from side to side of the pump enclosure. Mounted on this surface shall be all valve controls, the primer control, and the discharge relief valve controls (pilot valve). This surface shall be referred to as the "control panel".

All valves shall be the self-locking type, activated by a lever control that is connected to the valve with a direct linkage utilizing friction locking bell cranks and universal ball swivels. The slots for the control levers shall have an etched zinc bezel to trim the opening. The bezel shall be color coded and labeled "OPEN" and "CLOSED". The slots shall be evenly spaced with any unused slot supplied with necessary hardware beneath the panel for the addition of control handles for additional options, which may be added in the future.

INSTRUMENT PANEL

The surface behind the above described area shall angle upwards, sloping away from the pump operator, on a flat plane and shall contain all instruments, gauges, test fittings, and optional controls. This surface shall be referred to as the "instrument panel". The instrument panel shall be independent and hinged and latched so that it may be opened. All instruments, gauges, and other equipment shall be installed with sufficient slack in any cabling, tubing, or plumbing to allow the panel to swivel to the fully open position.

SIDE PUMP PANELS



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Two (2) panels shall be installed; one on each side of the pump enclosure, where the side discharges, inlets, steamers, and other pump associated equipment are located. These shall be referred to as the "left pump panel" and "right pump panel" respectively. Both of these panels shall be easily removable and held in place with quick release push latches. They shall be fully removable for pump and plumbing access without the need to use hand tools. Any electrical equipment that may be installed shall be equipped with connectors extended to the front so they may be easily separated from the opening created when the below described front access panel is removed.

PANEL SURFACES

The control panel, instrument panel, and both side panels shall be fabricated from a minimum of 12 gauge stainless steel with a #4 brushed finish.

PUMP PANEL LIGHTS

The pump operator's control panel and the left and right side pump panels shall each be illuminated by On-Scene Night Axe LED lighting. The pump panel lights shall become energized upon setting the parking brake so the gauge information provided may be consulted at any time the apparatus is parked. A stainless steel shield shall be installed over the pump panel lights to further protect them from the elements and to act as a reflector for additional illumination.

MASTER PUMP GAUGES

The pump vacuum and pressure gauges shall be supplied by Thuemling. Each gauge shall be fully filled with pulse and vibration dampening Interlube to insure proper operations to minus 40 degrees and to reduce lens condensation. The gauge shall read -30-0-400 PSI and shall be a minimum of 4-1/2" in diameter.

PRESSURE AND VACUUM TEST PORT

There shall be a Class1 model 121384 pressure and vacuum test port provided on the pump panel.

DISCHARGE TRIM PLATES

Each gated discharge shall have a chrome plated die cast zinc trim plate around the discharge valve and fitting. The trim plate shall be easily removable without the need to disturb the valve.

CENTER WALKWAY

Approximately 18" of the front section of the pump module shall be a center walkway at chassis frame rail height. The walkway shall be covered with bright aluminum tread plate and shall incorporate a "toe kick" where the walkway meets the vertical sheet that forms the front of the pump enclosure. The walkway shall be the same width as the pump module.

LIGHTING



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be two (2) Grote model 60571, LED lights shall be mounted in a manner that adequately illuminates the center walkway and steps for safe operation of the apparatus. The light housing shall be stainless steel and is completely encapsulated in order to provide maximum environmental protection. The lights shall become illuminated when the parking brake is engaged.

LEFT SIDE TOOL COMPARTMENT

TOOL COMPARTMENT BELOW WALKWAY, WITH DOOR AND LIGHT

There shall be a tool compartment under the pump operator's walkway. The compartment shall have a vertically hinged swing-open door. The door shall be of the single pan design and shall be positively latched in the closed position utilizing a pushbutton latch. This compartment shall have Dri-Dek flooring and two (2) drain holes at the rear of the compartment. A light shall be provided in the compartment.

RIGHT SIDE TOOL COMPARTMENT

TOOL COMPARTMENT BELOW WALKWAY, WITH DOOR AND LIGHT

There shall be a tool compartment under the pump operator's walkway. The compartment shall have a vertically hinged swing-open door. The door shall be of the single pan design and shall be positively latched in the closed position utilizing a pushbutton latch. This compartment shall have Dri-Dek flooring and two (2) drain holes at the rear of the compartment. A light shall be provided in the compartment.

LEFT SIDE RUNNING BOARD

A modular bolt-on running board shall be installed on the side of the pump module. The running board shall be constructed of anti-slip tread plate. There shall be a bar grate insert fabricated into the step area of the running board. The outside edge of the running board shall be flush with the rub rail that is installed on the body to maintain a uniform appearance. The running board shall be installed with sufficient support to form a sturdy, non-deflecting step area for personnel.

RIGHT SIDE RUNNING BOARD

A modular bolt-on running board shall be installed on the side of the pump module. The running board shall be constructed of anti-slip tread plate. There shall be a bar grate insert fabricated into the step area of the running board. The outside edge of the running board shall be flush with the rub rail that is installed on the body to maintain a uniform appearance. The running board shall be installed with sufficient support to form a sturdy, non-deflecting step area for personnel.

CROSSLAY CONFIGURATION

There shall be two (2) 2" crosslay pre-connects located ahead of the pump panel. Class1 high-pressure flex hose with stainless steel couplings shall be used in the plumbing.

A Trident 90° swivel elbow shall be utilized to keep the hose from kinking when pulled from either side of the apparatus. The swivel for each crosslay shall be located outboard for ease of making connections while changing hose.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The pre-connect hose beds shall be sized to accommodate the following hose load:

The 1-1/2" crosslay pre-connect shall have a capacity of 200' of 1-3/4" double jacket fire hose.

The hose shall be double stack.

The 1-1/2" crosslay pre-connect shall have a capacity of 200' of 1-3/4" double jacket fire hose.

The hose shall be double stack.

There shall be a heavy duty 22 oz. hypalon vinyl coated nylon end flap/cover located on each end of the pre-connected crosslays. The top of the end covers shall be connected to the tread plate top cover through a C-Rail channel. The bottom of the cover shall be attached to the pump module utilizing hooks and bungee cord.

The color of the vinyl restraint shall be black.

CROSSLAY COVER

There shall be an aluminum non-slip tread plate cover installed on the crosslay hose bed. The cover shall not interfere with hose loading when in the open position. When in the open position, the cover shall remain open due to automatically engaging mechanisms that require no type of latch operation to engage or release. The cover shall be provided with one full length stainless steel piano style hinge that shall attach the cover to the body. Opening of the cover may be performed by one person on one side of the apparatus. The cover shall be rigid enough to support weight without deformation.

Stainless steel rollers shall be provided at each end of the crosslay hose bed to facilitate deployment of hose. Vertical rollers shall be installed on each side of the hose bed opening, and a horizontal roller shall be installed under the opening.

The floor of the crosslay shall be covered with Dura-Dek fiber reinforced material. The Dura-Dek shall have "T" beams in parallel connected with cross slats that are first mechanically bonded and then epoxied. The "T" sections shall be spaced 3/4" apart to allow for drainage and ventilation.

The interior of the crosslay hose bed shall have a maintenance free abraded finish.

There shall be one (1) divider in the crosslay area. The divider shall be fabricated of 3/16" aluminum and be mounted in a channel on each end for adjustability.

The crosslay dividers shall have maintenance free abraded finish.

FRONT PUMP ACCESS DOOR

There shall be a tread plate access panel provided on the front of the pump compartment. The panel shall be of the single pan design and shall be positively latched in the closed position utilizing a push button latch. An aluminum sill protector shall be installed on the bottom of the door opening to protect the paint from chipping and scratching.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Shop Note: As large as possible for access

There shall be a vertical handrail installed at the entrance on each side of the pump module.

AIR HORN BUTTON

One (1) air horn button shall be provided on the pump panel. The button shall be red in color and included a label reading "AIR HORN".

EMERGENCY ENGINE SHUTDOWN SWITCH

There shall be one emergency engine shutdown switch provided at the pump panel. The switch shall be wired to the chassis manufacturer provided circuitry.

FUEL TANK GAUGE ON PUMP PANEL

There shall be a 2" fuel tank gauge provided on the pump panel. The gauge shall provide fuel tank readout for the pump operator during fire ground operations.

PUMP PANEL LIGHT SWITCH

There shall be an on/off switch located on the operator pump panel to control the pump panel lights.

ACCESS LADDER - LEFT SIDE

For access to the turntable, a set of steps shall be installed on the left side of the apparatus. The step design shall utilize two (2) air cylinders to aid in the deployment of the steps into the climbing position and a positively locking mechanism to lock the step assembly into the travel position. The main structural members of the assembly shall be fabricated from 12 gauge 304 stainless steel with aluminum tread plate overlays on the step area. The degree of slip resistance shall be in compliance with the intent of NFPA 1901.

The steps shall be designed as a two (2) part assembly. The lower step assembly shall swing out and down and the upper assembly will angle when the lower assembly is in down position to an approximate slope of 81 degrees to provide ease of access from ground to first step and allow for the maximum angle of departure of the apparatus. When the access ladder is in the down position, the maximum height from the ground to the first step shall not exceed 24". All remaining steps shall have a maximum stepping height that shall not exceed 18".

The access ladder shall be connected to the door open warning circuit to warn the driver it is not in the stored position. Steps shall be illuminated for night time operation with LED lighting. The lights shall be activated by the parking brake. To aid in ascending and descending the access steps, knurled aluminum handrails shall be provided on each side of the steps.

ALUMINUM BODY CONSTRUCTION



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The apparatus body shall be fabricated from 3/16", smooth aluminum sheet. The total outside width of the apparatus body shall not exceed 100 inches (2.54 meters). The width measurement of the sidewalls shall be made from the outside wall of the two opposite sides of the body.

The complete apparatus body shall be fabricated utilizing the break and bend techniques in order to form a strong, yet flexible, uni-body structure. The body shall be constructed with holding fixtures to ensure proper dimensioning. Each apparatus body is specific in design in order to meet the unique requirements of the purchasing fire department.

The main body compartments on each side, as well as the rear center compartment if applicable, shall contain a sweep out floor design. Each compartment shall be made to the most practical dimensions in order to provide maximum storage capacity for the fire department's equipment. The door opening threshold shall be positioned lower than the compartment floor permitting easy cleaning of the compartments.

Continuous, solid welded seams shall be located at the upper front and upper rear corners of the apparatus body. The flooring of all lower, main body compartmentation shall also have solid weld seams. All door jams, on both the top and the bottom, shall be solid welded as well. Each main door jam shall consist of a double jam design, this is comparable to a double struck frame design, which provides superior strength and durability. All double door jams are to be welded together utilizing the plug weld technique. All remaining compartment walls shall be stitch welded.

The compartment floors, specifically L1 and R1, shall have a minimum of two (2) 1" x 2" rectangular tubes welded to the entire width of the compartment floor. The two (2) rear side compartments as well as the rear center compartment, if applicable, shall be welded to the rear deck support structure. This rear deck support structure is specially designed for the galvanized apparatus body substructure. A minimum of two (2) squares tubes, which are 1/4" x 3" x 3", shall run the entire width of the body from sidewall to sidewall. Each lower, rear compartment shall be adequately stitch welded to the cross tubes providing strength and durability to the entire apparatus body.

The body design shall include a "false wall" design in the lower portion of each lower, rear compartment. This "false wall" is required in order to allow for easy accessibility to the rear electrical components found in the rear taillight cluster area.

On the upper area of the apparatus body, directly above the side compartment door openings, a header is to be fabricated from smooth, aluminum sheet. This area shall be free from any body seams and shall be painted the same color as the apparatus body. The height of the header may vary depending on the following factors: apparatus design, lettering requirements, scene lights and warning light requirements as well as various other options. A "J" channel shall be incorporated into the body design in order to provide a rain gutter to further assist in preventing excessive moisture from getting into the compartments.

ULTRA STAINLESS™ STEEL FASTENERS

Ultra Stainless™ steel fasteners shall be provided for all exposed and unpainted fasteners throughout the body in locations such as overlays, pump panels, and other numerous hardware mounting locations. The special ingredient in Ultra Stainless™ is Marutex®, which adds 2%



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

molybdenum (moly) to 410 stainless. Moly is the significant component of 316 stainless that provides extra corrosion resistance. The moly is now added to 410 self drilling screws to produce Ultra Stainless™. This combination provides for unprecedented corrosion resistance combined with hardness for drilling.

ADDITIONAL HARDWARE

There shall be a bag of stainless steel nuts, bolts, and washers supplied with the apparatus for mounting of equipment.

GS-36 BODY SUB FRAME

To assure proper body alignment and clearance, the body sub frame shall be constructed in a jig and fitted directly on the chassis. The sub frame shall be constructed of 36,000 PSI galvanized steel.

The chassis frame rails shall be fitted with fiber reinforced rubber to isolate the body frame members from direct contact with chassis frame rails.

The main body sub frame shall be constructed from steel tubing. The sub frame shall run the full length of the body and shall be spaced the same width as the chassis frame rails. The main sub frame shall also be the integral support for the water tank. Vertical drop tubes shall be welded to the sub frame. From these vertical drop tubes shall extend cross members constructed of steel angle. These cross members shall extend out to support the compartments. Cross members shall be located at the front and rear of the body and in front and rear of the wheel well opening.

A drop frame, fabricated of steel tube and steel angles, shall support the compartment area behind the rear. The rear drop frame shall be constructed using vertical drop tubes, welded to the main sub frame. All drop frame structures shall be welded directly to the body sub frame to allow the body to be a completely separate structure from the chassis.

After fabrication the sub frame shall be hot dip galvanized for maximum protection against corrosion.

BODY MOUNTING

The body sub frame shall be fastened to the chassis frame with a minimum of six (6) spring loaded body mounts. Each mount shall be configured using a two-piece bracket. The two (2) brackets shall be fabricated of steel plates. The plates shall be galvanized to prevent any corrosion. Each mounting assembly shall utilize two (2) plated bolts and two (2) heavy duty springs. The assembly design shall allow the body and sub frame to act as one (1) component, separate from the chassis. As the chassis frame twists under driving conditions, the spring mounting system shall limit any stress from being transferred into the body. The spring loaded body mounts shall also prevent frame side rail or body damage caused by unevenly distributed stress and strains due to load and chassis movement.

Body mountings that do not allow relief from chassis movement shall not be acceptable.

TANK MOUNTING



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The water tank shall rest on the sub frame cross members which are spaced as required by the tank manufacturer.

The tank shall be isolated from the cross members through the use of hard rubber strips with a minimum Rockwell hardness of 60 durometer. Additionally, the tank shall be supported around the entire perimeter and captured front and rear as well as side to side to prevent the tank from shifting during vehicle operations.

Although the tank shall be designed on a free floating suspension principle, it shall be required that the tank have adequate hold down restrains to minimize movement during vehicle operations.

The tank shall be completely removable without disturbing or dismantling the apparatus structure.

EXHAUST HEAT DEFLECTOR SHIELD

There shall be a 5" heat deflector shield installed over the exhaust to aid in dissipating the heat to prevent exhaust heat from adversely affecting anything stored in the body.

LEFT SIDE BODY CONFIGURATION

COMPARTMENT L1

There shall be a full height compartment located ahead of the rear wheels on the left side of the apparatus body. This compartment shall be designated as L1 within these specifications and any ensuing paperwork or drawings after contract execution.

- Door Opening 35.00" wide x 59.50" high
- Usable Depth 25.75"

There shall be one (1) ROM rollup door installed on the compartment face. The door shall be a shutter type with 34 millimeter slats that roll onto a spool at the top of the compartment. Each slat shall be equipped with nylon end shoes to assure operation without the need of constant lubrication. The rollup door shall have a satin finish.

The ROM rollup door shall be supplied with a full width lift bar and finger pull handle integrated into the bottom rail for easy one hand operation.

The compartment shall have one (1), 45" On-Scene LED Night Axe installed. The light shall be enclosed within a tough waterproof Lexan tube enclosure. The Night Axe shall offer 74 lumens per 18" of light and an adjustable beam angle.

There shall be four (4) aluminum strut channels, two (2) per side, welded in the full depth, full height compartment.

There shall be one (1), roll out equipment tray installed in the compartment. The tray shall be equipped with an Austin Hardware drawer slide. The roller assembly shall have a rated capacity of 300 lbs. distributed load and have 100% extension capability. The roller assembly shall be bolted to vertical struts to allow for height adjustment. The tray shall be constructed of 3/16"



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

aluminum sheet with 3" lips to prevent items from being shifted during transportation. The tray shall have an abraded finish and shall be equipped with a gas spring in order to hold the tray in either a fully extended or closed position.

There shall be a roll out tray installed on the floor of compartment. The tray shall be provided with a SlideMaster™ model SM3-MP roller type assembly. The roller assembly shall have a rated capacity of 600 lb. distributed load and have 100% extension capability. A mechanical lock assembly shall be provided to lock the tray in the extended or retracted position. The tray shall be constructed of 3/16" aluminum sheet with 3" lips and shall have an abraded finish. The tray roller assembly shall have a powder coated finish for added corrosion protection.

TRAY STRIPING

There shall be reflective striping chevron pattern installed on the front face and both sides of each trays in the compartment. Each stripe shall be a minimum of 1-3/4" in width and shall be applied to the trays at a 90 degree angle. The chevron striping colors shall be red and white.

There shall be one (1) application in the compartment that shall utilize Turtle Tile Plastics interlocking squares. Each square shall be made from polyvinyl chloride that is flame and chemical resistant. For maximum slip resistance and drainage, each square shall have a grid surface design.

There shall be one (1) PAC TRAC tool mounting section installed on the back wall of the compartment. The PAC TRAC section shall be constructed of 7/8" thick, 6063-T5 extruded aluminum.

COMPARTMENT L2

There shall be a standard height compartment located above the rear wheels on the left side of the apparatus body. This compartment shall be designated as L2 within these specifications and any ensuing paperwork or drawings after contract execution.

- Door Opening 61.00" wide x 28.00" high
- Usable Depth 25.75"

There shall be one (1) ROM rollup door installed on the compartment face. The door shall be a shutter type with 34 millimeter slats that roll onto a spool at the top of the compartment. Each slat shall be equipped with nylon end shoes to assure operation without the need of constant lubrication. The rollup door shall have a satin finish.

The ROM rollup door shall be supplied with a full width lift bar and finger pull handle integrated into the bottom rail for easy one hand operation.

The compartment shall have two (2), 18" On-Scene LED Night Axes installed. Each light shall be enclosed within a tough waterproof Lexan tube enclosure. Each Night Axe shall offer 74 lumens per 18" of light and an adjustable beam angle.

There shall be four (4) aluminum strut channels, two (2) per side, welded in the full depth compartment.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be one (1) application in the compartment that shall utilize Turtle Tile Plastics interlocking squares. Each square shall be made from polyvinyl chloride that is flame and chemical resistant. For maximum slip resistance and drainage, each square shall have a grid surface design.

COMPARTMENT L3

There shall be a full height compartment located behind the rear wheels on the left side of the apparatus body. This compartment shall be designated as L3 within these specifications and any ensuing paperwork or drawings after contract execution.

- Door Opening 32.00" wide x 59.50" high
- Usable Depth 25.75"

There shall be one (1) ROM rollup door installed on the compartment face. The door shall be a shutter type with 34 millimeter slats that roll onto a spool at the top of the compartment. Each slat shall be equipped with nylon end shoes to assure operation without the need of constant lubrication. The rollup door shall have a satin finish.

The ROM rollup door shall be supplied with a full width lift bar and finger pull handle integrated into the bottom rail for easy one hand operation.

The compartment shall have one (1), 45" On-Scene LED Night Axe installed. The light shall be enclosed within a tough waterproof Lexan tube enclosure. The Night Axe shall offer 74 lumens per 18" of light and an adjustable beam angle.

There shall be four (4) aluminum strut channels, two (2) per side, welded in the full depth, full height compartment.

There shall be two (2), aluminum adjustable shelves installed on the apparatus in the full depth compartment. The shelves shall be constructed of 3/16" aluminum sheet with 2" lips. The shelves shall have an abraded finish, and shall be designed in such a manner that will allow liquids to readily drain when spilled.

SHELF STRIPING

There shall be reflective striping chevron pattern installed on the front face of each shelves in the compartment. Each stripe shall be a minimum of 1-3/4" in width and shall be applied to the shelves at a 90 degree angle. The chevron striping colors shall be red and white.

There shall be three (3) applications in the compartment that shall utilize Turtle Tile Plastics interlocking squares. Each square shall be made from polyvinyl chloride that is flame and chemical resistant. For maximum slip resistance and drainage, each square shall have a grid surface design.

There shall be two (2) full height, slide out aluminum tool boards located in the split depth compartment. The tool boards shall utilize a locking roller assembly to lock them in both the opened and closed position. The tool boards shall be mounted to an adjustable unistrut to allow each board to be relocated for best fit in the compartment.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The tool boards shall have PAC TRAC tool mounting installed on each side of the pull out tool board. The PAC TRAC sections shall be constructed of 7/8" thick, 6063-T5 extruded aluminum.

There shall be one (1) permanent vertical partition installed in the full height compartment. The partition shall match the compartment interior.

LEFT SIDE BODY CONFIGURATION

COMPARTMENT R1

There shall be a full height compartment located ahead of the rear wheels on the right side of the apparatus body. This compartment shall be designated as R1 within these specifications and any ensuing paperwork or drawings after contract execution.

- Door Opening 35.00" wide x 59.50" high
- Usable Depth 25.75"

There shall be one (1) ROM rollup door installed on the compartment face. The door shall be a shutter type with 34 millimeter slats that roll onto a spool at the top of the compartment. Each slat shall be equipped with nylon end shoes to assure operation without the need of constant lubrication. The rollup door shall have a satin finish.

The ROM rollup door shall be supplied with a full width lift bar and finger pull handle integrated into the bottom rail for easy one hand operation.

The compartment shall have one (1), 45" On-Scene LED Night Axe installed. The light shall be enclosed within a tough waterproof Lexan tube enclosure. The Night Axe shall offer 74 lumens per 18" of light and an adjustable beam angle.

There shall be four (4) aluminum strut channels, two (2) per side, welded in the full depth, full height compartment.

There shall be one (1), aluminum adjustable shelf installed on the apparatus in the full depth compartment. The shelf shall be constructed of 3/16" aluminum sheet with 2" lips. The shelf shall have an abraded finish, and shall be designed in such a manner that will allow liquids to readily drain when spilled.

SHELF STRIPING

There shall be reflective striping chevron pattern installed on the front face of the shelf in the compartment. Each stripe shall be a minimum of 1-3/4" in width and shall be applied to the shelf at a 90 degree angle. The chevron striping colors shall be red and white.

There shall be a roll out tray installed on the floor of compartment. The tray shall be provided with a SlideMaster™ model SM3-MP roller type assembly. The roller assembly shall have a rated capacity of 600 lb. distributed load and have 100% extension capability. A mechanical lock assembly shall be provided to lock the tray in the extended or retracted position. The tray shall be constructed of 3/16" aluminum sheet with 3" lips and shall have an abraded finish. The tray roller assembly shall have a powder coated finish for added corrosion protection.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

TRAY STRIPING

There shall be reflective striping chevron pattern installed on the front face and both sides of the tray in the compartment. Each stripe shall be a minimum of 1-3/4" in width and shall be applied to the tray at a 90 degree angle. The chevron striping colors shall be red and white.

There shall be two (2) applications in the compartment that shall utilize Turtle Tile Plastics interlocking squares. Each square shall be made from polyvinyl chloride that is flame and chemical resistant. For maximum slip resistance and drainage, each square shall have a grid surface design.

COMPARTMENT R2

There shall be a standard height compartment located above the rear wheels on the right side of the apparatus body. This compartment shall be designated as R2 within these specifications and any ensuing paperwork or drawings after contract execution.

- Door Opening 61.00" wide x 28.00" high
- Usable Depth 25.75"

There shall be one (1) ROM rollup door installed on the compartment face. The door shall be a shutter type with 34 millimeter slats that roll onto a spool at the top of the compartment. Each slat shall be equipped with nylon end shoes to assure operation without the need of constant lubrication. The rollup door shall have a satin finish.

The ROM rollup door shall be supplied with a full width lift bar and finger pull handle integrated into the bottom rail for easy one hand operation.

The compartment shall have two (2), 18" On-Scene LED Night Axes installed. Each light shall be enclosed within a tough waterproof Lexan tube enclosure. Each Night Axe shall offer 74 lumens per 18" of light and an adjustable beam angle.

There shall be four (4) aluminum strut channels, two (2) per side, welded in the full depth, full height compartment.

There shall be one (1) application in the compartment that shall utilize Turtle Tile Plastics interlocking squares. Each square shall be made from polyvinyl chloride that is flame and chemical resistant. For maximum slip resistance and drainage, each square shall have a grid surface design.

COMPARTMENT R3

There shall be a full height compartment located behind the rear wheels on the right side of the apparatus body. This compartment shall be designated as R3 within these specifications and any ensuing paperwork or drawings after contract execution.

- Door Opening 32.00" wide x 59.50" high
- Usable Depth 25.75"



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be one (1) ROM rollup door installed on the compartment face. The door shall be a shutter type with 34 millimeter slats that roll onto a spool at the top of the compartment. Each slat shall be equipped with nylon end shoes to assure operation without the need of constant lubrication. The rollup door shall have a satin finish.

The ROM rollup door shall be supplied with a full width lift bar and finger pull handle integrated into the bottom rail for easy one hand operation.

The compartment shall have one (1), 45" On-Scene LED Night Axe installed. The light shall be enclosed within a tough waterproof Lexan tube enclosure. The Night Axe shall offer 74 lumens per 18" of light and an adjustable beam angle.

There shall be four (4) aluminum strut channels, two (2) per side, welded in the full depth, full height compartment.

There shall be a roll out tray installed on the floor of compartment. The tray shall be provided with a SlideMaster™ model SM3-MP roller type assembly. The roller assembly shall have a rated capacity of 600 lb. distributed load and have 100% extension capability. A mechanical lock assembly shall be provided to lock the tray in the extended or retracted position. The tray shall be constructed of 3/16" aluminum sheet with 3" lips and shall have an abraded finish. The tray roller assembly shall have a powder coated finish for added corrosion protection.

There shall be two (2) applications in the compartment that shall utilize Turtle Tile Plastics interlocking squares. Each square shall be made from polyvinyl chloride that is flame and chemical resistant. For maximum slip resistance and drainage, each square shall have a grid surface design.

There shall be one (1), aluminum adjustable shelf installed on the apparatus in the full depth compartment. The shelf shall be constructed of 3/16" aluminum sheet with 2" lips. The shelf shall have an abraded finish, and shall be designed in such a manner that will allow liquids to readily drain when spilled.

SHELF STRIPING

There shall be reflective striping chevron pattern installed on the front face of each shelves in the compartment. Each stripe shall be a minimum of 1-3/4" in width and shall be applied to the shelves at a 90 degree angle. The chevron striping colors shall be red and white.

REAR BODY CONFIGURATION

The rear of the body shall be a flat back.

COMPARTMENT AIR RELEASE

Each compartment shall be vented to help remove trapped air when closing a compartment door. The vent shall be a rubber gasket in the area of the outboard corners of the compartment. Wiring may also be run through these areas.

COMPARTMENT DRAIN HOLES



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Each body compartment shall be equipped with drain holes to allow standing water to exit to underneath the apparatus.

WALKWAYS AND OVERLAYS

All exterior surfaces designated by the manufacturer as stepping, standing, or walking areas shall be overlaid with 3003 H22 Bright Tread Plate to provide a slip resistant surface, even when the surface is wet. All interior surfaces designated by the manufacturer as stepping, standing, or walking areas shall be slip resistant when the surface is dry. The degree of slip resistance shall be in compliance with the intent of NFPA 1901.

Horizontal walkways shall have .080" aluminum tread plate overlays installed and vertical surfaces shall have .125" aluminum overlays. Overlays shall be installed that are totally insulated from the apparatus with nylon shoulder washers that extend into holes in the body. Stainless steel cap nuts shall be employed where bolt ends may damage equipment or cause injury. After the apparatus is painted and the overlays are reinstalled, they shall be additionally sealed at the edges with a caulking compound. The exterior top tread plate overlay shall be mounted flush with the outer edges of the apparatus body.

STEPPING SURFACES

All steps shall have a surface area of at least 35 square inches and shall be able to withstand a load of at least 500 pounds. Steps shall be provided at any area that personnel may need to climb and shall be adequately lighted.

REAR DECK

A modular bolt-on deck shall be installed on the rear of the apparatus to form a full width step area. The rear deck shall be constructed of anti-slip bright tread plate. The outside edge of the rear deck shall be flush with the rub rail that is installed on the body to maintain a uniform appearance. The depth of the rear deck shall be 13.25". The rear deck shall be installed with sufficient support to form a sturdy, non-deflecting step area for personnel.

REAR STEPS

There shall be eight (8) Cast Products bolt-on steps installed on the rear of the apparatus. Each step shall have large open slots to prevent buildup of ice or mud and to provide a handhold when necessary. Steps shall be provided in the following locations:

- Four (4) bolt-on steps on the left rear of the apparatus.
- Four (4) bolt-on steps on the right rear of the apparatus.

The steps shall be adequately lit with LED lighting. There shall be one (1) light located above each set of steps on the rear face of the body, for a total of two (2) lights. Each light shall be located in a manner that shall light all of the steps on its respective side.

FRONT BODY STEPS AND LIGHTING



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be three (3) Cast Products folding steps located on the front of the right side body compartments. The folding steps shall have two large open slots to prevent the buildup of ice or mud and to provide a handhold when necessary. The steps shall have a surface area of at least 35 square inches and shall be able to withstand a load of 500 pounds.

The steps shall be adequately lit with LED lighting. There shall be one (1) light located above the steps.

FRONT VERTICAL AREA TREAD PLATE OVERLAYS

There shall be a tread plate overlay on the vertical areas of each side of the apparatus body. The overlay will be located in front of the L1 and R1 compartments.

REAR WHEEL WELLS

The fenders shall be integral with the body sides and compartments with a seamless appearance. The fenders shall be fitted with bolt-in removable full circular inner liners in the wheel well area for ease of cleaning and maintenance. There shall be sufficient clearance provided in the wheel well to allow the use of tire chains when the apparatus fully loaded.

STAINLESS STEEL REAR FENDERETTES

Two (2) stainless steel fenderettes shall be installed at the outboard edge of the rear wheel well area, one on each side. The fenderettes shall be bolted to the apparatus body using nylon washers to space them slightly away from the body to reduce build-up of road grime. The fenderettes shall be constructed of stainless steel that has been polished to a high quality finish.

LEFT SIDE REAR WHEEL WELL POSITION - WL1

There shall be a wheel chock compartment installed in the rear wheel well area. The compartment shall be capable of storing one wheel chock.

The compartment door, hinges and frame shall all be constructed out of stainless steel material. The door shall have a rubber gasket in order to create a 100% seal to protect the interior of the compartment. The door shall have a brushed stainless steel finish.

LEFT SIDE REAR WHEEL WELL POSITION - WL3

There shall be a three (3) air bottle compartment installed in the rear wheel well area. The compartment shall be a triangle design. The compartment door, hinges and frame shall all be constructed out of stainless steel material. The door shall have a rubber gasket in order to create a 100% seal to protect the interior of the compartment. The storage compartment shall be a rotational, molded component that is assembled to the door and frame. This assembly process shall prevent the air bottle from making contact with the stainless steel frame while loading and unloading the air bottle. The door shall have a brushed stainless steel finish.

FUEL FILL



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The fuel fill pocket shall be located in the left rear wheel well area. The fuel fill shall utilize a stainless steel OEM manufactured door with a brushed finish and shall utilize a magnetic latch. The cap of the fuel fill shall be a click-type plastic cap. The hinge and frame shall all be constructed out of stainless steel material.

RIGHT SIDE REAR WHEEL WELL POSITION - WR1

There shall be a three (3) air bottle compartment installed in the rear wheel well area. The compartment shall be a triangle design. The compartment door, hinges and frame shall all be constructed out of stainless steel material. The door shall have a rubber gasket in order to create a 100% seal to protect the interior of the compartment. The storage compartment shall be a rotational, molded component that is assembled to the door and frame. This assembly process shall prevent the air bottle from making contact with the stainless steel frame while loading and unloading the air bottle. The door shall have a brushed stainless steel finish.

RIGHT SIDE REAR WHEEL WELL POSITION - WR3

There shall be a three (3) air bottle compartment installed in the rear wheel well area. The compartment shall be a triangle design. The compartment door, hinges and frame shall all be constructed out of stainless steel material. The door shall have a rubber gasket in order to create a 100% seal to protect the interior of the compartment. The storage compartment shall be a rotational, molded component that is assembled to the door and frame. This assembly process shall prevent the air bottle from making contact with the stainless steel frame while loading and unloading the air bottle. The door shall have a brushed stainless steel finish.

BODY RUB RAILS

Rub rails shall be installed beneath the compartment doors to protect them from damage should the body be brushed or rubbed against another object. The rub rails shall be 3/16" aluminum channel, 2-1/2" x 1". The rub rails shall be highly polished and then bright dip anodized.

The rub rails shall be installed on the body utilizing non-corrosive nylon spacers and secured with stainless steel bolts. The outside edge of the rub rails shall be even with the fenderettes and bolt-on steps to prevent snagging.

TWO REAR TOW EYES

There shall be two (2) chrome plated tow eyes installed at the rear of the apparatus, above the rear step area. The tow eyes shall be attached directly to the frame rail of the apparatus and capable of a 15,000 lb. straight pull rating. The tow eyes shall have a 2-1/2" ID hole.

HOSE BED

The hose bed shall be located above the water tank and have a minimum capacity of 30 cubic feet in accordance with the latest NFPA regulations. The inside of the hose bed shall be smooth aluminum. The hose bed shall exit at the rear of the apparatus through a single access opening. The opening shall be free of obstructions that might interfere with the deployment and loading of hose.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The floor of the hose bed compartment shall be constructed of Dura-Dek fiber reinforced plastic material. The flooring shall be fabricated of "T" beam pultrusions in parallel connected with cross slats that are first mechanically bonded and then epoxied, forming a large sheet. The top portion of each "T" cross section shall measure 1-1/4" wide and 3/16" thick with beaded ends. The vertical portion shall be 3/8" thick, beading out at the bottom to a thickness of 1/2" and tall enough to result in an overall height of 1". The "T" sections shall be spaced 3/4" apart to allow for drainage and ventilation.

Each "T" beam shall be constructed utilizing a core of 250,000 continuous glass fiber strands that are high in resistance to tension, compression and bending. An outer sheath consisting of a continuous strand mat to prevent lineal splitting and slipping shall surround the core. The sheath shall also serve to draw the protective resin to the bar surface. Both reinforcements shall be pulled through an isophthalic polyester resin, treated with antimony trioxide for fire resistance, to form a solid length.

The flooring shall then be protected with a polyurethane coating to screen out ultraviolet rays. This bright white coating shall be baked on and shall provide a pleasing contrast when installed in the apparatus.

The hose bed shall contain the following hose load:

300' of 3" double jacket hose

1000' of 5" double jacket hose

300' of 3" double jacket hose

There shall be a heavy-duty 22 oz. hypalon vinyl coated nylon restraint located on the end of the hose bed. The top of the restraint shall be connected to the tread plate hose bed cover through a C-Rail channel. The bottom of the restraint shall be attached to the body utilizing hooks and bungee cord.

The interior of the hose bed shall be coated with Line-X®, a thermoplastic polyurethane coating. The coating shall be black in color.

POWER OPERATED HOSE BED DOORS

The hose bed storage area shall be covered with two (2) hinged aluminum doors. The doors shall be hinged on the outside edges, utilizing full length stainless steel piano hinges. The doors shall lift up and out towards the outside of the body. The doors shall be fabricated with 1/8" aluminum inner panel for superior strength. The outside sheet shall be constructed of anti-slip tread plate.

The hose bed doors shall be power operated utilizing a self-contained hydraulic system. The system pressure of the hydraulic system shall be factory set to a pressure that will smoothly power the cover doors upward and downward. The system is designed to keep the doors firmly open when reloading hose as well as to hold the cover doors firmly down in the travel position. Mechanical locks are not required in order to avoid possible injury from accidental closing of cover doors.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Hydraulic cylinders, located in front of the hose bed storage area shall be utilized to open/close the cover doors. The hydraulic system shall be powered by Parker Hannifin series 108 self-contained power unit. The hydraulic system shall be designed so the doors only operate in the predetermined factory-set sequence. The system shall only allow one door at a time to move. The cylinders, when the doors are in the closed position, shall lower into a secluded compartment that is separate from the stored hose to ensure unobstructed hose deployment operations. The cylinder pins attached to the doors shall be designed to be removable with the doors in the closed position without having to climb inside the hose storage area.

A self-contained switch shall be utilized to raise/lower the cover doors. The switch shall be located at the rear of the apparatus in a convenient location allowing the operator to view the hose bed cover doors while operating the mechanism from ground level. The switch shall be the momentary type of switch that requires the operator to hold the switch until the desired movement of the cover doors is achieved.

The power unit shall be interlocked with the parking brake and shall be operable only when the park-brake is applied. The doors shall be connected to the open door warning system when in the open condition. An audible alarm shall be located towards the front of the hose bed area designed to warn occupants of the hose bed area that door movement is occurring.

Lighting shall be provided by two (2) 36 inch LED On Scene Night Axe lights. The lighting shall be enclosed within a tough waterproof Lexan tube enclosure. Night Axe lights shall offer 74 lumens per 18 inches of light and an adjustable beam angle. The lights shall activate when the door is opened.

HOSE BED DIVIDERS

There shall be two (2) hose bed dividers installed in the hose bed. The dividers shall be fabricated from 1/4" smooth aluminum plate and an aluminum extrusion. Each divider shall be coated with black Line-X® and mounted on hot-dipped galvanized slide rails at the front and rear of the hose bed. Where no obstruction such as a fill tower is present, the slide rails shall allow full movement of the dividers along the width of the hose bed. Each hose bed divider shall have an oval shaped hand hold slot to assist in moving the divider. This shall provide the capability for variable hose load configurations and capacities.

HARD SUCTION HOSE "V" TROUGHS

There shall be three (3) hard suction hose "V" troughs located above right side compartments, each with the capacity to store one hard 10' section of hard suction hose. The troughs shall be fabricated of aluminum plate. Velcro straps shall be supplied to hold the hard suction hose secure.

The suction hose storage shall be enclosed above the right side compartments.

HARD SUCTION HOSE, FIREQUIP

There shall be three (3), Firequip Maxi-Flex PVC 6" x 10' sections of hard suction hose provided.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

BARREL STRAINER

One (1), Kochek, model BS60, 6" barrel strainer shall be shipped loose on the apparatus. The strainer shall be constructed from aluminum with K-Brite finish and include a tie off loop on the end plate. The strainer shall be provided with a 6" NST female rocker lug coupling.

HARD SUCTION HOSE "V" TROUGHS

There shall be three (3) hard suction hose "V" troughs located above left side compartments, each with the capacity to store one hard 10' section of hard suction hose. The troughs shall be fabricated of aluminum plate. Velcro straps shall be supplied to hold the hard suction hose secure.

The suction hose storage shall be located above the left side compartments.

HARD SUCTION HOSE, FIREQUIP

There shall be three (3), Firequip Maxi-Flex PVC 6" x 10' sections of hard suction hose provided.

WHEEL CHOCKS

There shall be one (1) pair of Cast Products model TMC1008-4 wheel chocks provided with the apparatus.

The wheel chocks shall be stored in wheel chock compartments located in the rear wheel area on both sides of the apparatus.

HANDRAILS

All handrails shall be constructed of knurled stainless steel of not less than 1-1/4" in diameter. All railing shields and brackets shall be chrome plated, and shall be bolted to the body with stainless steel bolts. The lower bracket on all vertical handrails shall have a drain hole drilled in it at the lowest point.

The following handrails shall be provided on the apparatus:

There shall be a handrail installed on the top left front of the body.

There shall be a handrail installed on the top right front of the body.

There shall be a vertical handrail installed at the left rear of the apparatus.

There shall be a vertical handrail installed on the right rear of the apparatus.

FUEL TANK GAUGE ACCESS PANEL

There shall be a removable panel provided in the rear compartment to allow for access to the fuel tank gauge without removing the fuel tank.

LICENSE PLATE BRACKET



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be a license plate bracket mounted on the rear of the apparatus. A clear LED light shall be incorporated into the bracket.

FULL WIDTH HOSE BED STEP

There shall be a full width tread plate step located above the rear compartment door. The step shall be used to assist in reloading the hose bed. The step shall also include hand-holds in the rear of the step to be used when climbing the rear of the truck.

QL-12 ELECTRICAL SYSTEM

Wiring harnesses shall be the automotive type, engineered specifically for the builder's apparatus, and shall meet the following criteria. Under no circumstances shall diodes, resistors, or fusible links be located within the wiring harness. All such components shall be located in an easy to access wiring junction box or the main circuit breaker area. All wiring shall meet white book, baseline advanced design transit coach specification and Society of Automotive Engineers recommended practices. It shall be stranded copper wire core with cross linked polyethylene insulation complying with SAE specification J1128. Each wire shall be hot stamp function coded every three inches starting one inch from the end and continuing throughout the entire harness. In addition to function coding, each wire shall be number, color, and gauge coded.

Wire harnesses shall be wrapped with a high abrasion and chemical resistant thermoplastic polyester elastomer coated polyester yarn for braiding constructions of electrical wiring systems. The braid yarn shall have a minimum tensile strength of 15 lbs. before breaking and have a maximum of 20% elongation before breaking. Temperature properties for the yarn shall range from a minimum 280°F (138°C) service temperature to a maximum -112°F (-80°C) brittleness temperature with a cold flex tolerance of at least -49°F (-45°C).

Harnesses shall be modular in design; a main harness system subdivided into several smaller sub-harnesses. The harness subsections shall be connected using Deutsch branded, heavy duty, environmentally sealed, connectors with silicone seals and a rear insertion/removal contact system. For isolation of electrical "zones" the harness subsections shall consist of a main harness, a pump harness with a separate pump gauge panel harness, a left body harness with a separate left compartment harness, a right body harness with a separate right compartment harness, and a rear body harness with two separate rear compartment harnesses.

The main harness and three body harnesses shall interconnect at a central, easy to reach location and their connectors shall not be obstructed by other harnesses or fuel/air lines. In addition, the main and body harness connectors shall be color coded for ease of identification with their respective colors noted on the accompanying electrical diagrams.

Where connectors are not provided by the electrical component manufacturer, all 12 volt lights and other electrical components (excluding rocker and toggle switches) shall connect to the harnesses using Deutsch brand connectors; butt connectors are considered unacceptable.

All Deutsch connectors shall meet the following criteria:

- All connectors shall have a minimum IP67 rating.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

- Temperature range from -67°F (-55°C) to 257°F (125°C) continuous at rated current.
- Only solid contacts will be used. Stamped and formed contacts are unacceptable.
- All contacts shall be soldered unless a crimping tool or machine is used that gives an even and precise pressure for the terminal being used.
- All contacts shall be pull-tested to insure their integrity.

V-MUX ELECTRICAL MANAGEMENT SYSTEM

The apparatus shall be equipped with a V-MUX Multiplex System. There are several key benefits to multiplexing, one is to reduce the number of connections in a vehicles electrical system, because of this it is important to limit the amount of modules that control certain functions of the vehicle.

Outputs:

The outputs shall perform all the following items without added modules to perform any of the tasks:

1. **Load Shedding:** The System shall have the capability to Load Shed with 8 levels any output. This means you can specify which outputs (barring NFPA restrictions) you would like Load Shed. Level 1 12.9v, Level 2 12.5V, Level 3 - 12.1V, Level 4 - 11.7V, Level 5 11.3V, Level 6 10.9V, Level 7 10.5, Level 8 10.1. Unlike conventional load shedding devices you can assign a level to any or all outputs. No add-on modules shall be acceptable; the module with the outputs must perform this function.
2. **Load Sequencing:** The System shall be able to sequence from 0 8 levels any output. With 0 being no delay and 1 being a 1 second delay, 2 being a 2 second delay and so on. Sequencing reduces the amount of voltage spikes and drops on your vehicle, and can help limit damage to your charging system. No add-on modules shall be acceptable; the module with the outputs must perform this function.
3. **Output Device:** The System shall have solid-state output devices. Each solid-state output shall be a MOS-FET (Metal Oxide Semiconductor - Field Effect Transistors); MOS-FETs are solid-state devices with no moving parts to wear out. A typical relay when loaded to spec has a life of 100,000 cycles. The life of a FET is more than 100 times that of a relay. No add-on modules shall be acceptable; the module with the outputs must perform this function.
4. **Flashing Outputs:** The System shall be able to flash any output in either A or B phase, and logic is used to shut down needed outputs in park, or any one of several combined interlocks. The flash rate can be selected at either 80, or 160 FPM. This means any light can be specified with a multiplex truck with no need to add flashers. Flashing outputs can also be used to warn of problems. No add-on modules shall be acceptable; the module with the outputs must perform this function.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

5. PWM: The modules shall have the ability to PWM at some outputs so that a Headlight PWM module is not needed. No add-on modules shall be acceptable; the module with the outputs must perform this function.
6. Diagnostics: An output shall be able to detect either a short or open circuit.

Inputs:

1. The inputs shall have the ability to switch by a ground or battery signal.
2. The inputs shall be filtered for noise suppression via hardware and software so that RF or dirty power will not trick an input into changing its status.

System Network:

The Multiplex system shall contain a Peer-to-Peer network. A Master Slave Type network is not suitable for the Fire/Rescue industry. A Peer-to-Peer network means that all the modules are equal on the network; a Master is not needed to tell other nodes when to talk.

System Reliability:

The Multiplex system shall be able to perform in extreme temperature conditions, from -40° to +85° C (-40° to +185° F.) The system shall be sealed against the environment, moisture, humidity, salt or fluids such as diesel fuel, motor oil or brake fluid. The enclosures shall be rugged to withstand being mounted in various locations or compartments around the vehicle. The modules shall be protected from over voltage and reverse polarity.

WEATHERPROOF DOOR SWITCHES

Due the harsh environment and susceptibility to moisture on the fire ground, the fire apparatus compartment doors shall utilize weatherproof switches. Two different types of switches shall be used. Weatherproof proximity switches shall be utilized. **No Exceptions.**

The switches shall be used for activation of the compartment lights and to provide a signal to the door open circuit in the cab.

TAIL LIGHTS

There shall be a Whelen 600 series LED tail light assembly installed on each side of the rear of the apparatus. Each assembly shall include one (1) red LED stop/tail light model number 60BTT, one (1) amber LED model 60A00TAR turn light with arrow and one (1) clear halogen backup light model 60F000CR. The lights shall be mounted in a chrome plated four (4) light composite housing. The remaining slot in the housing shall be filled with a warning light specified in the warning light section.

MIDSHIP TURN SIGNALS

There shall be two (2) Truck-Lite Model 21 LED midship auxiliary/turn signal lights installed. One (1) light shall be located in the wheel well area on each side of the body.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

BODY GROUND LIGHTING

Four (4) Truck-Lite model 40, 4" round lights shall be installed beneath the apparatus in areas where personnel may be expected to climb on and off of the apparatus. The lights shall illuminate the ground within 30" of the apparatus to provide visibility of any obstructions or hazards. These areas shall include, but shall not be limited to, side running boards and the rear step area.

There shall be four (4) aluminum ground light brackets provided to position each ground light so as to illuminate the ground within 30" of the apparatus.

CLEARANCE LIGHTS

Grote model 65282 red LED clearance lights shall be installed in the rear tailboard as necessary to be in full compliance with applicable ICC and DOT codes and regulations. Clearance reflectors shall be placed on the apparatus to be in full compliance with applicable ICC and DOT codes and regulations.

REAR WORK LIGHT SWITCH

A switch shall be installed above the tail light bezel on the left side of the rear of the apparatus. The switch shall be wired to the backup lights to provide additional work lighting. The rear work light circuit shall be deactivated when the park brake is disengaged. In addition to the lights being activated by the above switch, the lights shall also come on when the transmission is placed in reverse.

RECEIVER TUBE FOR PORTABLE WINCH

There shall be one (1) square receiver tube provided for use with a portable winch. There shall also be an electrical connection provided near the receiver tube for use with the portable winch.

The receiver shall be located at the right front of the vehicle and shall have a straight pull rating of 9,000#.

RECEIVER TUBE FOR PORTABLE WINCH

There shall be two (2) square receiver tubes provided for use with a portable winch. There shall also be an electrical connection provided near the receiver tubes for use with the portable winch.

The receivers shall be located one each side of the apparatus.

The receivers shall have a straight pull rating of 9,000#.

UPPER ZONE A

There shall be one (1) 28-1/4" Whelen Engineering Freedom, model FT8CC00F, LED Lightbar installed on the front center of the chassis cab, The lightbar shall be equipped with two (2) forward facing white LEDs in the outside positions of the bar. Additionally, there shall be two (2), model FTDRR, red forward facing red LED's in the inner module positions.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be two (2) Whelen Freedom, model FNMINI, 24" LED lightbars installed on the forward section of the chassis cab roof. The lights shall be located each side of the front lightbar and mounted at 30 degrees angles. Each lightbar shall be 24" long and shall be equipped with two (2) corner red LED, one (1) forward facing white LED, and one (1) side facing red LED lights.

The lightbars shall be equipped with clear lenses. All clear LED lights in the lightbar shall be deactivated in the Blocking Right of Way mode.

UPPER ZONE C

There shall be two (2) Whelen, model L31 Super-LED® rotating beacon installed high at the rear of the apparatus. The beacons shall have a Cast Aluminum Base. Both beacons shall have a red LED and lens, model L31HRFN.

LOWER ZONE A

The warning lights shall be supplied and installed by the chassis manufacturer.

LOWER ZONE B

There shall be two (2) Whelen, model 60R02FRR Super-LED® lights with flanges installed. Each light shall have red LEDs and a red lens.

LOWER ZONE C

There shall be two (2) Whelen, model 60R02FRR Super-LED® lights with flanges installed. Each light shall have red LEDs and a red lens.

LOWER ZONE D

There shall be two (2) Whelen, model 60R02FRR Super-LED® lights with flanges installed. Each light shall have red LEDs and a red lens.

LED ROOF MOUNT 12 VOLT LIGHT

There shall be one (1) Fire Research Spectra LED Floodlight model SPA800-Q20 contour roof mount light installed on the apparatus. The mounting brackets shall attach to the bottom of the lamphead and be machined to conform to the roof radius. Wiring shall extend from a weatherproof strain relief at the rear of the lamphead.

The lamphead shall have eighty four (84) ultra-bright white LEDs, 72 for flood lighting and 12 to provide a spot light beam pattern. It shall operate at 12/24 volts DC, draw 18/9 amps, and generate 20,000 lumens of light. The lamphead shall have a unique lens that directs flood lighting onto the work area and focuses the spot light beam into the distance. The lamphead shall be no more than 5-7/8" high by 14" wide. The lamphead and mounting bracket shall be powder coated white. The light shall be for fire service use.

The 12 volt front scene light shall be controlled by a switch located in the chassis cab. The switch shall have an indicator that shall illuminate when the switch is in the "ON" position. The light shall be controlled by one (1) switch. The switch shall be labeled "FRONT SCENE."



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The 12 volt scene light shall be located on the front of the chassis cab.

LED SURFACE MOUNT 12 VOLT LIGHT

There shall be one (1) Fire Research Spectra LED Scene Light model SPA260-Q15 surface mount light installed on the apparatus. The light shall be mounted with four (4) screws to a flat surface. It shall be no more than 5-7/8" high by 14-1/2" wide and have a profile of less than 1-3/4" beyond the mounting surface. Wiring shall extend from a weatherproof strain relief at the rear of the lamphead.

The lamphead shall have sixty (60) ultra-bright white LEDs, 56 for flood lighting and 4 to provide a spot light beam pattern. It shall operate at 12/24 volts DC, draw 13/6.5 amps, and generate 15,000 lumens of light. The lamphead shall have a unique lens that directs flood lighting onto the work area and focuses the spot light beam into the distance. The lamphead shall be powder coated. The LED scene light shall be for fire service use.

The 12 volt left side scene light shall be controlled by a switch located in the chassis cab. The switch shall have an indicator that shall illuminate when the switch is in the "ON" position. The light shall be controlled by one (1) switch. The switch shall be labeled "LEFT SCENE."

The 12 volt scene light shall be located on the left side of the apparatus body.

12 VOLT SCENE LIGHTS

There shall be two (2) Fire Research, model SPA900-Q65, Spectra LED Flood and Loading Light surface mount light installed on the apparatus. The light shall be mounted with four (4) screws to a flat surface. It shall be 6 3/4" high by 9" wide and have a profile of less than 1 3/4" beyond the mounting surface. Wiring shall extend from a weatherproof strain relief at the rear of the lamphead.

The light shall have twenty-four (24) white LEDs. It shall operate at 12/24 volts DC, draw 6/3 amps and generate 4600 lumens of light. The lens shall redirect the light along the vehicle and out onto the working area. The lamphead housing shall be aluminum with a chrome colored bezel.

The 12 volt rear scene light shall be controlled by a switch located in the chassis cab. The switch shall have an indicator that shall illuminate when the switch is in the "ON" position. The light shall be controlled by one (1) switch. The switch shall be labeled "REAR SCENE."

In addition to the switch located in the cab, the 12 volt rear scene light shall be activated by the rear work light switch and when the apparatus is placed in reverse.

The 12 volt scene light shall be located on the rear of the apparatus body.

LED SURFACE MOUNT 12 VOLT LIGHT

There shall be one (1) Fire Research Spectra LED Scene Light model SPA260-Q15 surface mount light installed on the apparatus. The light shall be mounted with four (4) screws to a flat



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

surface. It shall be no more than 5-7/8" high by 14-1/2" wide and have a profile of less than 1-3/4" beyond the mounting surface. Wiring shall extend from a weatherproof strain relief at the rear of the lamphead.

The lamphead shall have sixty (60) ultra-bright white LEDs, 56 for flood lighting and 4 to provide a spot light beam pattern. It shall operate at 12/24 volts DC, draw 13/6.5 amps, and generate 15,000 lumens of light. The lamphead shall have a unique lens that directs flood lighting onto the work area and focuses the spot light beam into the distance. The lamphead shall be powder coated. The LED scene light shall be for fire service use.

The 12 volt right side scene light shall be controlled by a switch located in the chassis cab. The switch shall have an indicator that shall illuminate when the switch is in the "ON" position. The light shall be controlled by one (1) switch. The switch shall be labeled "RIGHT SCENE."

The 12 volt scene light shall be located on the right side of the apparatus body.

STREAMLIGHT RECHARGEABLE LED FIRE VULCANS

There shall be four (4) Streamlight, model 44451, high intensity rechargeable LED Fire Vulcans® supplied and installed on the apparatus. Each Vulcan shall feature C4® LED technology with a 50,000 hour lifetime and shall include two (2) bright blue LED taillights, utilizing blinking and steady modes. Each Vulcan shall be orange in color, include one (1) Vehicle Mount System (with quick-release strap), and shall be wired directly to the chassis batteries.

BODY PAINT PREPARATION

After the body and components have been fabricated and assembled they then shall be disassembled prior to painting so when the apparatus is completed there shall be finish paint beneath the removable components. The apparatus body and components shall be metal finished as follows to provide a superior substrate for painting.

All aluminum sections of the body shall undergo a thorough cleaning process starting with a phosphoric acid solution to begin the etching process followed by a complete rinse. The next step shall consist of a chemical conversion coating applied to seal the metal substrate and become part of the aluminum surface for greater film adhesion.

After the cleaning process, the body and its components shall be primed with a High Solids primer and the seams be caulked.

All bright metal fittings, if unavailable in stainless steel or polished aluminum, shall be heavily chrome plated. Iron fittings shall be copper under plated prior to chrome plating.

PAINT PROCESS

The paint process shall follow the strict standards as set forth by PPG Fleet Finish Guidelines.

The body shall go through a three-stage paint process: primer coat, base coat (color), and clear coat. In the first stage of the paint process the body shall be coated with PPG F3980 Low VOC / High Solids primer to achieve a total thickness of 2-4 mills. In the second stage of the paint



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

process the body shall be painted with PPG FBCH Delfleet™ High Solids Polyurethane Base Coat. A minimum of two to three coats of paint shall be applied to achieve hiding. In the final stage of the paint process the body shall be painted with PPG DCU-2002 Clear Coat. A minimum of two to three coats shall be applied to achieve a total dry film thickness of 2-3 mills.

As part of the curing process the painted body shall go through a Force Dry / Bake Cycle process. The painted components shall be baked at 185 degrees for 3 hours to achieve a complete coating cure on the finished product.

HAND POLISHED

After the Force Dry / Bake Cycle and ample cool down time, the coated surface shall be sanded using 3M 1000, 1200, and or 1500 grit sandpaper to remove surface defects. In the final step, the surface shall be buffed with 3M super-duty compound to add extra shine to coated surface. No more than .5 mil of clear shall be removed in this process.

BODY COLOR

The body shall be painted with PPG High Solids Polyurethane Base Coat. The single tone body shall be painted (RED) PPG# FBCH-71096-ALT.

COMPARTMENT COATING

The interior of the body compartment shall be coated with gray Line-X® thermoplastic polyurethane coating. The coating shall be durable enough to withstand every day abuse of equipment removal and shifting.

LINE-X® THERMOPLASTIC COATING

In designated areas, Line-X® XS-350, a two component spray-in-place thermoplastic polyurethane system shall be used for maximum protection of the body and equipment. Line-X® XS-350 is a 100% high performance aromatic solids pure Polyurea elastomeric membrane. The coating shall be a fast cure, textured surface, multi-purpose material designed for commercial and industrial applications. It shall exhibit excellent adhesion to the body and serve as a protective, abrasion resistant liner where applied.

The coating shall exhibit the following minimum typical physical properties:

- Tensile strength - 3,432 PSI (ASTM D-412)
- Elongation - 162% (ASTM D-412)
- Tear Strength - 783 PLI (ASTM D-624)
- Shore D Hardness - 60 +/-1 (ASTM D-2240)

TOUCH UP PAINT

One (1) two ounce bottle of acrylic enamel touch-up paint or two (2) touch up paint pens, if color is available, shall be supplied.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

CORROSION PREVENTION

One (1) 3.75 ounce tube of Electrolysis Corrosion Control (ECK) shall be provided to use whenever additional items are mounted to the apparatus.

ECK protects aluminum and stainless steel against electrolytic reaction, isolates dissimilar metals and gives bedding protection for hardware and fasteners. ECK contains anti-seizing lubricant for threads. ECK is dielectric and perfect for use with electrical connectors.

NFPA COMPLIANT REFLECTIVE STRIPING

Reflective striping shall be applied to the exterior of the apparatus in a manner consistent with NFPA 1901. It shall consist of a 1", 6", and a 1" wide stripe low across the front of the chassis and along the sides up to the first compartment on each side where it shall angle up and back to a point in the upper compartments where it shall then run level to the back edge of the body. There be a 1" gap provided between each of the stripes.

REFLECTIVE STRIPE TERMINATION

The NFPA reflective stripe located on the side of the apparatus shall terminate at the side of the front bumper.

There shall also be reflective striping provided on the front face of the bumper.

The color of the upper reflective striping on the apparatus shall be white.

The color of the main reflective striping on the apparatus shall be white.

The color of the lower reflective striping on the apparatus shall be white.

RUB RAIL REFLECTIVE STRIPING

There shall be 2" reflective striping installed in the rub rail channel. The reflective striping shall be diamond grade quality material for increased visibility. The reflective shall be silver in color.

CHASSIS CAB PAINT BREAK

There shall be 22kt engine turned gold leaf striping installed at the two tone paint break on the chassis cab.

CAB DOOR REFLECTIVE STRIPING

The reflective striping on the inside of the chassis door shall be provided by the chassis manufacturer.

CHEVRON REFLECTIVE STRIPING ON REAR

In addition to the custom striping pattern supplied on the apparatus, there shall be additional reflective striping applied to the entire rear of the unit. The reflective striping shall cover at least 50% of the rear facing vertical surface per NFPA 1901. The striping shall consist of alternating



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

reflective stripes. Each stripe shall be a minimum of 6" in width and shall be applied to the apparatus at 45° angle.

The chevron pattern shall include any painted storage compartment doors.

CHEVRON REFLECTIVE STRIPING, RED/FLUORESCENT YELLOW-GREEN

The chevron striping shall consist of 3M part numbers 1172 EC, red and 3983, fluorescent yellow-green.

Only 3M Diamond Grade™ VIP Reflective Striping shall be used. 3M Diamond Grade™ VIP Reflective Striping is a wide angle prismatic lens reflective sheeting designed for the production of durable traffic control signs and delineators that are exposed vertically in service. This sheeting is designed to provide higher sign brightness than sheetings that use glass bead lenses. It is intended to also provide high sign brightness in the legibility distance where other sheetings do not.

Specification

MODEL

The chassis shall be a Gladiator model. The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. The chassis shall be manufactured for heavy duty service with the strength and capacity to support a fully laden apparatus, one hundred (100) percent of the time.

MODEL YEAR

The chassis shall have a vehicle identification number that reflects a 2015 model year.

COUNTRY OF SERVICE

The chassis shall be put in service in the country of United States of America (USA).

The chassis will meet applicable U.S.A. federal motor vehicle safety standards per CFR Title 49 Chapter V Part 571 as clarified in the incomplete vehicle book per CFR Title 49 Chapter V Part 568 Section 4 which accompanies each chassis. Spartan Chassis is not responsible for compliance to state, regional, or local regulations. Dealers should



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

identify those regulations and order any necessary optional equipment from Spartan Chassis or their OEM needed to be in compliance with those regulations.

APPARATUS TYPE

The apparatus shall be a pumper vehicle designed for emergency service use which shall be equipped with a permanently mounted fire pump which has a minimum rated capacity of 750 gallons per minute (3000 L/min). The apparatus shall include a water tank and hose body whose primary purpose is to combat structural and associated fires.

VEHICLE TYPE

The chassis shall be manufactured for use as a straight truck type vehicle and designed for the installation of a permanently mounted apparatus behind the cab. The apparatus of the vehicle shall be supplied and installed by the apparatus manufacturer.

AXLE CONFIGURATION

The chassis shall feature a 4 x 2 axle configuration consisting of a single rear drive axle with a single front steer axle.

GROSS AXLE WEIGHT RATINGS FRONT

The front gross axle weight rating (GAWR) of the chassis shall be 23,000 pounds.

This front gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

GROSS AXLE WEIGHT RATINGS REAR

The rear gross axle weight rating (GAWR) of the chassis shall be 31,000 pounds.

This rear gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

PUMP PROVISION



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The chassis shall include provisions to mount a drive line pump in the middle of the chassis, behind the cab, more commonly known as the midship location.

CAB STYLE

The cab shall be a custom, fully enclosed, EMFD model with a 10.00 inch raised roof over the driver, officer, and crew area, designed and built specifically for use as an emergency response vehicle by a company specializing in cab and chassis design for all emergency response applications. The cab shall be designed for heavy-duty service utilizing superior strength and capacity for the application of protecting the occupants of the vehicle. This style of cab shall offer up to eight (8) seating positions.

The cab shall incorporate a fully enclosed design with side wall roof supports, allowing for a spacious cab area with no partition between the front and rear sections of the cab. To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side wall panels shall be assembled using a combination of welds and proven industrial adhesives designed specifically for aluminum fabrication for construction.

The cab shall be constructed using multiple aluminum extrusions in conjunction with aluminum plate, which shall provide proven strength and the truest, flattest body surfaces ensuring less expensive paint repairs if needed. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

All interior and exterior seams shall be sealed for optimum noise reduction and to provide the most favorable efficiency for heating and cooling retention.

The cab shall be constructed of 5052-H32 corrosion resistant aluminum plate. The cab shall incorporate tongue and groove fitted 6061-T6 0.13 & 0.19 inch thick aluminum extrusions for extreme duty situations. A single formed, one (1) piece extrusion shall be used for the "A" pillar, adding strength and rigidity to the cab as well as additional roll-over protection. The cab side walls and lower roof skin shall be 0.13 inch thick; the rear wall and raised roof skins shall be 0.09 inch thick; the front cab structure shall be 0.19 inch thick.

The exterior width of the cab shall be 99.40 inches wide with a minimum interior width of 91.00 inches. The overall cab length shall be 137.10 inches with 60.00 inches from the centerline of the front of the axle to the back of the cab.

The cab interior shall be designed to afford the maximum usable interior space and attention to ergonomics with hip and legroom while seated which exceeds industry standards. The crew cab floor shall be flat across the entire walking area for ease of movement inside the cab.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The cab shall offer an interior height of 57.50 inches from the front floor to the headliner and a rear floor to headliner height of 65.00 inches in the raised roof area, at a minimum. The cab shall offer an interior measurement at the floor level from the rear of the engine tunnel to the rear wall of the cab of 55.88 inches. All interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

The cab shall include a driver and officer area with two (2) cab doors large enough for personnel in full firefighting gear. The front doors shall offer a clear opening of 40.25 inches wide X 53.50 inches high, from the cab floor to the top of the door opening. The cab shall also include a crew area with up to two (2) cab doors, also large enough for personnel in full firefighting gear. The rear doors shall offer a clear opening of 32.25 inches wide X 61.00 inches high, from the cab floor to the top of the door opening.

The cab shall incorporate a progressive two (2) step configuration from the ground to the cab floor at each door opening. The progressive steps are vertically staggered and extend the full width of each step well allowing personnel in full firefighting gear to enter and exit the cab easily and safely.

The first step for the driver and officer area shall measure approximately 11.50 inches deep X 31.13 inches wide. The intermediate step shall measure approximately 8.50 inches deep X 32.50 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

The first step for the crew area shall measure approximately 11.50 inches deep X 20.44 inches wide. The intermediate step shall measure approximately 10.25 inches deep X 22.75 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.80 inches.

OCCUPANT PROTECTION

The vehicle shall include the Advanced Protection System™ (APS) which shall secure belted occupants and increase the survivable space within the cab. The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The system components shall include:

- Driver steering wheel airbag



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

- Driver dual knee air bags (patent pending) with energy management mounting (patent pending) and officer knee airbag.
- Large driver, officer, and crew area side curtain airbags
- APS advanced seat belt system - retractor pre-tensioners tighten the seat belts around the occupants, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries
- Heavy truck Restraints Control Module (RCM) - receives inputs from the outboard sensors, selectively deploys APS systems, and records sensory inputs immediately before and during a detected qualifying event
- Integrated outboard crash sensors mounted at the perimeter of the vehicle - detects a qualifying front or side impact event and monitors and communicates vehicle status and real time diagnostics of all critical subsystems to the RCM
- Fault-indicating Supplemental Restraint System (SRS) light on the driver's instrument panel

Frontal impact protection shall be provided by the outboard sensors and the RCM. In a qualifying front impact event the outboard sensors provide inputs to the RCM. The RCM activates the steering wheel airbag, driver side dual knee airbags (patent pending), officer side knee airbag, and advanced seat belts for each occupant in the cab.

The APS frontal impact system shall be independently tested to ensure occupant injury criteria does not exceed injury criteria defined in Federal Motor Vehicle Safety Standard (FMVSS) 208. Frontal impact into a rigid barrier at 25 mph shall be conducted by an independent third party test facility using belted 95th percentile Hybrid II test dummies.

Rollover, side impact, and ejection mitigation shall be provided by the outboard sensors and the RCM. In qualifying rollover or side impact events the outboard sensors provide inputs to the RCM. The RCM activates the side curtain airbags and advanced seat belts for each occupant in the cab. The RCM measures roll angle, lateral acceleration, and roll rate to determine if a rollover event or side impact event is imminent or occurring.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

In the event of a qualifying offset or other non-frontal impact, the RCM shall determine and intelligently deploy the front impact protection system, the side impact protection system, or both front and side impact protection systems based on the inputs received from the outboard crash sensors.

The APS side impact system shall be independently tested to ensure occupant injury criteria does not exceed injury criteria defined in Federal Motor Vehicle Safety Standard (FMVSS) 214. Side impact from a moving barrier at 17 mph shall be conducted by an independent third party test facility using belted 50th percentile ES-2re test dummies.

CAB FRONT FASCIA

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate which shall be an integral part of the cab. The fascia shall be Sirius styled, offering an aerodynamic look for a stylish appearance. The cab fascia shall encompass the front of the aluminum cab structure from the bottom of the windshield to the lower section of the cab.

The Sirius style cab fascia shall include provisions for headlights, turn signals and warning light assemblies designed to permit easy access for maintenance. The fascia shall include additional intake provisions at the lower portion just above the bumper further enhancing the total free air intake for engine cooling.

Chrome plated molded plastic bezels shall be provided for lighting assemblies located on each side of the cab fascia for optimum visibility.

FRONT GRILLE

The Sirius fascia shall include a fixed, two (2) piece front grille.

CAB UNDERCOAT

There shall be a rubberized undercoating applied to the underside of the cab that provides abrasion protection, sound deadening and corrosion protection.

CAB SIDE DRIP RAIL

There shall be a drip rail along the top radius of each cab side. The drip rails shall help prevent water from the cab roof running down the cab side.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

CAB PAINT EXTERIOR

The cab shall be painted prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

All metal surfaces on the entire cab shall be ground by disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once the surface is machine ground a high quality acid etching of base primer shall be applied. Upon the application of body fillers and their preparation, the cab shall be primed with a coating designed for corrosion resistance and surface paint adhesion. The maximum thickness of the primer coat shall be 2.00 mils.

The entire cab shall then be coated with an intermediate solid or epoxy surfacing agent that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be a sanding of the cab with 360 grit paper followed by sealing the seams with SEM brand seam sealer.

The cab shall then be painted the specific color designated by the customer with an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on the fire ground or emergency scene. The paint shall have a minimum thickness of 2.00 mils, followed by a clear top coat not to exceed 2.00 mils. The entire cab shall then be baked at 180 degrees for one (1) hour to speed the curing process of the coatings.

CAB PAINT MANUFACTURER

The cab shall be painted with PPG Industries paint.

CAB PAINT PRIMARY/LOWER COLOR

The lower paint color shall be PPG FBCH 71096 ALT Red.

CAB PAINT SECONDARY/UPPER COLOR

The secondary/upper paint color shall be PPG FBCH 2185 white.

CAB PAINT EXTERIOR BREAKLINE



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The upper and lower paint shall meet at a breakline on the cab which shall be located approximately 0.50 inch below the cab door windows on each side of the cab. The breakline shall curve downward at the front cab corners to approximately 6.50 inches below the windshields on the front of the cab ending at either side of the upper grille.

CAB PAINT PINSTRIPE

Where the upper and lower paint colors meet a temporary 0.50 inch wide black pinstripe shall be applied over this break line to offer a more finished look prior to the final pinstripe being installed by the OEM.

CAB PAINT WARRANTY

The cab and chassis shall be covered by a limited manufacturer paint warranty which shall be in effect for ten (10) years from the first owner's date of purchase or in service or the first 100,000 actual miles, whichever occurs first.

CAB PAINT INTERIOR

The visible interior cab structure surfaces shall be painted with black Spar-Liner spray on bed liner product which shall mold to each surface of the cab interior. The Spar-Liner shall be environmentally friendly and chemically resistant.

CAB ENTRY DOORS

The cab shall include four (4) entry doors, two (2) front doors and two (2) crew doors designed for ease of entering and egress when outfitted with an SCBA. The doors shall be constructed of extruded aluminum with a nominal thickness of 0.13 inch. The exterior skins shall be constructed of 0.13 inch aluminum plate.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each door hinge shall be piano style with a 0.38 inch pin and shall be constructed of stainless steel.

CAB ENTRY DOOR TYPE



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

All cab entry doors shall be barrier clear design resulting in exposed lower cab steps. The doors shall provide approximately 32.00 inches of clearance from the ground to the bottom of the door so cab doors may be opened un-hindered by most obstacles encountered, such as guard rails along interstate highways.

CAB INSULATION

The cab ceiling and walls shall include 1.00 inch thick foam insulation. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

CAB STRUCTURAL WARRANTY

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The cab structure shall be warranted for a period of ten (10) years or one hundred thousand (100,000) miles which ever may occur first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

CAB TEST INFORMATION

The cab shall have successfully completed the preload side impact, static roof load application and frontal impact without encroachment to the occupant survival space when tested in accordance with Section 4 of SAE J2420 COE Frontal Strength Evaluation Dynamic Loading Heavy Trucks, Section 5 of SAE J2422 Cab Roof Strength Evaluation Quasi -Static Loading Heavy Trucks and ECE R29 Uniform Provisions Concerning the Approval of Vehicles with regard to the Protection of the Occupants of the Cab of a Commercial Vehicles Annex 3 Paragraph 5.

The above tests have been witnessed by and attested to by an independent third party. The test results were recorded using cameras, high speed imagers, accelerometers and strain gauges. Documentation of the testing shall be provided upon request.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

ELECTRICAL SYSTEM

The chassis shall include a single starting electrical system which shall include a 12 volt direct current Weldon brand of multiplexing system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom. All nodes and sealed Deutsch connectors shall be waterproof.

OEM WIRING

The wiring system shall include a custom J1939 interface harness drop provided by the chassis manufacturer designed to meet the requirements provided by the OEM.

MULTIPLEX DISPLAY

The multiplex electrical system shall include (2) Weldon Vista IV displays with interactive touchscreens. The displays shall be located one (1) on the right side of the dash in the switch panel and one (1) on the left side of the dash in the switch panel. The Vista IV displays shall feature full color LCD touchscreens. The display shall include a message bar displaying the time of day and important messages requiring acknowledgement by the user on the top of the screen in the order they are received. There shall be eight (8) push button virtual controls, four (4) on each side of the display in addition to the touchscreen virtual controls, for the on-board diagnostics. The display screens shall be video ready for back-up cameras, thermal cameras, and DVD.

The Vista IV displays shall offer varying fonts and background colors. The displays shall be fully programmable to the needs of the customer and shall offer virtually infinite flexibility for screen configuration options.

DATA RECORDING SYSTEM

The chassis shall have a Weldon Vehicle Data Recorder (VDR) system installed. The system shall be designed to meet NFPA 1901 and shall be integrated with the Weldon Multiplex electrical system. The following information shall be recorded:

- Vehicle Speed
- Acceleration



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

- Deceleration
- Engine Speed
- Engine Throttle Position
- ABS Event
- Seat Occupied Status
- Seat Belt Status
- Master Optical Warning Device Switch Position
- Time
- Date

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system.

ACCESSORY POWER

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load. One (1) power stud shall be capable of carrying up to a 15 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud. A 225 amp battery direct power and ground stud shall be provided and installed on the chassis near the left hand battery box for OEM body connections.

AUXILIARY ACCESSORY POWER

An auxiliary set of power and ground studs shall be provided and installed in the officer side under seat storage compartment. The power and ground studs shall be circuit protected with a 40 amp breaker. The studs shall be 0.38 inch diameter and be capable of carrying up to a 40 amp battery direct load.

ADDITIONAL ACCESSORY POWER



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

An additional ten (10) position blade type fuse panel shall be installed behind the officer's seat. The fuse panel shall be protected by a 40 amp fuse located at the batteries. The panel shall be capable of carrying up to a maximum 40 amp battery direct load.

EXTERIOR ELECTRICAL TERMINAL COATING

All terminals exposed to the elements will be sprayed with a high visibility protective rubberized coating to prevent corrosion.

ENGINE

The chassis engine shall be a Cummins ISX15 engine. The ISX15 engine shall be an in-line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 600 horse power at 1800 RPM and shall be governed at 2100 RPM. The torque rating shall feature 1850 foot pounds of torque at 1200 RPM with 912 cubic inches (14.9 liter) of displacement.

The ISX15 engine shall feature a VGT™ Turbocharger, a high pressure common rail fuel system, fully integrated electronic controls with an electronic governor, and shall be EPA certified to meet the 2013 emissions standards using cooled exhaust gas recirculation and selective catalytic reduction technology.

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgo brand Citgard 500, or equivalent SAE 15W40 CJ4 low ash engine oil which shall be utilized for proper engine lubrication.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

CAB ENGINE TUNNEL

The cab interior shall include an integrated engine tunnel constructed of 5052-H32 Marine Grade 0.19 of an inch thick aluminum alloy plate. The tunnel shall be a maximum of 46.50 inches wide X 29.00 inches high.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

DIESEL PARTICULATE FILTER CONTROLS

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

ENGINE PROGRAMMING HIGH IDLE SPEED

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

ENGINE HIGH IDLE CONTROL

The vehicle shall be equipped with an automatic high-idle speed control. It shall be pre-set so when activated, it will operate the engine at the appropriate RPM to increase alternator output. This device shall operate only when the master switch is activated and the transmission is in neutral with the parking brake set. The device shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall be available to manually or automatically re-engage when the brake is released, or when the transmission is placed in neutral. There shall be an indicator on the Vista display and control screen for the high idle speed control.

ENGINE PROGRAMMING ROAD SPEED GOVERNOR

The engine shall include programming which will govern the top speed of the vehicle.

AUXILIARY ENGINE BRAKE

A compression brake, for the six (6) cylinder engine shall be provided. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS event occurs. The engine compression brake shall activate upon 0% accelerator when in operation mode and actuate the vehicle's brake lights.

The engine shall utilize a variable geometry turbo (VGT) as an integrated auxiliary engine brake to offer a variable rate of exhaust flow, which when activated in conjunction with the compression brake shall enhance the engine's compression braking capabilities.

AUXILIARY ENGINE BRAKE CONTROL



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected:

- A valid gear ratio is detected.
- The driver has requested or enabled engine compression brake operation.
- The throttle is at a minimum engine speed position.
- The electronic controller is not presently attempting to execute an electronically controlled final drive gear shift.
- There is no active ABS event.

The compression brake shall be controlled through an off/low/high rocker switch on the dash.

ELECTRONIC ENGINE OIL LEVEL INDICATOR

The engine oil shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal. The warning shall activate in a low oil situation upon turning on the master battery and ignition switches without the engine running.

FLUID FILLS

The engine oil, coolant, transmission, and power steering fluid fills shall be located under the cab. The windshield washer fill shall be accessible through the front left side mid step.

ENGINE DRAIN PLUG

The engine shall include an original equipment manufacturer installed magnetic oil drain plug.

EMERGENCY ENGINE SHUTDOWN SYSTEM

An emergency engine shutdown, which shuts off the air supply to the engine by activating a flapper valve to stop a run-away engine, shall be installed in the air intake



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

system. It shall be activated by a locking momentary rocker switch located on the rocker switch panel. The shutdown shall also include a locking momentary rocker test switch.

The shutdown shall include a red LED indicator lamp to illuminate when the shutdown system is activated. The indicator lamp shall be clearly labeled for identification.

Resetting this flapper valve shall require manually resetting the rocker switch and turning the lever on the air intake flapper valve. Refer to the chassis operator manual for complete instructions for testing and resetting the air intake flapper valve.

ENGINE WARRANTY

The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.

REMOTE THROTTLE HARNESS

An apparatus interface wiring harness for the engine and transmission pump interlocks shall be supplied with the chassis. The harness shall include a connector for connection to a chassis pump panel harness supplied by the body builder and shall terminate in the left frame rail behind the cab for connection by the body builder. The harness shall include circuits deemed for a pump panel and shall contain circuits for a hand throttle, and a multiplexed gauge. Separate circuits shall also be included for a pump control switch, "Pump Engaged" and "OK to Pump" indicator lights, open compartment ground, start signal, park brake ground, ignition signal, master power, clean power, customer ignition, air horn solenoid switch, high idle switch and high idle indicator light.

ENGINE PROGRAMMING REMOTE THROTTLE

The engine ECM discreet wire remote throttle circuit will be turned on for use with a discreet wire based pump controller.

CRUISE CONTROL

The chassis will be provided with a cruise control system. There shall be two (2) switches to control the engine inputs for cruise on/off, and set/resume/accelerate. The brake pedal activation shall deactivate cruise operation.

ENGINE PROGRAMMING IDLE SPEED



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The engine low idle speed will be programmed at 700 rpm.

ENGINE FAN DRIVE

The engine cooling system fan shall incorporate a thermostatically controlled, Horton clutched type fan drive.

When the clutched fan is disengaged it shall facilitate improved vehicle performance, cab heating in cold climates, and fuel economy. The fan clutch design shall be fail safe so that if the clutch drive fails the fan shall engage to prevent engine overheating due to the fan clutch failure.

ENGINE COOLING SYSTEM

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the emergency response industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall be comprised of a charge air cooler to radiator serial flow package that provides the maximum cooling capacity for the specified engine as well as serviceability. The main components shall include a surge tank, a charge air cooler bolted to the front of the radiator, recirculation shields, a shroud, a fan, and required tubing.

The radiator shall be a down-flow design constructed with aluminum cores, plastic end tanks, and a steel frame. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injected molded polymer eleven (11) blade fan with a fiberglass fan shroud.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and sight glass to monitor the level of the coolant. The surge tank shall have a dual seal cap that meets the engine manufacturer's pressure requirements, and allows for expansion and recovery of coolant into a separate integral expansion chamber.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with cast tanks. All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel “constant torque” style clamps meeting the engine manufacturer's requirements.

ENGINE COOLING SYSTEM PROTECTION

The engine cooling system shall include a recirculation shield designed to act as a light duty skid plate below the radiator to provide additional protection for the engine cooling system from light impacts, stones, and road debris. The skid plate shall be painted to match the frame color.

ENGINE COOLANT

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees Fahrenheit.

Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

ENGINE COOLANT FILTER

An engine coolant filter with a shut-off valve for the inlet and outlet shall be installed on the chassis. The location of the filter shall allow for easy maintenance.

Proposals offering engines equipped with coolant filters shall be supplied with standard non-chemical type particulate filters.

ELECTRONIC COOLANT LEVEL INDICATOR



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

ENGINE PUMP HEAT EXCHANGER

A single bundle type coolant to water heat exchanger shall be installed between the engine and the radiator. The heat exchanger shall be designed to prohibit water from the pump from coming in contact with the engine coolant. This shall allow the use of water from the discharge side of the pump to assist in cooling the engine.

COOLANT HOSES

The cooling system hoses shall be silicone heater hose with rubber hoses in the cab interior. The radiator hoses shall be formed silicone coolant hoses with formed aluminized steel tubing. All heater hose, silicone coolant hose, and tubing shall be secured with stainless steel constant torque band clamps.

ENGINE AIR INTAKE

The engine air intake system shall include an ember separator air intake filter which shall be located in the front of the cab behind the right hand side fascia. This filter shall protect the downstream air filter from embers using a combination of unique flat and crimped metal screens constructed into a corrosion resistant steel frame. This multilayered screen shall be designed to trap embers or allow them to burn out before passing through the pack, while creating only minimal air flow restriction through the system. Periodic cleaning or replacement of the screen shall be all that is required after installation.

The engine shall also include an air intake filter which shall be bolted to the frame and located under the front of the cab on the right hand side. The system shall utilize a replaceable dry type filter which ensures dust and debris remains safely contained inside the housing during operation via leak-tight seals. The service cover shall be located on the bottom of the housing, eliminating the chance of contaminating the air intake system during air filter service.

The air flow distribution and dust loading shall be uniform throughout the high-performance filter element, which shall result in pressure differential for improved horsepower and fuel economy. The air intake ember separator shall be mounted within easy access via a hinged panel behind the right hand side headlight module. The air



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

intake system shall include a restriction indicator light in the warning light cluster on the instrument panel, which shall activate when the air cleaner element requires replacement.

AIR INTAKE PROTECTION

A light duty skid plate shall be supplied for the engine air intake system below the right front side of the cab. The skid plate shall provide protection for the air intake system from light impacts, stones, and road debris. The skid plate shall be painted to match the frame color.

ENGINE EXHAUST SYSTEM

The exhaust system shall be mounted below the frame in the outboard position with the SCR canister in line rearward of the DPF. The exhaust system shall utilize a 90-degree bend in the exhaust tubing from the turbo into a side inlet DPF canister that allows the entire system to be pulled forward. The discharge shall terminate horizontally on the right side of the vehicle ahead of the rear tires.

The exhaust system shall include a diesel particulate filter (DPF), a diesel oxidation catalyst, and a selective catalytic reduction (SCR) catalyst to meet current EPA standards. The selective catalytic reduction catalyst utilizes a diesel exhaust fluid solution consisting of urea and purified water to convert NOx into nitrogen, water, and trace amounts of carbon dioxide. The solution shall be injected into the system through the decomposition tube between the DPF and SCR.

The system shall utilize 0.07 inch thick stainless steel exhaust tubing between the engine turbo and the DPF. Zero leak clamps seal all system joints between the turbo and DPF.

The DPF, the decomposition tube, and the SCR canister through the end of the tailpipe shall be connected with zero leak clamps.

DIESEL EXHAUST FLUID TANK

The exhaust system shall include a molded cross linked polyethylene tank for Diesel Exhaust Fluid (DEF). The tank shall have a capacity of six (6) usable gallons and shall be mounted on the left hand side of the chassis frame behind the batteries below the frame.

The DEF tank shall be designed with capacity for expansion in case of fluid freezing. Engine coolant, which shall be thermostatically controlled, shall be run through lines in



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

the tank to help prevent the DEF from freezing and to provide a means of thawing the fluid if it should become frozen.

The tank fill tube shall be routed under the rear of the cab with the fill neck and splash guard accessible in the top rear step.

ENGINE EXHAUST ACCESSORIES

An exhaust temperature mitigation device shall be shipped loose for installation by the body manufacturer on the vehicle. The temperature mitigation device shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

ENGINE EXHAUST WRAP

The exhaust tubing between the engine turbo and the diesel particulate filter (DPF) shall be wrapped with a thermal cover in order to retain the necessary heat for DPF regeneration. The exhaust wrap shall also help protect surrounding components from radiant heat which can be transferred from the exhaust.

TRANSMISSION

The drive train shall include an Allison model EVS 4000 torque converting, automatic transmission which shall include electronic controls. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.

The transmission shall include two (2) internal oil filters which shall offer Castrol TranSynd™ synthetic TES 295 transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The transmission gear ratios shall be:

1st	3.51:1
2nd	1.91:1
3rd	1.43:1
4th	1.00:1
5th	0.74:1
6th	0.64:1 (if applicable)
Rev	4.80:1



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

TRANSMISSION MODE PROGRAMMING

The transmission, upon start-up, will select five (5) speeds of operation. The sixth speed over drive shall be available with the activation of the mode button on the shifting pad.

TRANSMISSION FEATURE PROGRAMMING

The Allison Gen V-E transmission EVS group package number 127 shall contain the 198 vocational package in consideration of the duty of this apparatus as a pumper. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override.

This package shall be coupled with the use of a split shaft PTO and incorporate pumping circuits. These circuits shall be used allowing the vehicle to operate in the fourth range lockup while operating the pump mode due to the 1 to 1 ratio through the transmission, therefore the output speed of the engine is the input speed to the pump. The pump output can be easily calculated by using this input speed and the drive ratio of the pump itself to rate the gallons of water the pump can provide.

A transmission interface connector shall be provided in the cab. This package shall contain the following input/output circuits to the transmission control module. The Gen V-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

<u>Function ID</u>	<u>Description</u>	<u>Wire assignment</u>
<u>Inputs</u>		
C	PTO Request	142
J	Fire Truck Pump Mode (4th Lockup)	122 / 123
<u>Outputs</u>		
C	Range Indicator	145 (4th)
G	PTO Enable Output	130
	Signal Return	103

ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR

The transmission fluid shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

TRANSMISSION SHIFT SELECTOR

An Allison lever “T” style handle range selector with manual “bump” capability shall be provided and located to the right of the driver within clear view and easy reach. The shift lever shall have low (L), drive (D), neutral (N), and reverse (R) positions as well as a “bump” position for manual operation. The shift selector shall have a graphical Vacuum Florescent Display (VFD) capable of displaying two lines of text. The shift selector shall provide mode indication and a prognostic indicator (wrench symbol) on the digital display. The prognostics monitor various operating parameters and shall alert you when a specific maintenance function is required.

TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE

When the auxiliary brake is engaged, the transmission shall automatically shift to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle.

TRANSMISSION COOLING SYSTEM

The transmission shall include a water to oil cooler system located in the cooling loop between the radiator and the engine. The transmission cooling system shall meet all transmission manufacturer requirements. The transmission cooling system shall feature continuous flow of engine bypass water to maintain uninterrupted transmission cooling.

TRANSMISSION DRAIN PLUG

The transmission shall include an original equipment manufacturer installed magnetic transmission fluid drain plug.

TRANSMISSION WARRANTY

The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.

PTO LOCATION

The transmission shall have two (2) power take off (PTO) mounting locations, one (1) in the 8:00 o'clock position and one (1) in the 1:00 o'clock position.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

DRIVELINE

All drivelines shall be heavy duty metal tube and equipped with Spicer 1810 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. In areas of the driveline where a slip shaft is required, the splined slip joint shall be coated with Glide Coat[®].

MIDSHIP PUMP / GEARBOX

A temporary jackshaft driveline shall be installed by the chassis manufacturer to accommodate the mid-ship split shaft pump as specified by the apparatus manufacturer.

MIDSHIP PUMP / GEARBOX MODEL

The midship pump/gearbox provisions shall be for a Waterous CSUC20 pump.

MIDSHIP PUMP GEARBOX DROP

The Waterous pump gearbox shall have a "C" (medium length) drop length.

MIDSHIP PUMP RATIO

The ratio for the midship pump shall be 2.27:1.

MIDSHIP PUMP LOCATION C/L SUCTION TO C/L REAR AXLE

The midship pump shall be located so the dimension from the centerline of the suction to the centerline of the rear axle is 80.00 inches.

PUMP SHIFT CONTROLS

One (1) pump shift control panel shall be mounted on the lower left section of the center dash panel. The following shall be provided on the panel: a three (3) position locking toggle switch; an engraved PUMP ENGAGED identification light; and an engraved OK TO PUMP identification light. The pump shift control panel shall be black with a yellow border outline. One (1) label indicating pump instructions and the transmission shift selector position used for pumping shall be provided and located so it can be read from



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

the driver's position per NFPA **16.10.1.3**. The road mode shall be selected when the switch is in the up position and pump mode shall be selected when the switch is in the down position.

The center switch position shall exhaust air from both pump and road sides of the pump gear box shift cylinder.

PUMP SHIFT CONTROL PLUMBING

Air connections shall be provided from the air supply tank to the pump shift control valve and from the pump shift control valve to the frame mounted bracket. The frame mounted bracket shall include labeling identifying the pump and road connection points with threaded 0.25 inch NPT fittings on the solenoid for attaching the customer installed pump. The air supply shall be pressure protected from service brake system.

FUEL FILTER/WATER SEPARATOR

The fuel system shall have a Racor S3238 fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve and a see through cover to allow visual inspection of fuel and filter condition. The Racor S3238 shall be a 10 micron filter capable of handling a maximum flow rate of 150 gallons per hour.

A secondary fuel filter shall be included as approved by the engine manufacturer.

An instrument panel lamp and audible alarm which indicates when water is present in the fuel-water separator shall also be included.

FUEL LINES

The fuel system supply and return lines installed from the fuel tank to the engine shall be black textile braided lines which are reinforced with braided high tensile steel wire. The fuel lines shall be connected with reusable steel fittings.

FUEL SHUTOFF VALVE

A fuel shutoff valve shall be installed in the fuel draw line at the primary fuel filter to allow the fuel filter to be changed without loss of fuel to the fuel pump.

ELECTRIC FUEL PRIMER



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Integral to the engine assembly is an electric lift pump that serves the purpose of pre-filter fuel priming.

FUEL COOLER

An aluminum cross flow air to fuel cooler shall be provided to lower fuel temperature allowing the vehicle to operate at higher ambient temperatures. The fuel cooler shall be located behind the rear axle.

FUEL TANK

The fuel tank shall have a capacity of one-hundred (100) gallons and shall measure 35.00 inches in width X 15.00 inches in height X 48.00 inches in length. The baffled tank shall be made of 14 gauge aluminized steel. The exterior of the tank shall be painted with a PRP Corsol™ black anti-corrosive exterior metal treatment finish. This results in a tank which offers the internal and external corrosion resistance. In addition, the exterior of the fuel tank shall be coated with Spar-Liner spray on protective coating.

The tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

The tank is designed with dual draw tubes and sender flanges. The tank shall have 2.00 inch NPT fill ports for right or left hand fill. A 0.50 inch NPT drain plug shall be centered in the bottom of the tank.

The fuel tank shall be mounted below the frame, behind the rear axle. Two (2) three-piece stainless steel strap hanger assemblies with "U" straps bolted midway on the fuel tank front and rear shall be utilized to allow the tank to be easily lowered and removed for service purposes. Rubber isolating pads shall be provided between the tank and the upper tank mounting brackets. Strap mounting studs through the rail, hidden behind the body shall not be acceptable

FUEL TANK FILL PORT

The fuel tank fill ports shall be provided with two (2) left fill ports located one (1) in the forward position and one (1) in the middle position and the right fill port located in the rearward position of the fuel tank.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

FUEL TANK SERVICEABILITY PROVISIONS

The chassis fuel lines shall have additional length provided so the tank can be easily lowered and removed for service purposes. The additional 8.00 feet of length shall be located above the fuel tank and shall be coiled and secured. The fuel line fittings shall be pointed towards the right side (curbside) of the chassis.

FUEL TANK DRAIN PLUG

A 0.5 inch NPT drain plug shall be centered in the bottom of the fuel tank.

FRONT AXLE

The front axle shall be a Meritor Easy Steer Non drive front axle, model number MFS-23. The axle shall include a 3.74 inch drop and a 71.00 inch king pin intersection (KPI). The axle shall include a conventional style hub with a standard knuckle. The weight capacity for the axle shall be rated to 23,000 pounds. This rating shall require special approvals from the wheel manufacturers.

FRONT AXLE WARRANTY

The front axle shall be warranted by Meritor for two (2) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

FRONT WHEEL BEARING LUBRICATION

The front axle wheel bearings shall be lubricated with oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.

FRONT SHOCK ABSORBERS

Two (2) Bilstein inert, nitrogen gas filled shock absorbers shall be provided and installed as part of the front suspension system. The shocks shall be a monotubular design and fabricated using a special extrusion method, utilizing a single blank of steel without a welded seam, achieving an extremely tight peak-to-valley tolerance and maintains consistent wall thickness. The monotubular design shall provide superior strength while maximizing heat dissipation and shock life.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The ride afforded through the use of a gas shock is more consistent and shall not deteriorate with heat, the same way a conventional oil filled hydraulic shock would.

The Bilstein front shocks shall include a digressive working piston assembly allowing independent tuning of the compression and rebound damping forces to provide optimum ride and comfort without compromise. The working piston design shall feature fewer parts than most conventional twin tube and "road sensing" shock designs and shall contribute to the durability and long life of the Bilstein shock absorbers.

Proposals offering the use of conventional twin tube or "road sensing" designed shocks shall not be considered.

FRONT SUSPENSION

The front suspension shall include a ten (10) leaf spring pack in which the longest leaf measures 53.38 inch long and 4.00 inches wide. The springs shall be shot peened for long life and include a military double wrapped front eye. The springs shall be bolted in place with M20 10.9 bolts and have replaceable rubber bushings in the spring eyes. The spring capacity shall be rated at 23,000 pounds.

STEERING COLUMN/ WHEEL

The cab shall include a Douglas Autotech steering column which shall include a seven (7) position tilt, a 2.25 inch telescopic adjustment, and an 18.00 inch, four (4) spoke steering wheel located at the driver's position. The steering wheel shall be covered with black polyurethane foam padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR

The power steering fluid shall be monitored electronically and shall send a signal to activate an audible alarm and visual warning in the instrument panel when fluid level falls below normal.

POWER STEERING PUMP

The hydraulic power steering pump shall be a TRW PS and shall be gear driven from the engine. The pump shall be a balanced, positive displacement, sliding vane type.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

FRONT AXLE CRAMP ANGLE

The chassis shall have a front axle cramp angle of 48-degrees to the left and 44-degrees to the right.

POWER STEERING GEAR

The power steering gear shall be a TRW model TAS 85 with an assist cylinder.

CHASSIS ALIGNMENT

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer.

REAR AXLE

The rear axle shall be a Meritor model RS-30-185 single drive axle. The axle shall include precision forged, single reduction differential gearing, and shall have a fire service rated capacity of 33,000 pounds.

The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the fire industry's demands. The axle shall include rectangular shaped, hot-formed housing with a standard wall thickness of 0.56 of an inch for extra strength and rigidity and a rigid differential case for high axle strength and reduced maintenance.

The axle shall have heavy-duty Hypoid gearing for longer life, greater strength and quieter operation. Industry-standard wheel ends for compatibility with both disc and drum brakes, and unitized oil seal technology to keep lubricant in and help prevent contaminant damage will be used.

REAR AXLE DIFFERENTIAL LUBRICATION

The rear axle differential shall be lubricated with oil.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

REAR AXLE WARRANTY

The rear axle shall be warranted by Meritor for two (2) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

REAR WHEEL BEARING LUBRICATION

The rear axle wheel bearings shall be lubricated with oil.

VEHICLE TOP SPEED

The top speed of the vehicle shall be approximately 68 MPH +/-2 MPH at governed engine RPM.

REAR SUSPENSION

The single rear axle shall feature a Reyco 79KB vari-rate, self-leveling captive slipper type conventional multi-leaf spring suspension, with 57.50 inch X 3.00 inch springs. One (1) adjustable and one (1) fixed torque rod shall be provided.

The rear suspension capacity shall be rated from 21,000 to 31,500 pounds.

REAR SHOCK ABSORBERS

Two (2) Bilstein inert, nitrogen gas filled shock absorbers shall be provided and installed as part of the rear suspension system. The shocks shall be a monotubular design and fabricated using a special extrusion method, utilizing a single blank of steel without a welded seam, achieving an extremely tight peak-to-valley tolerance and maintains consistent wall thickness. The monotubular design shall provide superior strength while maximizing heat dissipation and shock life.

The ride afforded through the use of a gas shock is more consistent and shall not deteriorate with heat, the same way a conventional oil filled hydraulic shock would.

The Bilstein front shocks shall include a digressive working piston assembly allowing independent tuning of the compression and rebound damping forces to provide optimum ride and comfort without compromise. The working piston design shall feature fewer parts than most conventional twin tube and "road sensing" shock designs and shall contribute to the durability and long life of the Bilstein shock absorbers.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Proposals offering the use of conventional twin tube or “road sensing” designed shocks shall not be considered.

FRONT TIRE

The front tires shall be Michelin 425/65R22.5 “L” tubeless radial XFE regional tread.

The front tire stamped load capacity shall be 22,800 pounds per axle with a speed rating of 65 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Tire Intermittent Service Rating load capacity shall be 24,400 pounds per axle with a speed rating of up to 75 miles per hour when properly inflated to 120 pounds per square inch. The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to one (1) hour of loaded travel with a one (1) hour cool down prior to another loaded run.

REAR TIRE

The rear tires shall be Michelin 315/80R-22.5 20PR "L" tubeless radial XDN2 Grip all weather tread.

The rear tire stamped load capacity shall be 33,080 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 130 pounds per square inch.

The Michelin Tire Intermittent Service Rating load capacity shall be 33,080 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 130 pounds per square inch. The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to one (1) hour of loaded travel with a one (1) hour cool down prior to another loaded run.

REAR AXLE RATIO

The rear axle ratio shall be 5.86:1.

TIRE PRESSURE INDICATOR

There shall be a voucher provided with the chassis for a dial style tire pressure indicator at the front and rear tire valve stem. The indicator shall provide visual indication of pressure in the specific tire.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The tire pressure indicators shall be redeemed upon the vehicle manufacturer's receipt of the voucher for installation by the customer.

FRONT WHEEL

The front wheels shall be Alcoa hub piloted, 22.50 inch X 12.25 inch LvL One™ polished aluminum wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts. The wheels shall feature one-piece forged strength and shall include Alcoa's Dura-Bright® finish with XBR technology as an integral part of the wheel surface. Alcoa Dura-Bright® wheels keep their shine without polishing. Brake dust, grime and road debris are easily removed by simply cleaning the wheels with soap and water.

REAR WHEEL

The rear wheels shall be Alcoa hub piloted, heavy duty, 22.50 inch X 9.00 inch LvL One™ polished aluminum wheels with Alcoa Dura-Bright® wheel treatment with XBR® technology as an integral part of the wheel. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

WHEEL TRIM

The front wheels shall include stainless steel lug nut covers and stainless steel baby moons shipped loose with the chassis for installation by the apparatus builder. The baby moons shall have cutouts for oil seal viewing when applicable.

The rear wheels shall include stainless steel lug nut covers and band mounted spring clip stainless steel high hats shipped loose with the chassis for installation by the apparatus builder.

The lug nut covers, baby moons, and high hats shall be RealWheels® brand constructed of 304L grade, non-corrosive stainless steel with a mirror finish. Each wheel trim component shall meet D.O.T. certification.

BRAKE SYSTEM

A rapid build-up air brake system shall be provided. The air brakes shall include a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

applying and releasing the brakes. An inversion valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss. All air reservoirs provided on the chassis shall be labeled for identification.

The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

A four (4) sensor, four (4) modulator Anti-lock Braking System (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards.

Additional safety shall be accommodated through Automatic Traction Control (ATC) which shall be installed on the single rear axle. The ATC system shall apply the ABS when the drive wheels lose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

A virtual style switch shall be provided and properly labeled "mud/snow". When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The Electronic Stability Control (ESC) unit is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicle's motion about the vertical axis, caused, for instance, by cornering or by skidding on a slippery road surface. An acceleration sensor measures the vehicle's lateral acceleration. The Controller Area Network (CAN) bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

FRONT BRAKES



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The front brakes shall be Meritor EX225 Disc Plus disc brakes with 17.00 inch vented rotors.

REAR BRAKES

The rear brakes shall be Meritor 16.50 inch X 8.63 inch S-cam drum type. The brakes shall feature a cast iron shoe.

PARK BRAKE

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

PARK BRAKE CONTROL

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake system. The control shall be yellow in color.

The parking brake actuation valve shall be mounted 6.00 inches to the left of center of the dash within easy access of the driver.

REAR BRAKE SLACK ADJUSTERS

Haldex rear brake automatic slack adjusters shall be installed on the axle.

AIR DRYER

The brake system shall include a Wabco System Saver 1200 air dryer with an integral heater with a Metri-Pack sealed connector. The air dryer incorporates an internal turbo cutoff valve that closes the path between the air compressor and air dryer purge valve during the compressor "unload" cycle. The turbo cutoff valve allows purging of moisture and contaminants without the loss of turbo boost pressure. The air dryer shall be mounted behind the battery box on the left hand side.

FRONT BRAKE CHAMBERS

The front brakes shall be provided with MGM type 24 long stroke brake chambers.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

REAR BRAKE CHAMBERS

The rear axle shall include TSE 30/36 brake chambers which shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake shoes against the brake drum. The TSE Type 36 brake chamber has a 36.00 square inch effective area.

AIR COMPRESSOR

The air compressor provided for the engine shall be a Wabco[®] SS318 single cylinder pass-through drive type compressor which shall be capable of producing 18.7 CFM at 1200 engine RPMs. The air compressor shall feature a higher delivery efficiency translating to more air delivery per horsepower absorbed. The compressor shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation. Superior piston and bore finishing technology shall reduce oil consumption and significantly increasing the system component life.

AIR GOVERNOR

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be located on the air dryer bracket on the left frame rail behind the battery box.

MOISTURE EJECTORS

A heated, automatic moisture ejector with a manual drain provision shall be installed on the wet tank of the air supply system. Manual pet-cock type drain valves shall be installed on all remaining reservoirs of the air supply system.

AIR SUPPLY LINES

The air system on the chassis shall be plumbed with color coded reinforced nylon tubing air lines. The primary (rear) brake line shall be green, the secondary (front) brake line red, the parking brake line orange and the auxiliary (outlet) will be blue.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Brass compression type fittings shall be used on the nylon tubing. All drop hoses shall include fiber reinforced neoprene covered hoses.

AIR INLET CONNECTION

An air connection for the shoreline air inlet shall be supplied.

AIR INLET LOCATION

The air inlet shall be installed in the left hand side lower front step in the forward position.

PLUMBING AIR INLET CONNECTION

The air inlet connector shall be plumbed to the air system with a check valve to prevent air from escaping through the inlet connector.

AIR INLET/ OUTLET FITTING TYPE

The air connector supplied shall be a 0.25 inch size Tru-Flate Interchange style manual connection which is compatible with Milton 'T' style, Myers 0.25 inch Automotive style and Parker 0.25 inch 10 Series connectors.

REAR AIR TANK MOUNTING

If a combination of wheel base, air tank quantity, or other requirements necessitate the location of one or more air tanks to be mounted rear of the fuel tank, these tank(s) will be mounted perpendicular to frame.

WHEELBASE

The chassis wheelbase shall be 220.00 inches.

REAR OVERHANG

The chassis rear overhang shall be 78.00 inches.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

FRAME

The frame shall consist of double rails running parallel to each other with cross members forming a ladder style frame. The frame rails shall be formed in the shape of a "C" channel, with the outer rail measuring 10.25 inches high X 3.50 inches deep upper and lower flanges X 0.38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and 0.38 inches thick. Each rail shall be constructed of 110,000 psi minimum yield high strength low alloy steel. Each double rail section shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches. The frame shall measure 35.00 inches in width.

Proposals calculating the frame strength using the "box method" shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail.

A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the body mounting, or bumper mounting shall not be considered as a cross member. The cross members shall be attached using zinc coated grade 8 fasteners. The bolt heads shall be flanged type, held in place by distorted thread flanged lock nuts. Each cross member shall be mounted to the frame rails utilizing a minimum of 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame.

Any proposals not including additional reinforcement for each cross member shall not be considered.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

The frame and cross members shall carry a lifetime warranty to the original purchaser. A copy of the frame warranty shall be made available upon request.

Proposals offering warranties for frames not including cross members shall not be considered.

FRAME WARRANTY

Summary of Warranty Terms:



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The frame and cross members shall carry a limited lifetime warranty to the original purchaser. The warranty period shall commence on the date the vehicle is delivered to the first end user.

FRAME CLEAR AREA

The chassis frame shall be left clear of chassis mounted components inside or outside the frame rails within the first 30.00 inches behind the cab to allow space for OEM installed components. Cross members may be installed in the clear area if required for proper frame or driveline configuration.

FRAME PAINT

The frame shall be powder coated black prior to any attachment of components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-cured pencil hardness of H-2H. The direct impact resistance test per ASTM D2794 shall have an impact resistance of 120.00 inches per pound at 2 mils.

Any proposals offering painted frame with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

The chassis under carriage consisting of frame, axles, driveline running gear, air tanks and other chassis mounted components shall be painted with gloss black paint. Paint shall be applied prior to airline and electrical wiring installation.

FRONT BUMPER

The chassis shall include a formed channel front bumper. The bumper shall be constructed of 110 psi high strength low alloy steel. The bumper material shall measure



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

10.25 inches high with a 3.50 inch flange and shall be 0.38 inch thick and 104.50 inches wide, with angled front corners.

The bumper shall be primed and painted as specified.

FRONT BUMPER EXTENSION LENGTH

The front bumper shall be extended approximately 24.00 inches ahead of the cab.

FRONT BUMPER EXTENSION FRAME WIDTH

The front bumper extension frame shall feature an overall width of 48.25 inches.

FRONT BUMPER PAINT

The front bumper shall be painted the same as the lower cab color.

FRONT BUMPER APRON

The 24.00 inch extended front bumper shall include an apron constructed of 0.19 inch thick embossed aluminum tread plate.

The apron shall be installed between the bumper and the front face of the cab affixed using stainless steel bolts attaching the apron to the top bumper flange.

FRONT BUMPER COMPARTMENT CENTER

The front bumper shall include a hose tray compartment in the bumper apron located in the center that shall measure 58.00 inches wide X 6.00 inches deep. The compartment shall be constructed of 0.13 inch 5052-H32 grade aluminum and shall include drain holes in the bottom corners to allow excess moisture to escape. The compartment shall include a cover constructed of 0.19 inch thick bright embossed aluminum tread plate.

FRONT BUMPER COMPARTMENT COVER HARDWARE

The front bumper compartment shall include a 7.00 inch stainless lift handle at the top center of the compartment lid. Gas cylinder stays shall hold the cover open. The cover



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

shall held in the closed position via two (2) pull to release rubber "T" style hold down handles located one (1) at each end of the cover.

MECHANICAL SIREN

The front bumper shall include an electro mechanical Federal Q2B™ siren, which shall be streamlined, chrome-plated and shall produce 123 decibels of sound at 10.00 feet. The Q2B™ siren produces a distinctive warning sound that is recognizable at long distances. A unique clutch design provides a longer coast down sound while reducing the amp draw to 100 amps. The siren shall measure 10.50 inches wide X 10.00 inches high X 14.00 inches deep. The siren shall include a pedestal mount to surface mount on a horizontal surface.

MECHANICAL SIREN LOCATION

The siren shall be pedestal mounted on the bumper apron on the furthest outboard section of the bumper on the driver side.

AIR HORN

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 21.00 inches long with a 6.00 inch round flare. The air horns shall be trumpet style with a chrome finish on the exterior and a painted finish deep inside the trumpet.

AIR HORN LOCATION

The air horns shall be recess mounted in the front bumper face, one (1) on the right side of the bumper in the inboard position relative to the right hand frame rail and one (1) on the left side of the bumper in the inboard position relative to the left hand frame rail.

AIR HORN RESERVOIR

One (1) air reservoir, with a 1200 cubic inch capacity, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

ELECTRONIC SIREN SPEAKER



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be one (1) Federal Signal Inc. Dynamax® model ES100C, 100 watt speaker provided. The speaker shall measure 5.90 inches tall X 5.50 inches wide X 2.30 inches deep. The speaker shall include a Federal Signal “Electric F” style grille which shall measure 6.61 inches tall X 6.78 inches wide.

ELECTRONIC SIREN SPEAKER LOCATION

The electronic siren speaker shall be located on the front bumper face in the center position between the frame rails.

FRONT BUMPER TOW EYES

The bumper shall include two (2) painted tow eyes which shall be installed below the front bumper. The tow eyes shall be fabricated from 0.75 inch thick #1020 ASTM-36 hot rolled steel. The inside diameter of the eye shall be 2.00 inches and include a chamfered edge. The tow eyes shall be painted to match the frame.

CAB TILT SYSTEM

The entire cab shall be capable of tilting approximately 45-degrees to allow for easy maintenance of the engine and transmission. The cab tilt pump assembly shall be located on the right side of the chassis above the battery box.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the “Down” button to indicate safe road operation.

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks.

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90 inch ball and be anchored to frame brackets with 1.25 inch diameter studs.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

A steel safety channel assembly, painted safety yellow shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab.

CAB TILT LIMIT SWITCH

A cab tilt limit switch shall be installed. The switch will effectively limit the travel of the cab when being tilted. The final adjustment of the switch shall be performed by the apparatus manufacturer to prevent damage to the cab or any bumper mounted option mounted in the cab tilt arc.

CAB TILT CONTROL RECEPTACLE

The cab tilt control cable shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a six (6) pin Deutsch receptacle with a cap.

The remote control pendant shall include 20.00 feet of cable with a mating Deutsch connector. The remote control pendant shall be shipped loose with the chassis.

CAB WINDSHIELD

The cab windshield shall have a surface area of 2969.88 square inches and be of a two (2) piece wraparound design for maximum visibility.

The glass utilized for the windshield shall include standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and replacement costs.

Each windshield shall be installed using black self locking window rubber.

GLASS FRONT DOOR

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished using electric actuation. The left and right



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

front door windows shall be controlled using a switch on each respective side inner door panel. The driver's door shall include a switch for each powered door window in the cab.

There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as "cozy glass" ahead of the front door roll down windows.

The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

GLASS TINT FRONT DOOR

The windows located in the left and right front doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS REAR DOOR RH

The rear right hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the inner door panel and on the driver's control panel.

GLASS TINT REAR DOOR RIGHT HAND

The window located in the right hand side rear window shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS REAR DOOR LH

The rear left hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the inner door panel and on the driver's control panel.

GLASS TINT REAR DOOR LEFT HAND

The window located in the left hand side rear door shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

GLASS SIDE MID RH

The cab shall include a window on the right side behind the front and ahead of the crew door which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID RIGHT HAND

The window located on the right hand side of the cab between the front and rear doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS SIDE MID LH

The cab shall include a window on the left side behind the front door and ahead of the crew door and above the wheel well which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID LEFT HAND

The window located on the left hand side of the cab between the front and rear doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

CLIMATE CONTROL

The cab shall be equipped with a ceiling mounted combination defrost / heating and air-conditioning system mounted above the engine tunnel in a central location.

The system shall offer sixteen (16) adjustable louvers. Six (6) of the louvers shall face forward towards the windshield, offering 45,000 BTU of heat at 320 CFM for defrosting. The system shall include six (6) rearward facing louvers to direct air for the crew area



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

and four (4) for driver and officer comfort. The HVAC system shall be designed to produce 60,000 BTU of heat and 32,000 BTU of cooling. The HVAC cover shall be made of aluminum which shall be coated with a customer specified interior paint, or protective coating.

All defrost/heating systems shall be plumbed with one (1) seasonal shut-off valve at the front corner on the right side of the cab.

The air conditioner lines shall be a mixture of custom bent zinc coated steel fittings and Aero-quip GH 134 flexible hose with Aero-Quip EZ-Clip fittings.

CLIMATE CONTROL DRAIN

The climate control system shall include a gravity drain for water management. The gravity drain shall remove condensation from the air conditioning system without additional mechanical assistance.

CLIMATE CONTROL ACTIVATION

The heating, defrosting, and air conditioning controls shall be located on the center switch panel in the lower center section, in a position easily accessible to the driver and officer. The climate control shall be activated by a rotary switch.

HVAC OVERHEAD COVER PAINT

The overhead HVAC cover shall be coated with black Spar-Liner.

AUXILIARY CLIMATE CONTROL FRONT UNDERSEAT

One (1) 13,500 BTU heater shall be provided and installed in the face of the under seat storage area below the left hand front seat. The fan controls shall be located on the Vista display and control screen(s).

The auxiliary heater system hoses shall be silicone with stainless steel constant torque clamps approved for use with silicone hose. The auxiliary heater system shall include one (1) seasonal shut-off valve. The valve shall be supplied at the front of the right hand corner of the cab. The cab must be tilted to access the shut-off valve.

A/C CONDENSER LOCATION



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

A roof mounted A/C condenser shall be installed centered on the cab forward of the raised roof against the slope rise.

A/C COMPRESSOR

The air-conditioning compressor shall be a belt driven, engine mounted, open type compressor that shall be capable of producing a minimum of 32,000 BTU at 1500 engine RPMs. The compressor shall utilize R-134A refrigerant and PAG oil.

CAB CIRCULATION FANS FRONT

The cab shall include two (2) all metal 6.00 inch air circulation fans installed outer front cab corners. Each fan shall be controlled by an individual virtual button on the Vista display and control screen or a toggle switch on each fan. The fans shall automatically activate whenever the HVAC is in defrost mode. The fans can be used to help defog the windshield or to increase air circulation for passenger comfort.

UNDER CAB INSULATION

The underside of the cab tunnel surrounding the engine shall be lined with multi-layer insulation, engineered for application inside diesel engine compartments.

The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. As an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.

The engine tunnel insulation shall measure approximately 0.75 inch thick including a vertically lapped polyester fiber layer, a 1.0 lb/ft² PVC barrier layer, an open cell foam layer, and a moisture and heat reflective foil facing reinforced with a woven fiberglass layer. The foil surface acts as protection against moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The insulation shall be cut precisely to fit each section and sealed for additional heat and sound deflection. The insulation shall be held in place by 3 mils of acrylic pressure sensitive adhesive and aluminum pins with hard hat, hold in place fastening heads.

INTERIOR TRIM FLOOR MAT



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive.

The floor shall have an overlay of 5052-H32 aluminum plate with a Spar-Liner finish. The aluminum plate shall be held down with screws and aluminum trim moldings. The step well area aluminum trim molding shall feature a Mebac[®] grit surface finish. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

Proposals offering any step well trim molding other than with the Mebac[®] brand surface shall not be considered.

INTERIOR TRIM

The cab interior shall include painted aluminum trim on the front ceiling, rear crew ceiling, and the cab walls. It shall be removable to assist in maintenance.

REAR WALL INTERIOR TRIM

The rear wall of the cab shall be trimmed with aluminum sheet metal coated with a customer specified interior paint or protective coating.

HEADER TRIM

The cab interior shall feature header trim over the driver and officer dash constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum.

TRIM CENTER DASH

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate. There shall be four (4) holes located on the top of the dash near each outer edge of the electrical access cover for ventilation. The dash shall include cup holders and storage bins.

TRIM LH DASH

The left hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate for a perfect fit around the instrument panel. For increased occupant



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

protection the extreme duty left hand dash utilizes patent pending break away technology to reduce rigidity in the event of a frontal crash. The left hand dash shall offer lower vertical surface area to the left and right of the steering column to accommodate control panels.

TRIM RH DASH

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 6.38 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment.

ENGINE TUNNEL TRIM

The cab engine tunnel shall be covered with a multi-layer mat consisting of 0.25 inch closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The mat shall be held in place by pressure sensitive adhesive. The engine tunnel mat shall be trimmed with anodized aluminum stair nosing trim for an aesthetically pleasing appearance.

POWER POINT DASH MOUNT

The cab shall include one (1) Dual universal serial bus (USB) charging receptacle in the cab dash rocker switch cutout to provide a power source for USB chargeable electrical equipment. One (1) USB port shall be capable of a 5 Volt-1 amp output and One (1) USB port shall be capable of a 5 Volt-2.1 amp output. The receptacles shall be wired battery direct and include a backlit legend.

STEP TRIM

Each cab entry door shall include a three step entry. The first step closest to the ground shall be constructed of polished 5032 H32 aluminum Grip Strut® grating with angled outer corners. The step shall feature a splash guard to reduce water and debris from splashing in to the step. The splash guard shall have an opening on the outer edge to allow debris and water to flow through rather than becoming trapped within the stepping surface. The lower step shall be mounted to a frame which is integral with the construction of the cab for rigidity and strength. The middle step shall be integral with the cab construction and shall be trimmed with a Flex-Tred® adhesive grit surface material.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

STEP TRIM KICKPLATE

The cab steps shall include a kick plate in the rise of each step. The risers shall be trimmed in 3003-H22 bright aluminum tread-plate which is 0.07 inch thick.

UNDER CAB ACCESS DOOR

The cab shall include an aluminum access door in the left crew step riser painted to match the cab interior paint with a push and turn latch. The under cab access door shall provide access to the diesel exhaust fluid fill.

INTERIOR DOOR TRIM

The interior trim on the doors of the cab shall consist of an aluminum panel constructed of Marine Grade 5052-H32 0.13 of an inch thick aluminum plate. The door panels shall include a painted finish.

DOOR TRIM KICKPLATE

The inner door panels shall include an aluminum tread kick plate which shall be fastened to the lower portion of the door panels.

DOOR TRIM SCUFF PLATE

The trim along the door shall include a stainless steel scuff plate along the door jamb to prevent the chipping of paint should the seat belt buckle come in contact with the door jamb.

DOOR TRIM CUSTOMER NAMEPLATE

The interior door trim on the front doors shall include a customer nameplate which states the vehicle was custom built for their Department.

CAB DOOR TRIM REFLECTIVE

The interior of each door shall include high visibility reflective tape. A white reflective tape shall be provided vertically along the outer rear edge of the door. The lowest portion



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

of each door skin shall include solid white reflective tape. The tape shall measure 6.00 inches in height.

INTERIOR GRAB HANDLE "A" PILLAR

There shall be two (2) rubber covered 11.00 inch grab handles installed inside the cab, one on each "A" post at the left and right door openings. The left handle shall be located 7.88 inches above the bottom of the door window opening and the right handle shall be located 2.88 inches above the bottom of the door window opening. The handles shall assist personnel in entering and exiting the cab.

INTERIOR GRAB HANDLE FRONT DOOR

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured black powder coat finish to assist personnel entering and exiting the cab.

INTERIOR GRAB HANDLE REAR DOOR

A black Spar-Liner coated cast aluminum assist handle shall be provided on the inside of each rear crew door. The 30.00 inch long handle shall extend horizontally the width of the window just above the window sill. The handle shall assist personnel in exiting and entering the cab.

INTERIOR SOFT TRIM COLOR

The cab interior soft trim surfaces shall be gray in color.

INTERIOR TRIM SUN VISOR

The header shall include two (2) sun visors, one each side forward of the driver and officer seating positions above the windshield. Each sun visor shall be constructed of Masonite and covered with padded vinyl trim.

In addition to the padded sun visors, two (2) 7.00 inches high X 18.00 inches wide impact resistant, transparent acrylic polycarbonate sun visors with a smoke gray tint shall be provided and installed on the header above the driver and officer.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The see thru visors are designed for maximum flexibility of positioning utilizing an arm with virtually unlimited adjustability with 13.50 inch long lateral travel of the tinted visor at the end of the arm which can be locked in place by a thumbscrew.

The visors are easily adjusted and can be placed into a chosen position with one hand. The sun visors will help protect vehicle occupants from solar glare without obscuring their vision.

INTERIOR FLOOR MAT COLOR

The cab interior floor mat shall be black in color.

CAB PAINT INTERIOR

The inner door panel surfaces shall be coated with Spar-Liner black pebble-grain texture finish.

HEADER TRIM INTERIOR PAINT

The metal surfaces in the header area shall be coated with black Spar-Liner.

TRIM CENTER DASH INTERIOR PAINT

The entire center dash shall be coated with black Spar-Liner. Any accessory pods attached to the dash shall also be coated with this material.

TRIM LEFT HAND DASH INTERIOR PAINT

The left hand dash shall be coated with black Spar-Liner.

TRIM RIGHT HAND DASH INTERIOR PAINT

The right hand dash shall be coated with black Spar-Liner.

REAR WALL INTERIOR PAINT



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The rear wall of the cab shall be trimmed with aluminum sheet metal coated with a protective coating of black Spar-Liner.

FLOOR INTERIOR PAINT

The metal surfaces on the floor of the cab shall be coated with black Spar-Liner.

DASH PANEL GROUP

The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.

SWITCHES CENTER PANEL

The center dash panel shall include six (6) switch positions in the upper left portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SWITCHES LEFT PANEL

The left dash panel shall include four (4) switches. There shall be three (3) across the top of the panel with one (1) below. Two (2) of the top row of switches shall be rocker type and the left one (1) shall be the windshield wiper/washer control switch. The lower switch shall be a rocker type switch.

A rocker switch with a blank legend installed directly above shall be provided for any position not designated by a specific option. The non-designated switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SWITCHES RIGHT PANEL



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The right dash panel shall include no rocker switches or legends.

SEAT BELT WARNING

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall provide a visual warning indicator in the Vista display and control screen(s), an indicator light in the instrument panel, and an audible alarm.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds, the corresponding seat belt remains unfastened, and the park brake is released. The warning system shall also activate when any seat is occupied, the corresponding seat belt was fastened in an incorrect sequence, and the park brake is released. Once activated, the visual indicators and audible alarm shall remain active until all occupied seats have the seat belts fastened.

SEAT MATERIAL

The seats shall include a covering of extra high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Common trade names for this material are Imperial 1800 and Durawear Plus.

SEAT COLOR

All seats supplied with the chassis shall be black in color. All seats shall include red seat belts.

SEAT BACK LOGO

The seat back shall include the "Smeal Fire Apparatus Co." logo. The logo shall be centered on the standard headrest of the seat back and on the left side of a split headrest.

SEAT DRIVER

The driver's seat shall be an H.O. Bostrom Firefighter Sierra model seat. The seat shall feature eight-way electric positioning. The eight positions shall include up and down,



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

fore and aft with 8.00 inches of travel, back angle adjustment and seat rake adjustment. The seat shall feature integral springs to isolate shock.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt, automatic retractor and buckle as an integral part of the seat assembly.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches measured with the seat height adjusted to the lowest position of travel.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207, 209, and 210 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK DRIVER

The driver's seat shall include a standard seat back incorporating the all belts to seat feature (ABTS). The seat back shall feature a contoured head rest.

SEAT MOUNTING DRIVER

The driver's seat shall be installed in an ergonomic position in relation to the cab dash.

OCCUPANT PROTECTION DRIVER

The driver's position shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The driver's seating area APS shall include:

- Advanced seat belt system - retractor pre-tensioner tightens the seat belt around the driver, securing the occupant in the seat and the load limiter plays out some of



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

- Large side curtain airbag - protects the driver's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to the driver in a qualifying event by covering the window and the upper portion of the door.
- Dual knee airbags (patent pending) with energy management mounting (patent pending) - protects the driver's lower body from dangerous surface contact injuries, acceleration injuries, and from intrusion as well as locks the lower body in place so the upper body shall be slowed by the load limiting seat belt.

Steering wheel airbag - protects the driver's head, neck, and upper torso from contact injuries, acceleration injuries, and contact points with intrusive surfaces as a result of a collision.

SEAT OFFICER

The officer's seat shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. The seat shall be a non-adjustable type seat.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK OFFICER

The officer's seat shall feature a SecureAll™ SCBA locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING OFFICER

The officer's seat shall be installed in an ergonomic position in relation to the cab dash.

OCCUPANT PROTECTION OFFICER

The officer's position shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The officer's seating area APS shall include:



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

- Advanced seat belt system - retractor pre-tensioner tightens the seat belt around the officer, securing the occupant in the seat and the load limiter plays out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.
- Large side curtain airbag - protects the officer's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to the officer in a qualifying event by covering the window and the upper portion of the door.

Knee airbags - protects the officer's lower body from dangerous surface contact injuries, acceleration injuries, and from contact points with intrusive surfaces as a result of a collision as well as locks the lower body in place so the upper body shall be slowed by the load limiting seat belt.

POWER SEAT WIRING

The power seat or seats installed in the cab shall be wired directly to battery power.

SEAT BELT ORIENTATION CREW

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

SEAT REAR FACING OUTER LOCATION

The crew area shall include two (2) rear facing crew seats, which include one (1) located directly behind the left side front seat and one (1) located directly behind the right side front seat.

SEAT CREW REAR FACING OUTER

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK REAR FACING OUTER

The rear facing outboard seat shall feature a Bostrom SecureAll™ self contained breathing apparatus (SCBA) locking system which shall store most U.S. and International SCBA brands and bottle sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the center of the bottom seat cushion for easy access and to eliminate hooking the release handle with clothing or other equipment.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING REAR FACING OUTER

The rear facing outer seats shall offer special mounting positions which shall be 2.00 inches towards the rear wall offering additional space between the front seats and the outer rear facing seats.

OCCUPANT PROTECTION RFO

The rear facing outer seat position(s) shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

Each rear facing outer seating position APS shall include:

- APS advanced seat belt system - retractor pre-tensioners tighten the seat belts around each occupant, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

Side curtain airbag - protects each occupant's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to each occupant in a qualifying event by covering the windows and walls adjacent to each seating position with an airbag custom designed for each cab configuration.

SEAT FORWARD FACING CENTER LOCATION

The crew area shall include two (2) forward facing center crew seats with both located at the center of the rear wall.

SEAT CREW FORWARD FACING CENTER



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The crew area shall include a seat in the forward facing center position which shall be a H.O. Bostrom Firefighter series. The seat shall feature a tapered and padded seat, and cushion. The seat and cushion shall be hinged and compact in design for additional room and shall remain in the stored position until occupied.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK FORWARD FACING CENTER

The forward facing center seat shall feature a SecureAll™ self contained breathing apparatus (SCBA) locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto- locking system. Once the lock



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

OCCUPANT PROTECTION FFC

The forward facing center seat position(s) shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

Each forward facing center seating position APS shall include:

- APS advanced seatbelt system - retractor pre-tensioners tighten the seat belts around each occupant, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

Side curtain airbag - provides ejection mitigation protection to each occupant in a qualifying event by covering the windows and walls adjacent to crew seating with an airbag custom designed for each cab configuration.

SEAT FRAME FORWARD FACING

The forward facing center seating positions shall include an enclosed style seat frame located and installed at the rear wall. The seat frame shall measure 62.38 inches wide X 12.38 inches high X 20.00 inches deep. The seat frame shall be constructed of Marine Grade 5052-H32 0.19 inch thick aluminum plate. The forward corners of the bench shall be chamfered 45-degrees X 4.00 inches.

SEAT FRAME FORWARD FACING STORAGE ACCESS



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

There shall be two (2) access points to the seat frame storage area, one (1) on each side of the seat frame. Each access point shall be covered by a hinged door which measures 15.00 inches in width X 10.63 inches in height.

SEAT MOUNTING FORWARD FACING CENTER

The forward facing center seats shall offer a special mounting. The seats shall be installed 6.00 inches apart offering additional room for each occupant.

CAB FRONT UNDERSEAT STORAGE ACCESS

The left and right under seat storage areas shall have a vented aluminum hinged door with non-locking latch.

SEAT COMPARTMENT DOOR FINISH

All underseat storage compartment access doors shall have a protective coating of black Spar-Liner.

HELMET STORAGE FRONT LOCATION

The front cab area shall include two (2) helmet storage brackets located overhead on the right and left hand sides of the cab.

HELMET STORAGE FRONT

The front cab area shall include Ziamatic model UHH-1 helmet storage bracket designed to meet current NFPA regulations. The UHH-1 shall securely fasten fire helmets to flat cab surfaces. The UHH-1 utilizes a helmet hook and an adjustable strap to accommodate nearly any helmet size or configuration.

HELMET STORAGE FRONT CREW OUTER LOCATION

The front outboard crew area of the cab shall include two (2) helmet storage brackets. The brackets shall be located overhead on both the right and left side.

HELMET STORAGE FRONT CREW OUTER



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The front outer crew area shall include Ziamatic model UHH-1 helmet storage designed to meet current NFPA regulations. The UHH-1 shall securely fasten fire helmets to flat cab surfaces. The UHH-1 utilizes a helmet hook and an adjustable strap to accommodate nearly any helmet size or configuration.

HELMET STORAGE REAR CREW CENTER LOCATION

The rear inboard crew area of the cab shall include two (2) helmet storage brackets located overhead on both the right and left side.

HELMET STORAGE REAR CREW CENTER

The rear center crew area shall include Ziamatic model UHH-1 helmet storage designed to meet current NFPA regulations. The UHH-1 shall securely fasten fire helmets to flat cab surfaces. The UHH-1 utilizes a helmet hook and an adjustable strap to accommodate nearly any helmet size or configuration.

WINDSHIELD WIPER SYSTEM

The cab shall include a dual arm wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers which shall be affixed to a radial wet arm. The system shall include a single motor which shall initiate the arm in which both the left hand and right hand windshield wipers are attached, initiating a back and forth motion for each wiper. The wiper motor shall be activated by an intermittent wiper control located within easy reach of the driver's position.

ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR

The windshield washer fluid level shall be monitored electronically. When the washer fluid level becomes low the yellow "Check Message Center" indicator light on the instrument panel shall illuminate and the message center in the dual air pressure gauge shall display a "Check Washer Fluid Level" message.

CAB DOOR HARDWARE

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be made of aluminum with a chrome plated finish.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The interior exit door handles shall be flush paddle type with a black finish, which are incorporated into the upper door panel.

All cab entry doors shall include locks which are keyed alike. The door locks shall be designed to prevent accidental lockout.

The exterior pull handles shall include a scuff plate behind the handle constructed of polished stainless steel to help protect the cab finish.

DOOR LOCKS

Each cab entry door shall include a manually operated door lock. Each door lock may be actuated from the inside of the cab by means of a red knob located on the paddle handle of the respective door or by using a TriMark key from the exterior. The door locks are designed to prevent accidental lock out.

GRAB HANDLES

The cab shall include one (1) 18.00 inch knurled, anti-slip, one-piece exterior assist handle behind each cab door. The assist handle shall be made of 14 gauge 304- stainless steel and be 1.25 inch diameter to enable easy grabbing with the gloved hand. Each assist handle shall include a stainless steel plate which saves the cab from scuffs through continued use of the handle.

AUXILIARY GRAB HANDLE

There shall be a 7.00 inch molded stainless steel grab handle with a bright finish attached to the front fascia of the cab in the center below the windshield. The handle installation shall include a stainless steel scuff plate behind the grab handle to protect the painted surface and a steel reinforcement behind the front cab fascia.

REARVIEW MIRRORS

Retrac Aerodynamic West Coast style dual vision mirror heads model 613305 shall be provided and installed on each of the front cab doors.

The mirrors shall be mounted via 1.00 inch diameter tubular stainless steel arms to provide a rigid mounting to reduce mirror vibration.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The mirrors shall measure 8.00 inches wide X 19.00 inches high and shall include an integral convex mirrors installed in the mirror head below the flat glass to provide a wider field of vision. The flat and convex mirrors shall be motorized with remote horizontal and vertical adjustment. The control switches shall be mounted within easy reach of the driver. The flat and convex mirrors shall be heated for defrosting in severe cold weather conditions.

The mirrors shall be constructed of a vacuum formed chrome plated ABS plastic housing that is corrosion resistant and shall include the finest quality non-glare glass.

REARVIEW MIRROR HEAT SWITCH

The heat for the rearview mirrors shall be controlled through a virtual button on the Vista display and control screen.

EXTERIOR TRIM REAR CORNER

There shall be mirror finish stainless steel scuff plates on the outside corners at the back of the cab. The stainless steel plate shall be affixed to the cab using two sided adhesive tape.

TRIM REAR WALL EXTERIOR

The exterior rear wall of the cab shall include an overlay of 3003-H22 aluminum tread plate which shall be 0.07 inches thick. This overlay shall cover the entire rear wall of the cab.

TRIM ROOF

The raised portion of the cab roof shall include 3003-H22 bright aluminum embossed tread plate which is 0.08 inches thick. This plate shall be intended for reinforcement value and shall start at the rear edge of the roof extending to the radius at the forward end of the raised roof, and shall be the full width of the flat portion of the roof left to right.

The tread plate shall be held in place using stainless steel fasteners and shall be sealed with silver silicone caulk around the perimeter of the tread plate and at each mounting screw.

CAB FENDER



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. Each two-piece liner shall consist of an inner liner 16.00 inches wide made of vacuum formed ABS composite and an outer fenderette 3.50 inches wide made of 14 gauge 304 polished stainless steel.

MUD FLAPS FRONT

The front wheel wells shall have mud flaps installed on them.

IGNITION

A master battery system with a keyless start ignition system shall be provided. Each system shall be controlled by a one-quarter turn Cole Hersee switch, both of which shall be mounted to the left of the steering wheel on the dash. A chrome push type starter button shall be provided adjacent to the master battery and ignition switches.

Each switch shall illuminate a green LED indicator light on the dash when the respective switch is placed in the "ON" position.

The starter button shall only operate when both the master battery and ignition switches are in the "ON" position.

BATTERY

The single start electrical system shall include six (6) Harris BCI 31 950 CCA batteries with a 210 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541.

BATTERY TRAY

The batteries shall be installed within two (2) steel battery trays located on the left side and right side of the chassis, securely bolted to the frame rails. The battery trays shall be coated with the same material as the frame.

The battery trays shall include drain holes in the bottom for sufficient drainage of water. A durable, non-conducting, interlocking mat made by Dri-Dek shall be installed in the bottom of the trays to allow for air flow and help prevent moisture build up. The batteries shall be held in place by non-conducting phenolic resin hold down boards.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

BATTERY BOX COVER

Each battery box shall include a steel cover which protects the top of the batteries. Each cover shall include flush latches which shall keep the cover secure as well as a black powder coated handle for convenience when opening.

BATTERY CABLE

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed at the ends with heat shrink and sealant.

BATTERY JUMPER STUD

The starting system shall include battery jumper studs. These studs shall be located in the forward most portion of the driver's side lower step. The studs shall allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

ALTERNATOR

The charging system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

BATTERY CONDITIONER

A Kussmaul 1200 battery conditioner shall be supplied. The battery conditioner shall be mounted in the cab in the LH rear facing outer seating position.

BATTERY CONDITIONER DISPLAY

A Kussmaul battery conditioner display shall be supplied. The battery conditioner display shall be mounted in the cab, viewable through the cab mid side window behind the left front door.

AUXILIARY AIR COMPRESSOR



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

A Kussmaul Auto Pump 120V air compressor shall be supplied. The air compressor shall be installed behind the officer's seat. The air compressor shall be plumbed to the air brake system to maintain air pressure.

ELECTRICAL INLET

A Kussmaul 20 amp super auto-eject electrical receptacle shall be supplied. It shall automatically eject the plug when the starter button is depressed.

A single item or an addition of multiple items must not exceed the rating of the electric inlet that it's connected to.

Amp Draw Reference List:

Kussmaul 1000 Charger - 3.5 Amps

Kussmaul 1200 Charger - 10 Amps

Kussmaul 35/10 Charger - 10 Amps

1000W Engine Heater - 8.33 Amps

1500W Engine Heater - 12.5 Amps

120V Air Compressor - 4.2 Amps

ELECTRICAL INLET LOCATION

An electrical inlet shall be installed on the left hand side of cab over the wheel well.

ELECTRICAL INLET CONNECTION

The electrical inlet shall be connected to the battery conditioner and the air pump.

ELECTRICAL INLET COLOR

The electrical inlet connection shall include a red cover.

HEADLIGHTS

The cab front shall include four (4) rectangular LED headlamps with separate high and low beams mounted in bright chrome bezels.

FRONT TURN SIGNALS



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The front fascia shall include two (2) Whelen model 600 4.00 inch X 6.00 inch programmable amber LED turn signals which shall be installed in polished aluminum housing above and outboard of the front warning and head lamps.

HEADLIGHT LOCATION

The headlights shall be located on the front fascia of the cab directly below the front warning lights.

SIDE TURN/MARKER LIGHTS

The sides of the cab shall include two (2) LED round side marker lights which shall be provided just behind the front cab radius corners.

MARKER AND ICC LIGHTS

In accordance with FMVSS, there shall be five (5) LED cab marker lamps designating identification, center and clearance provided. These lamps shall be installed on the roof of the cab. The lamps shall be a teardrop shape and include chrome housings. The lights and shall measure 3.00 inches high X 3.75 inches wide X 11.00 inches long.

HEADLIGHT AND MARKER LIGHT ACTIVATION

The headlights and marker lights shall be controlled via a virtual button on the Vista display. There shall be a virtual dimmer control on the Vista display to adjust the brightness of the dash lights. The headlamps shall be equipped with the "Daytime Running" light feature, which shall illuminate the headlights to 80% brilliance when the battery master switch is in the "On" position and the parking brake is released.

GROUND LIGHTS

Each door shall include an NFPA compliant LED ground light mounted to the underside of the cab step below each door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life. The ground lighting shall be activated by the opening of the door on the respective cab side, when the parking brake is set and through a virtual button on the Vista display and control screen.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

LOWER CAB STEP LIGHTS

The middle step located at each door shall include a recess mounted 4.00 inch round LED light which shall activate with the opening of the respective door.

UNDER BUMPER LIGHTS

There shall be two (2) 4.00 inch round LED NFPA compliant ground lights mounted under the bumper. The lights shall include a polycarbonate lens, a housing which is vibration welded, and LEDs which shall be shock mounted for extended life. The under bumper ground lighting shall be interlocked with the park brake and the marker light activation.

ENGINE COMPARTMENT LIGHT

There shall be an incandescent NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall include a polycarbonate lens, a housing which is vibration welded and a bulb which shall be shock mounted for extended life. The light shall activate automatically when the cab is tilted.

INTERIOR OVERHEAD LIGHTS

The cab shall include a red/clear Whelen LED dome lamp located over each door. The dome lamps shall be rectangular in shape and shall measure approximately 7.00 inches in length X 3.00 inches in width with a black colored bezel. The clear function of each lamp shall be activated by opening the respective door. While the door is closed the individual red or clear function of each lamp can be activated dependently by switches on each lamp.

An additional separately functioning red or clear Whelen LED dome lamp shall be provided over the engine tunnel. Each individual function can be activated dependently by switches on the lamp.

MAP LIGHTS

Two (2) Sunnex swivel map lights shall be provided. Each light shall have a clear lens and a control switch on the base. The lights shall be mounted on the overhead HVAC cover, one (1) on each side.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

DO NOT MOVE APPARATUS LIGHT

The front headliner of the cab shall include a flashing red light clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound while the light is activated.

The flashing red light shall be 6.00 inches long X 2.50 inches wide X 1.75 inches high and shall be located centered left to right for greatest visibility.

The light and alarm shall be interlocked for activation when either a cab door is not firmly closed or an apparatus compartment door is not closed, and the parking brake is released.

MASTER WARNING SWITCH

A master switch shall be included, as a virtual button on the Vista display and control screen which shall be labeled "E Master" for identification. The button shall feature control over all devices wired through it. Any warning device switches left in the "ON" position when the master switch is activated shall automatically power up.

HEADLIGHT FLASHER

An alternating high beam headlight flashing system shall be installed into the high beam headlight circuit which shall allow the high beams to flash alternately from left to right.

Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On Scene" when the park brake is applied.

HEADLIGHT FLASHER SWITCH

The flashing headlights shall be activated through a virtual button on the Vista display and control screen.

INBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen 600 Series Super LED Rota-Beam front warning lights in the left and right inboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

INBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the inboard positions shall be red.

OUTBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen 600 series Super LED Rota-Beam front warning lights in the left and right outboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

OUTBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the outboard position shall be red.

FRONT WARNING SWITCH

The front warning lights shall be controlled through a virtual control on the Vista display and control screen. This switch shall be clearly labeled for identification.

INTERSECTION WARNING LIGHTS

The chassis shall include two (2) Whelen 600 series Super LED intersection warning lights, one (1) each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors.

INTERSECTION WARNING LIGHTS COLOR

The intersection lights shall be red.

INTERSECTION WARNING LIGHTS LOCATION

The intersection lights shall be recess mounted into the side face of the bumper.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

SIDE WARNING LIGHTS

The cab sides shall include two (2) Whelen 600 series Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the cab within a chrome bezel.

SIDE WARNING LIGHTS COLOR

The warning lights located on the side of the cab shall be red.

SIDE WARNING LIGHTS LOCATION

The warning lights on the side of the cab shall be mounted over the front wheel well directly over the center of the front axle.

SIDE AND INTERSECTION WARNING SWITCH

The side warning lights shall be controlled through a virtual button on the Vista display and control screen. This button shall be clearly labeled for identification.

INTERIOR DOOR OPEN WARNING LIGHTS

The interior of each door shall include one (1) 15.87 inch long X 0.73 inch tall amber Weldon LED warning light. The light shall be located on the upper portion of the door frame to be visible when a person is standing in front of the door while entering or exiting the cab. Each light shall activate with a scrolling directional flash pattern which moves from inside to outside when the door is in the open position. This shall serve as a warning to oncoming traffic.

SIREN CONTROL HEAD

A Federal PA4000 electronic siren control head shall be provided and flush mounted in the in the switch panel with a location specific to the customer's needs. The siren shall feature 200-watt output, wail, radio broadcast, public address, yelp, priority tones and a noise cancelling microphone.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

HORN BUTTON SELECTOR SWITCH

A virtual button on the Vista display and control panel shall allow control of either the electric horn or the electronic siren from the steering wheel horn button. The electric horn shall sound by default when the selector switch is in either position to meet FMCSA requirements.

AIR HORN ACTIVATION

The air horn activation shall be accomplished by two (2) lanyard cables, one (1) on the left hand side accessible to the driver and one (1) on the right hand side accessible to the officer. An air horn activation circuit shall be provided to the chassis harness pump panel harness connector.

MECHANICAL SIREN ACTIVATION

The mechanical siren shall be actuated by two (2) Linemaster model SP491-S81 foot switches mounted in the front section of the cab for use by the driver and officer. Two (2) siren brake controls shall be provided. One (1) shall be a push button type and one (1) shall be provided on the Vista display.

The siren activation shall be interlocked with the park brake and shall only be active when master warning switch is on to prevent accidental engagement.

ELECTRONIC SIREN AUXILIARY ACTIVATION

The electronic siren shall include activation by the steering wheel horn button.

BACK-UP ALARM

An ECCO model 575 backup alarm shall be installed at the rear of the chassis with an output level of 107 dB. The alarm shall automatically activate when the transmission is placed in reverse.

INSTRUMENTATION

An ergonomically designed instrument panel shall be provided. Each gauge shall be backlit with LED lamps. Stepper motor movements shall drive all gauges. The



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

instrumentation system shall be multiplexed and shall receive ABS, engine, and transmission information over the J1939 data bus to reduce redundant sensors and wiring.

The instrument panel shall contain the following gauges:

One (1) electronic speedometer shall be included. The primary scale on the speedometer shall read from 0 to 100 MPH, and the secondary scale on the speedometer shall read from 0 to 160 KM/H.

One (1) electronic tachometer shall be included. The scale on the tachometer shall read from 0 to 3000 RPM.

One (1) two-movement gauge displaying primary system, and secondary system air volumes and integral LCD odometer/trip odometer shall be included on the lower portion of the LCD. The scale on the air pressure gauges shall read from 0 to 150 pounds per square inch (PSI). The air pressure scales shall be linear to operate with an accuracy of 1 degree of the measured data with a red indication zone on the gauge showing critical levels of air pressure. A red indicator light in the gauge shall indicate a low air pressure, as well as a message on the LCD screen. The odometer shall display up to 9,999,999.9 miles. The trip odometer shall display 9,999.9 miles. The LCD shall display Transmission Temperature in degrees Fahrenheit on the upper portion of the LCD. The LCD screen shall also be capable of displaying certain diagnostic functions.

One (1) four-movement gauge displaying engine oil pressure, coolant temperature, fuel level, voltmeter, and an *indicator bar displaying Diesel Exhaust Fluid (DEF) LED bar shall be included. The scale on the engine oil pressure gauge shall read from 0 to 120 pounds per square inch (PSI). The engine oil pressure scale shall be linear to operate with an accuracy of 1 degree of the measured. A red indicator light in the gauge shall indicate a low engine oil pressure, as well as a message on the LCD screen. The scale on the coolant temperature gauge shall read from 100 to 250 degrees Fahrenheit (F). The coolant temperature scale shall be linear to operate with an accuracy of 1 degree of the measured data with a red indication zone on the gauge showing critical levels of air pressure. A red indicator light in the gauge shall indicate high coolant temperature, as well as a message on the LCD screen. The scale on the fuel level gauge shall read from empty to full as a percentage of fuel remaining. An amber indicator light shall indicate low fuel at 25% tank level. The scale on the voltmeter shall read from 10 to 16 volts with a red indication zone on the gauge showing critical levels of battery voltage. A red indicator light shall indicate high or low system voltage, as well as a message on the LCD screen. The scale on the DEF LED bar will consist of four (4) LEDs displaying levels in increments of 25% of useable DEF in green. Upon decreasing levels, the indicator bar will change colors to notify the driver of decreasing levels of DEF and action will be required. An amber indicator light shall indicate low levels of DEF, as well as a message on the LCD screen and an audible alarm.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

The instrument panel shall include a light bar that contains the following LED indicator lights and produce the following audible alarms in applicable configurations:

RED LAMPS

Stop Engine-indicates critical engine fault

Air Filter Restricted-indicates excessive engine air intake restriction

Park Brake-indicates parking brake is set

Seat Belt Indicator-indicates when a seat is occupied and corresponding seat belt remains unfastened

Low Coolant-indicates engine coolant is required

AMBER LAMPS

MIL-indicates an engine emission control system fault

Check Engine-indicates engine fault

Check Trans-indicates transmission fault

High Transmission Temperature-indicates excessive transmission oil temperature

ABS-indicates anti-lock brake system fault

HEST-indicates a high exhaust system temperature

Water in Fuel-indicates presence of water in fuel filter

*DPF-indicates a restriction of the diesel particulate filter

*Regen Inhibit-indicates regeneration has been postponed due to user interaction

Range Inhibit-indicates a transmission operation is prevented and requested shift request may not occur.

*SRS-indicates a problem in the supplemental restraint system

Check Message-Turn Signal On

Check Message-Door Ajar

Check Message-Cab Ajar

*Check Message-ESC Active

*Check Message-DPF Regen Active

Check Message-No Engine Data

Check Message-No Transmission Data

Check Message-No ABS Data

Check Message-No Data All Communication With The Vehicle Systems Has Been Lost

Check Message-Check Engine Oil Level

Check Message-Check Washer Fluid Level

Check Message-Check Power Steering Fluid Level

Check Message-Low Transmission Fluid Level

Check Message-Check Coolant Level

GREEN LAMPS

Left and Right turn signal indicators

*ATC-indicates low wheel traction for automatic traction control equipped vehicles, also indicates mud/snow mode is active for ATC system

High Idle-indicates engine high idle is active.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Cruise Control-indicates cruise control is active
OK to Pump-indicates the pump engage conditions have been met
Pump Engaged-indicates the pump is currently in use
Auxiliary Brake-indicates secondary braking device is active

BLUE LAMP

High Beam Indicator

WHITE LAMP

Wait to Start-indicates active engine air preheat cycle

AUDIBLE ALARMS FROM GAUGE PACKAGE

High Trans Temp
High or Low Voltage
Check Engine
Check Transmission
Stop Engine
Low Air Pressure
Fuel Low
Water in Fuel
*ESC
High Coolant Temperature
Low Engine Oil Pressure
Low Coolant Level
*Low DEF Level
Air Filter Restricted
Extended Left and Right Turn Remaining On
Cab Ajar
Door Ajar
ABS System Fault
Seatbelt Indicator

EXTERNAL AUDIBLE ALARM

Air Filter
Cab Ajar
Door Ajar
Check Engine
Stop Engine
Low Air Pressure
Low Engine Oil Pressure
Water in Fuel
*Low DEF
ABS System Fault
Seatbelt Indicator



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

*Items marked with an asterisk are provided only in applicable configurations.

LCD MESSAGES

Transmission Temperature
Battery Voltage
Engine Hours
Vehicle Speed
Engine RPMs
Fuel Level
DEF Level
Engine Oil Pressure
Ammeter (If quipped)
Auxiliary Ammeter (If quipped)
Engine Coolant Temp
Primary System Air Pressure
Secondary System Air Pressure
Turbo Boost Pressure
Exhaust Temperature
Engine Load
Engine Torque
Instant Fuel Economy
Average Fuel Economy

BACKLIGHTING COLOR

The instrumentation gauges and the switch panel legends shall be backlit using blue LED backlighting.

RADIO

A Jensen radio with weather band, AM/FM stereo receiver, compact disc (CD) player, and four (4) speakers shall be installed in the cab. The radio shall include rear RCA input pigtail connector, satellite radio capability, and a covered front auxiliary mini stereo input with iPod ready USB jack. The CD player shall be compatible with CD-R, CD-RW and MP3 format discs. The radio shall be installed in the left hand overhead position. The speakers shall be installed inside the cab with two (2) speakers recessed within the headliner of the front of the cab just behind the windshield and two (2) speakers on the upper rear wall of the cab.

AM/FM ANTENNA



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

A small antenna shall be located on the left hand side of the cab roof for AM/FM and weather band reception.

CAMERA

An Audiovox Voyager heavy duty rearview camera system shall be supplied. The system shall include one (1) box shaped camera shall be shipped loose for OEM installation in the body to afford the driver a clear view to the rear of the vehicle as well as one (1) box shaped camera which shall be mounted on the officer side of the cab above the front door. The officer side camera shall have a brush shield mounted around the perimeter of the camera painted upper cab color.

The camera shall be wired to dual Weldon Vista displays which shall be located on the driver and officer sides of the dash. The rear camera display shall activate when the vehicle's transmission is placed in reverse. The side camera display shall activate when the respective side turn signal is activated. The camera system display can also be activated through the Vista display panel.

CAB EXTERIOR PROTECTION

The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer.

FIRE EXTINGUISHER

A 2.50 pound D.O.T approved fire extinguisher with BC rating shall be shipped loose with the cab.

ROAD SAFETY KIT

The cab and chassis shall include one (1) emergency road safety triangle kit.

DOOR KEYS

The cab and chassis shall include a total of four (4) door keys for the manual door locks.

DIAGNOSTIC SOFTWARE OCCUPANT PROTECTION



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

Diagnostic software for the Spartan Advanced Protection System shall be available for free download from the Spartan Chassis website to Spartan authorized OEMs, dealers and service centers, as well as the vehicle owner.

The software has been validated to be compatible with the following RP1210 interface adapters:

- Dearborn Group DPA4 Plus
- Noregon Systems JPRO[®] DLA+
- Cummins INLINE5
- Cummins INLINE6
- NexIQ[™] USB-Link[™]

The software and adapter utilize the SAE J1939-13 heavy duty nine (9) pin connector which is located below the driver's side dash to the left of the steering column.

WARRANTY

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN CHASSIS, INC. LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The chassis manufacturer shall provide a limited parts and labor warranty to the original purchaser of the custom built cab and chassis for a period of twenty-four (24) months, or the first 36,000 miles, whichever occurs first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

CAB AND CHASSIS LABELING LANGUAGE

The cab and chassis shall include the applicable caution, warning, and safety notice labels with text to be written in English.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

CHASSIS OPERATION MANUAL

There shall be two (2) digital copies of the chassis operation manual provided with the chassis. The digital data shall include a parts list specific to the chassis model.

ENGINE AND TRANSMISSION OPERATION MANUALS

The following manuals specific to the engine and transmission models ordered will be included with the chassis in the ship loose items:

- (2) Digital copies of the Engine Owner's manual
- (2) Digital copies of the Transmission Operator's manual
- (2) Hard copies of the Engine Operation and Maintenance manual with CD

ENGINE SERVICE MANUALS

There shall be two (2) printed hard copy sets of Cummins ISX engine service reference manuals which shall be provided with the chassis.

TRANSMISSION SERVICE MANUALS

There shall be one (1) printed hard copy set of Allison 4000 transmission service manuals included with the chassis.

CAB/CHASSIS AS BUILT WIRING DIAGRAMS

The cab and chassis shall include two (2) digital copies of wiring schematics and option wiring diagrams.

SALES TERMS

The sale of the Spartan Chassis shall be governed by the terms contained on the Sales Terms – Acceptance of Purchase Order document, a copy of which is attached to this option.



610 WEST 4TH ST. - P.O. BOX 8
SNYDER, NEBRASKA 68664

smeal.com
(402) 568-2224

WE BUILD RESPECT.

Smeal Top Mount Pumper Demo #S4455

DRIVELINE LAYOUT CONFIRMATION

During the design phase of the chassis the Spartan Chassis driveline engineer shall submit the driveline layout to an OEM engineer to review the chassis design for any potential problems integrating the OEM body to the chassis. The OEM engineer shall provide approval to the driveline engineer prior to driveline bills of materials being released.